## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

NO. F6/DFS/MS/ EH/2013/194

Dated: 23/04/13

## FIRE SAFETY CERTIFICATE

Certified that O<sub>2</sub> Multicuisine Restaurant (name of the building or premises) located at 23-A(GF & FF), N N Tower, Block B, Road No. 44, DDA Commercial Complex, Pitampura, Delhi was granted NOC by this department vide letter No. F.6/MS/DFS/EH/09/2973 dated 07-10-2009. The premises was re-inspected by the officer concerned of this department on 13-04-2013 in the presence of Mr. M.S. Rana, and observed that all the fire prevention and fire safety arrangements as provided in the premises found in good working condition. The premises / building is fit for occupancy class D, Assembly with effect from 23/04/13 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to conditions printed below.

Issued on 23/04/13 at New Delhi by.

(SANTOKH SINGH) CHIEF FIRE OFFICER DELHI FIRE SERVICE

Tel:- 011-23414250 E-mail:- cfowz.dlfire@nic.in

Copy to: -

1. The Addl.C.P (Lic.), 1<sup>st</sup> floor, Police Station Defence Colony, New Delhi.

2. The Owner, O<sub>2</sub> Multicuisine Restaurant, 23-A, NN Tower, Road No. 44, Pitampura, Delhi

## Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

(Ground + one upper flows)

|           | INSPE  | CTION REPORT                          |  |                                     |  |  |
|-----------|--|---------------------------------------|--|-------------------------------------|--|--|
|           | 1. Name & address of the building:   | Pulticuisine H                        | estament so                                  | ANNIT                               |  |  |
|           | 2. Type of Occupancy : Asse  | mbly                                  | Roc  | ad No-44, Pitanel                   |  |  |
|           | 1. Name & address of the building: Og Multicuisine Restaurant 23-A NN Towe  2. Type of Occupancy: Assembly Road No-44, Pitam  3. Type of Case: New Case/ Renewal   |                                       |  |                                     |  |  |
| 39        | 4. Details of previous NOC : Letter No. F-6 DFS MS EH 09 2973 Dated: 07 10 09  |                                       |  |                                     |  |  |
|           | 5. Fire Safety directives letter No :  |                                       |  |                                     |  |  |
| 9         | 6. Date of inspection : 13 4 2013  7. Name of the Inspecting Officers : DO (MN) & ADO(WP)  8. Name and designation of officers from the building side : Lh. M.S. Rana  |                                       |  |                                     |  |  |
| i         |  |                                       |  |                                     |  |  |
|           |  |                                       |  |                                     |  |  |
|           |  |                                       |  |                                     |  |  |
| 9         | 9. Year of Construction : 2005   |                                       |  |                                     |  |  |
| 1         | 0. Applicant's letter No. : DHO  | 1R7113/120                            | 2 St. 21/03                                  | 12012                               |  |  |
|           |  | 1 1 - 1 - 2                           |  |                                     |  |  |
| S.<br>No. | Minimum Standards on fire prevention and fire safety U/R 33  | NBC                                   | Provided at site                             | Remarks                             |  |  |
|           | II.  | Requirement                           |  | MR/NMR                              |  |  |
| 1         | Access to building   |                                       |  |                                     |  |  |
|           | Road width   | 6 mtr.                                | D plant                                      | 0.0                                 |  |  |
|           | Gate width   |                                       | mided  | MR                                  |  |  |
|           |  |                                       | 1 A 1 A                                      | 1 A                                 |  |  |
|           | <ul> <li>Width of internal road</li> </ul>   | NA                                    | NA   | NA                                  |  |  |
| 2         |  | NA                                    | MA   | MA                                  |  |  |
| 2         | Number, Width, Type & Arrangement of E   | NA                                    |  |                                     |  |  |
| 2         | Number, Width, Type & Arrangement of E   | NA                                    |  |                                     |  |  |
| 2         | Number, Width, Type & Arrangement of E  a. Number of staircases  • Upper Floors  | NA                                    |  |                                     |  |  |
| 2         | Number, Width, Type & Arrangement of E  a. Number of staircases  • Upper Floors  • Basements   | Exits                                 | NA   | MA                                  |  |  |
| 2         | Number, Width, Type & Arrangement of E  a. Number of staircases  • Upper Floors  • Basements  b. Width of staircases   | NA<br>exits                           | Britaled<br>NA                               | MA                                  |  |  |
| 2         | Number, Width, Type & Arrangement of E  a. Number of staircases  • Upper Floors  • Basements  b. Width of staircases  • Upper Floors   | NA<br>exits                           | Privided NA                                  | MR<br>MR<br>NA                      |  |  |
| 2         | Number, Width, Type & Arrangement of E  a. Number of staircases  • Upper Floors  • Basements  b. Width of staircases  • Upper Floors  • Basements  | NA Exits  02 NA                       | Britaled<br>NA                               | MR<br>MR<br>NA                      |  |  |
| 2         | Number, Width, Type & Arrangement of E  a. Number of staircases  • Upper Floors  • Basements  b. Width of staircases  • Upper Floors  • Basements  c. Protection of exits  | NA Exits  02 NA  Old Carp             | Provided<br>NA<br>1)1.48m<br>2)0.97m         | MR<br>NA<br>Mil old case            |  |  |
| 2         | Number, Width, Type & Arrangement of E  a. Number of staircases  • Upper Floors  • Basements  b. Width of staircases  • Upper Floors  • Basements  c. Protection of exits  • Fire check door   | NA Exits  02 NA  Old Carp             | Provided<br>NA<br>1)1.48m<br>2)0.97m         | MR<br>NA<br>MR Old Case<br>NA       |  |  |
|           | Number, Width, Type & Arrangement of E  a. Number of staircases  • Upper Floors  • Basements  b. Width of staircases  • Upper Floors  • Basements  c. Protection of exits  • Fire check door  • Pressurization   | NA Exits  O2 NA  Old Carp  MA         | Privided<br>NA<br>1) 1.48m<br>2) 0.97m<br>NA | MR<br>NA<br>MR old case<br>NA       |  |  |
|           | Number, Width, Type & Arrangement of E  a. Number of staircases  • Upper Floors  • Basements  b. Width of staircases  • Upper Floors  • Basements  c. Protection of exits  • Fire check door  • Pressurization  e. No. of continuous staircases to terrace | NA Exits  02 NA  Old Care  NA  NR  NR | Privided NA  1) 1.48m 2) 0.97m NA  NA        | MR<br>NA<br>MR old case<br>NA<br>NA |  |  |
|           | Number, Width, Type & Arrangement of E  a. Number of staircases  • Upper Floors  • Basements  b. Width of staircases  • Upper Floors  • Basements  c. Protection of exits  • Fire check door  • Pressurization   | NA Exits  02  NA  Old Care  MA  NR    | Privided<br>NA<br>1) 1.48m<br>2) 0.97m<br>NA | MR<br>NA<br>MR old case<br>NA       |  |  |

|    | a design                                      |                 |          |     |
|----|---|-----------------|----------|-----|
|    | Compartmentation.                             | Required        | Burded   | Md  |
|    | Fire check door                               | MR              | NA       | NA  |
|    | Sealing of electrical shafts                  |                 | MA       | NA  |
|    | Fire Rating of shaft door                     | NR              |          | NA  |
|    | Water Curtain                                 | NR              | NA       |     |
|    | Fire Dampers                                  | MR              | MA       | MA  |
|    | Smoke Management System.                      |                 | 110      | NA  |
|    | Basements                                     | 30 a/c per hour | NA       |     |
| 1  | Upper floors                                  | 12 a/c per hour | Provided | MR  |
|    | Fire Extinguishers                            |                 | 0        | MR  |
|    | Total numbers                                 | 06              | Provided |     |
|    | · Types Co24-Slcp. & ARC-Slcp.                | ISI marked      | Provided | MR  |
|    | IS marking                                    |                 | Provided | MR  |
| 6  | First-Aid Hose Reels.                         |                 | 0        |     |
|    | Total numbers on each floor                   | one             | mided    | MR  |
| -  | <ul> <li>Length of hose reel hose</li> </ul>  | 30 m            | Bruided  | MR  |
|    | Nozzle diameter                               | 5 mm            | Provided | mr  |
| 7  | Automatic fire detection and alarming syst    | em.             |          |     |
|    | Type of detectors                             |                 |          |     |
|    | <ul> <li>Location of Main Panel</li> </ul>    |                 |          |     |
|    |   |                 |          |     |
|    | Location of Repeater Panel                    |                 | MP       |     |
|    | Alternate source of power                     |                 |          |     |
|    | Hooters' Location                             | 0.00            | Porrided | mR  |
| 8  | MOEFA   | Required        |          |     |
| 9  | Public Address System.                        | NR              | NA       | NA  |
| 10 | Automatic Sprinkler System.                   |                 |          |     |
|    | Basement                                      | NA              | NA       | NA  |
|    | II Eleca                                      | Repaired        | bonded   | mer |
|    | Opper Floor     Sprinkler above false ceiling | NA              | NA       | NA  |
| 1  |   |                 |          |     |
| 1  | Size of riser/down-comer                      | 100 mm          | movided  | me  |

|     |  |          | 0         |           |
|-----|--|----------|-----------|-----------|
| 1   | <ul> <li>Number of hydrants per floor</li> </ul>             | One      | Provided  | MR        |
|     | • Hose Box   | One      | provided  | mR        |
| 12  | Yard Hydrants.   |          |           |           |
|     | Total number of hydrants                                     |          |           |           |
|     | Hose Box   |          | MR        |           |
| 13  | Pumping Arrangements.  |          |           |           |
|     | Ground Level   |          |           |           |
|     | <ul><li>Discharge of main Pump</li></ul>                     |          |           |           |
|     | Head of Main pump  |          |           |           |
|     | Number of main pumps   |          |           |           |
|     | Jockey Pump out put  |          |           |           |
|     | Jockey pump head   |          | 12        |           |
|     | Standby Pump out put   |          | M         |           |
|     | <ul><li>Standby Pump Head</li></ul>                          |          |           |           |
|     | <ul><li>Auto Starting/ Manual stopping</li></ul>             |          |           |           |
|     | Pump House Access  | ./       |           |           |
| -   | Terrace level  | t 0 18M  | forded    | mr        |
|     | <ul><li>Discharge of pump</li><li>Head of the pump</li></ul> | 450 LPM  | Brided    | mr        |
|     | Power Supply   | 36 mtr.  | 0         | MR        |
|     |  | Required | bonded    | ms        |
|     | ➤ Auto Starting of pump                                      | Required | pronaed   |           |
|     |  |          |           |           |
| 14  | Captive Water Storage for fire fighting.                     |          | * 11      |           |
|     | Underground tank capacity                                    | NR       | NA        | M         |
|     | Draw-off connection  | NR       | AN        | NA        |
|     | ➤ Fire service inlet   | NR       | Provided  | NA        |
|     | > Access to tank   | NR       | MA        | MA        |
| 1   | Overhead Tank capacity                                       |          | 5,000 Us. |           |
| 1.5 | Euld Clause  | old case | 0         | old case. |
| 15  | Exit Signage.  | Required | Provided  | MR        |
| 16  | Provision of Lifts.  | V        |           | <u>ر</u>  |
|     | Pressurization of Lift Shaft                                 | 7        | 1112      |           |
|     | Pressurization of Lift lobby                                 |          | - W/V     |           |
|     |  |          |           |           |

|    |  | · ·                        |
|----|--|----------------------------|
| ,  | Communication In lift Car     Cranding Switch                            | W/8                        |
|    | <ul><li>Fireman's Grounding Switch</li><li>Lift Signage</li></ul>        | 1 1 1 COCKUA) DOB          |
| 17 | Standby power supply   | Required mided Da Bet)     |
| 18 | Refuge Area.   |                            |
|    | > Total Area   | , N/R                      |
|    | > Location   |                            |
| 19 | Fire Control Room  |                            |
|    | Detector System Panel  |                            |
|    | Flow Switch Panel  |                            |
|    | PA System Panel  | 216                        |
|    | Batter backup  |                            |
|    | <ul> <li>Building Floor Plans</li> </ul>                                 | Cubuna Tand                |
| 20 | Special Fire Protection Systems for Protection of special Risks, if any: | Roof level and strikler mr |

The fire protection systems provided in the building were test checked and found functional at the time of CTOR inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.....

Signature of the Inspecting Officer

Name S. k. Dua

Designation ADO (WP)

Signature of the Inspecting Officer

Name Sunil Chaudhary
Designation DO (W)