GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. F6/DFS/MS/2013 / 239

Dated: 01/05 /2013

FIRE SAFETY CERTIFICATE

Conditions for the validity of Fire Safety Certificate:

- 1 All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2 Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3 The trained fire fighting staff should be available round the clock.
- 4 Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5 The basement shall be used strictly as per the provision of building bye laws.
- 6 This certificate cannot be treated in any case for regularizations of unauthorized construction
- 7 The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on WWW.dfs.Delhigovt.nic.in

(SANTOKH SINGH)
Chief Fire Officer
Delhi Fire Service
Ph: 011-23414250

cfowz.dlfire@nic.in

90

Copy to:

1. The Dy. Health Officer, Civil line Zone, North Delhi Municipal Corporation, 16, Raj pur Road, Delhi.

2. Shanti Royal Banquets B-4, G.T.K Road Ind. Area Delhi 110033.

	INSPECT	ION REPORT			54				
1.	Name & address of the building: SHAN	IT! ROYAL !	Banquets B-4	S.T. K.Rd. 2	1. Aseer				
2	Type of Occupancy : Ban	gnet Hall	(Assembly) *	Jemi 11003)				
3.	Type of Case : New Ca:	se/Renewal for	Assembly is	Idag.	¥				
4.	Name & address of the building: SHANT! ROYAL BANQUETS R-49. TIKED Sein!! Type of Occupancy: Ranguet Hall (Assembly) New Case/ Renewal for Assembly Blog. Details of previous NOC: Letter No								
5.	S 414	FS/MS/2012/1	3 P/3553 dt.	26/9/12					
6.									
7.	0.00	ovifin Kens	al & D.O S.	S. Tuli					
8.	Name and designation of officers	,							
	from the building side :								
9.	Year of Construction : 26	012		77					
10	. Applicant's letter No. :	il olt. 21	-3-13						
		NDC	D 111144	Remarks					
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	MR/NMR					
1	Access to building		9:						
	Road width								
	Gate width	u u	/	-	*				
	Width of internal road		-/						
2	Number, Width, Type & Arrangement	of Exits		S					
	a. Number of staircases	2							
	Upper Floors								
	• Basements		/						
	b. Width of staircases	/		0.7.8	,				
	Upper Floors				×				
	• Basements								
	c. Protection of exits	1	¥.						
	Fire check door	R	P	MIR -					
	Pressurization								
	e. No. of continuous staircases to terrace								
	g. Width of Corridor								
M	h. Door Size	02 Mtr.	P	MIR -					
3	Compartmentation.								
V	Fire check door	R	P	M/R.					
	Sealing of electrical shafts								
	Fire Rating of shaft door		/		100				
	Water Curtain								
	Fire Dampers	No. descriptions	/						
4	Smoke Management System.								
N	Basements	30 a/c per hour	P	MIR					
	Upper floors	12 a/c per hour	D	MIN -					

Fire Extinguishers 08 Nos of W.G.L 08 Nos of 162 ISI marked Typo Total numbers Types YOS IS marking First-Aid Hose Reels. 6 MIR Total numbers on each floor 2 0453 Length of hose reel hose MIR 30 m 5 mm MIR Nozzle diameter Automatic fire detection and alarming system. 7 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power · Hooters' Location MOEFA 8 9 Public Address System. Automatic Sprinkler System. 10 Basement Upper Floor Sprinkler above false ceiling 11 **Internal Hydrants** Size of riser/down-comer Number of hydrants per floor MIR Hose Box 2 MMS 12 Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. 13 Ground Level Discharge of main Pump > Head of Main pump MIN 4 Ners > Number of main pumps Jockey Pump out put Jockey pump head MIL 2280 UM Standby Pump out put MIR yo mtr Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump

	= <u>Gay</u> *****	5	10				
4	Captive Water Storage for fire fighting.						
	Underground tank capacity	50000	P	MIR			
	> Draw-off connection			<u> </u>			
	Fire service inlet			6.			
	Access to tank						
	Overhead Tank capacity						
15	Exit Signage.	R.	8	MIR			
16	Provision of Lifts.						
***************************************	Pressurization of Lift Shaft			12			
	Pressurization of Lift lobby	-		*			
	Communication In lift Car						
	Fireman's Grounding Switch						
	Lift Signage						
17	Standby power supply						
18	Refuge Area.						
	> Total Area	4					
	> Location						
19	Fire Control Room						
	Detector System Panel			-			
	Flow Switch Panel						
	PA System Panel		2				
	Batter backup						
	Building Floor Plans						
20	Special Fire Protection Systems for Protection of special Risks, if any:	Separate Circuit for convergency serv	P	M/R.			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers......

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name

Name

Designation

Designation