GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: cfohq.dlfire@nic.in, Tel:- 011-23414333

NO.F6/DFS/MS/EH/2013/ 274

Dated: 08/05/13

FIRE SAFETY CERTIFICATE

Certified that M/s Yum! Restaurant (India) Pvt. Ltd. located at ground & mezzanine floor of A-12, Connaught Circus, New Delhi-110001 of a building comprised of basement, ground & three upper floors was granted NOC by this department vide letter No. F.6/DFS/MS/EH/2009/2633 dated 26-08-2009. The premises was re-inspected by the officer concerned of this department on 26-04-2013 in the presence of Mr. Harvinder, Liaison Manager and found that the said restaurant have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class Assembly (Restaurant) with effect from <u>08/05/1/2</u>— for a period of **3(three)** years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules,2010.

Issued on - at New Delhi by.

(Dr. G.C. Misra) **CHIEF FIRE OFFICER DELHI FIRE SERVICE**

Copy to: -

1. The Additional Commissioner of Police (Lic), 1st floor, Police Station, Defence Colony, New Delhi.

2. The Medical Officer of Health, NDMC, Health Department, Palika Kendra, New

3. The Authorized Signatory, M/s Yum! Restaurant (India) Pvt. Ltd., A-12, Connaught Circus, New Delhi-110001

Conditions for the validity of fire safety certificate

a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.

b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.

The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building: M/s Yum! Restaurants (India) Pvt.Ltd., A-12, Connaught

Circus, NewDelhi-110001

2. Type of Occupancy

: Eating House

3. Type of Case

: Renewal

4. Details of previous NOC

: Letter NoF.6/DFS/MS/EH/09/ 2633 Dated: 26-08-2009

5. Fire Safety directives letter No

: N/A

6. Date of inspection

: 26-04-2013

7. Name of the Inspecting Officers : M.K.Chattopadhyay, ADO(CC)

8. Name and designation of officers

from the building side

: Mr. Harvinder, Liaison Manager

9. Year of Construction

: 1960 & Starting year 2005

10. Applicant's letter No.

: Nil dated 16-11-2012

lo.	Minimum Standards on fire prevention and fire safety U/R 33	NB0 Require		Provided at site	Remarks MR/NMR
	Access to building				
	Road width	06 mts	More	than 06 mts	MR
	Gate width		Direct	tly accessible from	MR
	 Width of internal road 		parking space		
		N/A	N/A		N/A
Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	_		_	~
	• Upper Floors	02		02	MR
	• Basements	N/A		N/A	N/A
	b. Width of staircases				
	• Upper Floors	1.25 mts		1.30 mts, 0.80 mts	MR
	 Basements 	N/A		N/A	N/A
	c. Protection of exits				
	 Fire check door 	N/A		N/A	N/A
	 Pressurization 	N/A		N/A	N/A
	e. No. of continuous staircases to terrace	01		01	MR
	g. Width of Corridor	N/A		N/A	N/A
	h. Door Size	N/A		N/A	N/A
		N/A		N/A	N/A



 Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers Types IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming sy Type of detectors Location of Main Panel 	0 m mm stem.	N/A N/A N/A N/A N/A N/A N/A N/A Smoke venting provided in kitchen Provided Provided Provided Provided Provided Provided Provided	N/A N/A N/A N/A N/A N/A N/A MR MR MR MR MR MR MR MR
 Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers Types IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming sy Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power 	N/A	N/A N/A N/A N/A N/A Smoke venting provided in kitchen Provided Provided Provided Provided Provided Provided Provided	N/A N/A N/A N/A N/A MR MR MR MR MR
 Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers Types IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming sy Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power 	J/A	N/A N/A N/A Smoke venting provided in kitchen Provided Provided Provided Provided Provided Provided Provided Provided	N/A N/A N/A N/A MR MR MR MR MR MR
• Fire Dampers Smoke Management System. • Basements • Upper floors Fire Extinguishers • Total numbers • Types • IS marking First-Aid Hose Reels. • Total numbers on each floor • Length of hose reel hose • Nozzle diameter Automatic fire detection and alarming sy • Type of detectors • Location of Main Panel • Location of Repeater Panel • Alternate source of power	N/A 30 a/c per hour 22 a/c per hour 05 Water CO ₂ , ABC (SI marked) 1 0 m mm stem. N/R	N/A Smoke venting provided in kitchen Provided Provided Provided Provided Provided Provided Provided Provided	N/A N/A MR MR MR MR MR MR
Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming sy Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power	30 a/c per hour 12 a/c per hour 15 Water CO ₂ , ABC (SI marked) 1 0 m mm stem. N/R	N/A Smoke venting provided in kitchen Provided Provided Provided Provided Provided Provided Provided Provided	N/A MR MR MR MR MR MR
 Basements Upper floors Fire Extinguishers Total numbers Types IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming sy Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power 	2 a/c per hour 05 Water CO ₂ , ABC (SI marked) 1 0 m mm stem.	Smoke venting provided in kitchen Provided Provided Provided Provided Provided Provided Provided Provided	MR MR MR MR MR MR
 Basements Upper floors Fire Extinguishers Total numbers Types IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming sy Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power 	2 a/c per hour 05 Water CO ₂ , ABC (SI marked) 1 0 m mm stem.	Smoke venting provided in kitchen Provided Provided Provided Provided Provided Provided Provided Provided	MR MR MR MR MR MR
Fire Extinguishers Total numbers Types IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming sy Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power	05 Water CO ₂ , ABC (SI marked) 1 0 m mm stem.	Provided Provided Provided Provided Provided Provided Provided Provided Provided	MR MR MR MR
 Total numbers Types IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming sy Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power 	Water CO ₂ , ABC [SI marked] 1 0 m mm stem.	Provided Provided Provided Provided Provided	MR MR MR MR
Types IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming sy Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power	Water CO ₂ , ABC [SI marked] 1 0 m mm stem.	Provided Provided Provided Provided Provided	MR MR MR MR
 IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming sy Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power 	ISI marked 1 0 m mm stem.	Provided Provided Provided Provided	MR MR MR
First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming sy Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power	1 0 m mm stem.	Provided Provided Provided	MR MR
 Total numbers on each floor Length of hose reel hose Nozzle diameter 7 Automatic fire detection and alarming sy Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power 	0 m mm stem.	Provided Provided	MR
 Length of hose reel hose Nozzle diameter Automatic fire detection and alarming sy Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power 	0 m mm stem.	Provided Provided	MR
 Nozzle diameter Automatic fire detection and alarming sy Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power 	mm stem. N/R	Provided	
 Automatic fire detection and alarming sy Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power 	stem. N/R		MR
 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power 	N/R		
 Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power 	N/R		
 Location of Main Panel Location of Repeater Panel Alternate source of power 		Smoke type	MR
Alternate source of power	N/R	Ground floor	MR
	N/R	Ground floor	MR
Hooters' Location	N/R	UPS &D.G.Set	MR
	N/R	reception	MR
8 MOEFA	Required	Provided	MR
9 Public Address System.	N/A	N/A	N/A
10 Automatic Sprinkler System.			
Basement	N/A	N/A	N/A
Upper Floor	Required	Provided	MR
Sprinkler above false ceiling		N/A	N/A
11 Internal Hydrants		IN/A	

7				
	Size of riser/down-comer	N/A	N/A	N/A
	Number of hydrants per floor	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
12	Yard Hydrants.			
	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
13	Pumping Arrangements.			h
	Ground Level			
	Discharge of main Pump	N/A	N/A	N/A
	➤ Head of Main pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	Jockey Pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	Standby Pump out put	N/A	N/A	N/A
	Standby Pump Head	N/A	N/A	N/A
	Auto Starting/ Manual stopping	N/A	N/A	N/A
	Pump House Access	N/A	N/A	N/A
	Terrace level			
	Discharge of pump	450 LPM, 180 LPM	Provided	MR
2	➤ Head of the pump	Required	Provided	MR
	Power Supply	Required	Starting switch	MR
	Auto Starting of pump		provided at GF	
14	Captive Water Storage for fire fighting.			
	Underground tank capacity	N/A	N/A	N/A
	Draw-off connection	N/A	N/A	N/A
	Fire service inlet	N/A	N/A	N/A



	> Access to tank	N/A	N/A	N/A		
	Overhead Tank capacity	5,000 lts	provided	MR		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A			
	Communication In lift Car	N/A	N/A			
	Fireman's Grounding Switch	N/A	N/A			
	Lift Signage	N/A	N/A			
17	Standby power supply	Required	Provided	MR		
18	Refuge Area.					
	> Total Area	N/A	N/A	N/A		
	> Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector System Panel	N/A	N/A	N/A		
	Flow Switch Panel	N/A	N/A	N/A		
	PA System Panel	N/A	N/A	N/A		
	Batter backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	ABC type fire extinguisher provided near elect. panel	MR		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

> Signature of the Inspecting Officer Name M.K.Chattopadhyay

Designation: - ADO(CC)