GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI -110001 Fax: 23412593 E-mail:cfohq.dlfire@nic.in

No F8/DFS/MS/2013/269

Dated 7/5/2013

FIRE SAFETY CERTIFICATE

Certified that the Poorva Shanskriti Kendra at plot No. 14, Distt. Centre Laxmi Nagar Delhi. which comprises of basement, ground & two upper floors was granted NOC by this deptt. vide letter No. F6 / DFS / MS / 2009 / 1494 dated 28-05-2009. The premises was re-inspected by the officer concerned of this department on 09-04-2013 in the presence of Mr. Ghai and found that the building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy with effect from - 2013 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

Issued on

at New Delhi.

(DR. G.C.MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph. 23414333

Copy to:-

1. The Asstt. Commissioner (Clubs) GNCTD, L & N Block, Vikas Bhawan, I. P. Estate, New Delhi.

2. The Gernal Manager
Poorva Shanskriti Kendra
at plot No. 14 Diett Centre
Laxmi Nagar Delhi.

Condition

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.
- 5. Basements shall be used as per BBL
- 6. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction, if any.
- 7. The owner / occupier of the building shall, under clause 38 of the DFS Rules, declare in Form 'K' every year that the fire prevention & safety measures provided in the building / premises are in good working condition.

ADO (LN) (Inderven)

-Nbn-

INSPECTION REPORT

1. Name & address of the building: Poorva Sanskriti Kendra 14, Distt.

Centre, Laxmi Nagar, Delhi.

2. Building is comprised of

Basement, Ground + 2

3. Type of Occupancy

Club (Assembly)

4. Type of Case

Renewal

5. Details of Previous NOC letter:

F6/MS/DFS/2009/1494 dated 28.5.2009

6. Fire Safety direction letter No

NA

7. Date of Inspection

09.04.2013

8. Name of the Inspecting officers:

Gurmukh Singh

9. Name and designation of Officer:

Sh. D.S.Ghai (GM)

from the building side

10. Year of Construction

2003 -

11. Applicant's letter No ·

-Nil- dated 03.01.2013

S.NO.	Minimum Standards on fire prevention and fire safety U/R33		Provided at Site	Remarks MR/NMR	
1	Access to building		,		
	 Road width 	12 Mtr	24 Mtr	MR	
	 Gate width 	5.0 Mtr	5.0 Mtr	MR	
	Width of internal road		*		
2 .	Number, Width, Type and Arrangement of Exits				
	a. Number of Staircases				
	 Upper Floor 	2Nos	2Nos	MR	
*2	 Basement 	2Nos ·	2+2ramp	MR	
v	B. Width of Staircases	•			
	 Upper Floor 	Existing	2.0Mtr&1.20Mtr.	MR	
	 Basement 	Existing ·	1.5&1.2Mtr	MR	
	c. Protection of exits		a		
	Fire check door	NA	NA .		
	 Pressurization 	NA.	NA ·		
= 5				×	
	e. No. of continuous staircases to terrace	2Nos	2Nos	MR _.	

•	6	· · · · · · · · · · · · · · · · · · ·		**		
	g. Width of Corridor					
	h. Door Size	1.5 Mtr.	1.5 Mtr	MR ·		
3	Compartmentation.					
	 Fire check door 	Required	Provided	MR		
	 Sealing of electrical 	Required	Provided	MR		
	shafts	NA	NA			
	 Fire rating of shaft door 	NA ·	NA			
•	Water curtain	NA	NA			
	Fire Dampers					
4	Smoke Management System.					
	Basement	Required	Provided	MR		
	Upper floor					
5. ·	Fire Extinguishers					
0.	Total numbers	22Nos.	25Nos.	MR		
	types	ABC & Co2	ABC & Co2	MR ·		
		Required	Provided	MR		
	IS marking First-aid-Hose Reels.	Required	Flovided	IVIIX		
6		ONLog	ONIco	MD		
	 Total numbers at ground floor 	2Nos	2Nos	MR .		
	 Length of hose reel hose 	30 mtr ·	30 mtr	MR		
	Nozzle diameter	5 mm	5mm	MR		
	ŧ	•				
7	Automatic fire detection and alar	ming system				
,	Type of detectors	Heat/smoke	Heat & smoke	MR		
	Location of main panel	Basement	Basement	MR		
	Location of repeater		200 Garage	TVII X		
	panel	IN/A				
	panei	7				
		Regd.	Provided	MR		
	 Alternate source of 		Tiovided	iviix		
	power			5		
	Hooter's location					
8	MOEFA	Required	Provided	MR .		
9	Public address System.	Required	Provided	MR		
			Provided	MR		
10	Automatic Sprinkler System.	Required		MR		
	Basement	Required .	Provided	IVIE		
•	upper floor .	Required	Provided	MR		
	 sprinkler above false 	NA	NA	NA		
	ceiling					
11	Internal Hydrants	Required	Provided	MR		
	. • size of riser/down-comer	100mm	100mm	MR		
•	Number of hydrants per floor	2 Nos.	2Nos.	MR -		
	Hose Box	2 Nos	2 Nos	MR		
	I IOSC DOX		2 1400	- init		

Poorva Sanstroit Kenolva 14. Dist lentre, Laxmo Magar, Delh.

12	Yard Hydrants.			* ,
В	 Total number of hydrants 	Required	Provided	MR
	Hose Box	Required	Provided	MR ·
13	Pumping Arrangements.			
	Ground Level			
1	➤ Discharge of main Pump	2850 LPM.	2850 LPM	MR
•	➤ Head of Main Pump	52 Mtrs.	52 mtrs	MR
	Number of main pumps	2 Nos	2 Nos	MR
	➤ Jockey pump out put	180LPM	180LPM	MR
	➢ Jockey pump head	56 Mtrs.	56 mtrs.	MR
	. > Standby pump out put	2850 LPM	2850 LPM	MR
	➤ Standby pump Head	52Mtrs	52 Mtrs.	MR
ď	➤ Auto Starting /Manual stopping	Required	Provided	MR
	> Pump House Access	Required	Available	MR
	Terrace Level	NA	NA	NA .
	➤ Discharge of pump	NA	NA	NA ·
	> Head of the Pump	NA .	NA	NA ·
	➤ Power supply	NA .	NA	NA
	> Auto Starting of pump	NA	NA	NA
14 ·	Captive Water Storage for Fire Fighting.			
	Underground tank capacity	1,00,000Ltr	1,00,000 Ltrs. ·	MR
	> Draw-off connection	Required	Provided	MR
* +	➤ Fire service inlet	Required	Provided	MR
	> Access to tank	Required	Provided	MR
•	 Overhead Tank capacity 	10,000Ltr.	10,000Ltr.	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.	Required	Provided	MR
	 Pressurization of Lift Shaft 		NA	•
	 Pressurization of Lift lobby 	NA	NA	
	Communication in lift car	Required	Provided	MR
	Firemen's grounding switch	Required	Provided	MR
	Lift Signage	Required	Provided	MR
17	Standby power supply	Required	Provided	MR
18	Refuge Area.	NA ·	NA	
	Total area	NA	NA	
	Location	NA	NA	

19	Fire Control Room	Required	Provided	MR ·
	Detector system panel	NA	NA	NA .
	Flow switch panel	NA ·	NA	NA .
- 2 s	PA system panel	NA	NA	NA
	Battery backup	NA .	NA	NA
	Building Floor Plans	NA	NA	NA
20	Special Fire Protection systems	NA	NA	
	for protection of special Risks, if			
1	any:	•	9. •1 9. 4	

The fire protection systems provided in the building were tested checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer

Name Gurmnich Singh Designation ADO(14)