GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. FELDES/MSIINU/12013/306

Dated: 15/65/2013

FIRE SAFETY CERTIFICATE

Certified that the M/s Ajay Rubber Industries, Located at 291, Pocket-E, Sector-4, Bawana Industrial Area, New Delhi comprised of Basement + Ground and First floor owned / occupied by M/s Ajay Rubber Industries have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concern of Fire Service on 12 / 04 / 2013 in presence of Mr Dheeraj / Mr Manoj representative of the factory and that the premise is fit for Class G (G-1) industrial occupancy with effect from 15 / 25 / 2013 for a period of three years, in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provision of building bye laws.
- 6. This certificate cannot be treated in any case for regularizations of unauthorized construction
- The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>WWW.dfs.Delhigovt.nic.in</u>

Issued on 15) 05 12 00 at New Delhi by

(SANTOKH SINGH) Chief Fire Officer Delhi Fire Service Ph: 011-23414250

cfowz.dlfire@nic.in

Copy to:

1. Sh Ajay Maken, Prop. M/s Ajay Rubber Industries, Located at 291, Pocket-E, Sector-4, Bawana Industrial Area, New Delhi

4	INSPECT	TION REPORT	Sec. 19	
1	Name & address of the building: M/s	Ajay Rubber	Inclustries P. M.	10291 PUT-
2	. Name & address of the building: <u>M/s</u> . Type of Occupancy : <u>C/a</u>	ss 9 (9-1) 2	dustral	
3	37 0	ase/ R enew al		
4			Dated	l:
5				
6				
7	. Name of the Inspecting Officers:			
8	Name and designation of officers		, 1	
	from the building side :	r Dheesoy/	mr Manoj	
9	. Year of Construction :		,	
10	O. Applicant's letter No. : 19	9/03/2013		
	N. M. C. 1 1 00	NBC	Provided at site	Remarks
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Requirement	Provided at site	MR/NMF
	Access to building			1
	Road width			
	Gate width			
	Width of internal road			
2	Number, Width, Type & Arrangement	of Exits	2 ,	2
	a. Number of staircases			
	Upper Floors		***	
	Basements			
	b. Width of staircases			
	Upper Floors			
	Basements			
	c. Protection of exits			
	Fire check door			
	 Pressurization 			
	e. No. of continuous staircases to terrace	1		
	g. Width of Corridor		-	
	h. Door Size		-	
3	Compartmentation.			
	Fire check door	R	P	m/R
	Sealing of electrical shafts	1 2		
	 Fire Rating of shaft door 	*		
	Water Curtain	i - ha-i		
	1		THE POST OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TO PERSON NAMED IN	

Fire Dampers

5	Fire Extinguishers			3			
0	Total numbers	10 ABC	P	MIK			
	• Types	ISI marked	ABC	MA			
*	IS marking		P	m/R			
6	First-Aid Hose Reels.						
	Total numbers on each floor						
	Length of hose reel hose	30 m					
	Nozzle diameter	5 mm					
7	Automatic fire detection and alarming	g system.					
	Type of detectors						
	 Location of Main Panel 						
20	Location of Repeater Panel						
28	Alternate source of power	-					
	Hooters' Location						
8	MOEFA						
		*					
9	Public Address System.						
10	Automatic Sprinkler System.						
	Basement						
	Upper Floor						
	Sprinkler above false ceiling						
11	Internal Hydrants						
	Size of riser/down-comer	¥					
	Number of hydrants per floor		*				
12	Hose Box Vard Hydrants						
12	Yard Hydrants.			3,9 3			
	Total number of hydrantsHose Box			-			
12			`				
13	Pumping Arrangements.			1008			
	Ground Level Discharge of main Property		2				
_	Discharge of main Pump						
	Head of Main pump	9					
	Number of main pumps Number of main pumps						
	Jockey Pump out put						
9)	> Jockey pump head						
	Standby Pump Hood						
8	Standby Pump Head		0				
	Auto Starting/ Manual stopping						
	> Pump House Access						
5.	Terrace level		Habita O Tosa ii				

14	Captive Water Storage for fire fighting.						
	Underground tank capacity						
	> Draw-off connection						
	> Fire service inlet						
	> Access to tank						
	Overhead Tank capacity						
15	Exit Signage.						
16	Provision of Lifts.						
	Pressurization of Lift Shaft						
	• Pressurization of Lift lobby						
	Communication In lift Car						
9	• Fireman's Grounding Switch						
	Lift Signage						
17	Standby power supply			,			
18	Refuge Area.						
	> Total Area						
	> Location						
19	Fire Control Room						
	Detector System Panel		2				
à	Flow Switch Panel		8				
	PA System Panel		,				
	Batter backup						
	Building Floor Plans						
20	Special Fire Protection Systems for Protection of special Risks, if any:						

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the noted serial shortcomings as Delhi Fire Service Rules 2010/ issue numbers.....

Designation

Signature of the Inspecting Officer

Name

DCFo (w 2)

Signature of the Inspecting Officer

Name

Designation