## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DLEHI-110001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/EH/2013/ 365

Dated: 24/05/13

## FIRE SAFETY CERTIFICATE

Certified that the **Kadhai Tadka Restaurant** (A unit of Bharat Fortune Resorts Pvt. Ltd.) located at R-549, Shankar Road, New Rajinder Nagar, New Delhi-110060. The building comprised of basement, ground floor plus three upper floors. The restaurant is running at Ground floor and first floor only was issued NOC by this department vide letter No.F.6/DFS/MS/EH/10/195 dated 18.01.2010 owned/occupied by Bharat Fortune Resorts Pvt. Ltd. The Restaurant was re-inspected by the officers concerned of this department on 16.05.2013 in the presence of Sh. Sanjay Uppal (Director) and found that the Bharat Fortune Resorts Pvt. Ltd have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class Group D assembly building Sub- Division D-6 w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on 24/05/13 at New Delhi.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

Sh. Sanjay Uppal (Director),
 Bharat Fortune Resorts Pvt. Ltd,
 R-549, Shankar Road, New Rajinder Ngr., N.D-60.

02 Vy Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

Basement, Ground Floor plus three cepper Floors Note: The Restaurant running at Ground Floor & First Floor only.

	NIS				
	INSPECTI	ION REPORT			
	<ol> <li>Name &amp; address of the building: k</li> </ol>	adhai Tadh	a Recio ci	- 01 0	
	. /	Assembly (Res	taument)	JUNKER KA, NG	Ginoler
	a. Type of Case	Vew Case/Renev	val	Nagar, 1	4.2-60.
	4. Details of Previous NOC : L	etter No.F.6/N	ES/MS/EH/10/1	OC Data 10 a	
	and an ectives leffel 140	A /	MA	73 Date 18,0	1.2010
	6. Date of inspection :	10.0	5.2013		
	7. Name of Inspecting Officer :			0001	1
	8. Name and designation of officers	00/12/11)	neja & A.D.	P.S. Dah	iya
	From the building side :	Sh. Sonjo	111/11/21		
	9. Year of Construction :	Before 2008	a appar		
	10. Applicant's letter No.	Mil plate	1 03:05-201	0	
S.	Minimum Standards on fire	NBC/BBL	Provided at	The second secon	==
No.	prevention and fire safety U/R 33	Requirement	site	Remarks	
1.	Access to building	negatient	site	MR/NMR	
	Road width	Accessible	12 mtr	100	-
	• Gate width	FICCOSTONE		MR	The Committee of the Co
	Width of internal road		170 cms	MR	
2.			^	•	
1	Number, Width, Type & Arrangement of Staircases	of Exits		1	1
					2
	• Upper Floors	Two	Two	MR	
	<ul><li>Basements</li><li>b. Width of staircases</li></ul>	-do-	-do-	MR	
	I II				
	Upper Floor	•	130 cm s, 94 cms	MR Beins	Maria
	Basements	*	121 Cmp, 92 Cms	- do -	Old Cope
	c Protection of exits		To the talk	- 00 -	
	<ul> <li>Fire check door</li> </ul>		7		
	• pressurization				
	d. No. of continuous staircases to				
	terrace	neg	One		
	e. Width of Corridor				
	f. Door Size		126 Cmp 112 cms x 202 cms		
2		_	88 Cms x 202 cmp	-	:
3.	Compartmentation		So Comp Know (mp	1	
	Fire check door				
	<ul> <li>Sealing of electrical shafts</li> </ul>				
	<ul> <li>Fire Rating of shaft door</li> </ul>		Sealed	-	
	Water Curtain		2	~	
	• Fire Dampers		_	-	
4,	A CONTRACTOR OF THE PROPERTY O		· ·	-	
7,	Smoke Management System				
	<ul> <li>Basements</li> </ul>	30 a/c per	Exhaust fans		
	<ul> <li>Upper flcors</li> </ul>	hour	are Provided	MR	10
			Matural Ventilation	mR	

	NIA	**************************************		; ;
		12 a/c per hour		
5.	Fire Extinguishers			
	<ul> <li>Total numbers</li> </ul>	ree at each floo.	Paovided	41-0
	• Types	Co, WCo, ABC	- 010 -	MR
	<ul> <li>IS marking</li> </ul>	ISI marked	151 Marked	MR MR
5.	First-Aid Hose Reels		13/1/arrea	IMK
	<ul> <li>Total numbers on each floor</li> </ul>	One	Provided	MR
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	-do-	MR
7	Nozzle diameter	5 mm	- do :-	MR
7.	Automatic fire detection and alarming	system		
	<ul> <li>Type of detectors</li> </ul>			
	<ul> <li>Location of Main Panel</li> </ul>	-		
	<ul> <li>Location of Repeater Panel</li> </ul>		-	
	<ul> <li>Alternate source of power</li> </ul>		02 D. G. Set of 62.5	KVA MR
. 0	Hooters' Location	-	- 60	ch
8. 9.	MOEFA	Required	Provided	MR
10.	Public Address System	-'do-	-do-	MR
	Automatic Sprinkler System			1 N
	bascincin	Required.	Provided	MR
	• Upper Floor / First Floor	-d0-	- do -	MR
11.	<ul> <li>Sprinkler above false ceiling</li> <li>Internal Hydrants</li> </ul>			-
	Size of riser/down-comer		'	1
		100 m.m	100 M.M	MR
	<ul><li>Number of hydrants per floor</li><li>Hose Box</li></ul>	<u>One</u>	One	MAR
12.	Yard Hydrants	-do-	-do-	MR
	<ul> <li>Total number of hydrants</li> </ul>		J.	
	* Hose Box	*		
13.	Pumping Arrangements		Lance Control of the	
	* Ground Level			
	Discharge of main Pump			
	Head of Main pump			
	Number of main pumps			
	Jockey Pump out put			
	<ul> <li>Jockey pump head</li> </ul>		-	
	Standby Pump out put		-	
	Standby Pump Head			
	Auto Starting/Manual	-		_
	stopping		-	

	Pump House Access		•	_		
	<ul> <li>Terrace level</li> </ul>					
	Discharge of pump	450LPM	450 LPM	MR		
	Head of the pump					
	Power Supply	30 M Required	43 M Provided	MR		
	Auto Starting of pump	~	-			
14.	Captive Water Storage for fire fighting			9		
	<ul> <li>Underground tank capacity</li> </ul>			-		
	Draw-off connection	•		-		
	Fire service inlet		Quantum.			
	Access to tank		C	-		
	<ul> <li>Overhead Tank capacity</li> </ul>		6000 Ur	MR, Being a Ola		
15.	Exit Signage.	Required	Provided	MR		
16.						
	Pressurization of Lift Shaft		_			
	<ul> <li>Pressurization of Lift lobby</li> </ul>			_		
	Communication In lift Car		0 11			
	<ul> <li>Fireman's Grounding Switch</li> </ul>	-	Provided	MR		
	• Lift Signage	Regleired	- de -	MR		
	Entersignage	Regierred - do-	-do-	MR		
17.	Standby power supply	Required	Provided	MR		
18.	Refuge Area.					
7.70.00.000	Total Area	6.	- 1	-		
	> Location	-	2 0 52 2 0 20	-		
19.	Fire Control Room					
17.						
	Detector System Panel     Flow Switch Panel	(**	_			
	Flow Switch Panel     PA System Panel	tan-	*	-		
	PA System Panel     Patter hardway	-	~	•		
	<ul><li>Batter backup</li><li>Building Floor Plans</li></ul>	Required	Provided	MR		
	Banania Hoor Halls		-			
20.	Special Fire Protection System for Protection of special Risks, if any:		_	~		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the above substantial compliance of the minimum standards on fire prevention and Fire Safety measures required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial

numbers.....

Name H. L. Aneja Designation Divisional Officer

Signature of Inspecting Officer

Name P.S. Dahiya

Designation ASSH. Divisional Officer.