## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2013/ 52/ 482

Dated: 25/06/13

## FIRE SAFETY CERTIFICATE

Certified that the Guest House Sri Nanak Continental located at 2222, Hardhyan Singh Road, Karol Bagh, New Delhi-110005 comprised of Basement, ground floor plus three upper floors, using basement as one office & hall running vacant, ground floor as reception and shops, first floor having nine guest rooms, one office & one store room, second floor having eight guest rooms, third floor having nine guest rooms, one office & one store room (Total Twenty Six guest rooms), A staff kitchen with temporary shed on terrace was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2010/1978 dated 05.07.2010 owned/occupied by Sh. Sandeep Khandelwal. The guest house building was re- inspected by the officer concerned of this department on 15.06.2013 in the presence of Sh. Sandeep Khandelwal (Owner) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

- 1. The Addl. Commissioner of Police (Lic.) 1<sup>st</sup> floor, P.S., Defence Colony, New Delhi. (Re. No.24608/Addl. C.P./Lic.(H), Dated 25.05.2013)
- 2. Sh. Sandeep Khandelwal (Owner), Guest House Sri Nanak Continental, 2222, Hardhyan Singh Road, Karol Bagh, N.D-05.

Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

## Basement, Ground Floor plas three apper Floors.

	The second secon	INSPECT	ION REPORT			
	L. Name & address of the Z. Type of Occupancy	e building :	2. H Sxi Nanak	Continuedat of	1990 11- 11 0	.,
		: 9	Residential CG	hest House)	Lada, Marahyan Singh,	ld,
	3. Type of Case		New Case/Rene	wal	Karol Bogh, R.S.	
	d. Details of Previous NO	C :	Letter No. F.6/AF	c/me/GHI)nie/102	18 Date 05.07.2011	
	5. Fire Safety directives le	etter No :		2/1/3/01/1/2010/1/77	B Date 03,04.2011	)
	6. Date of inspection		15.0	36-2013	AND THE PROPERTY OF THE PROPER	
	Name of Inspecting Of	S. Dahiya	Market and a second of the second			
	8. Name and designation	of officers				
	From the building side	Sh. Sandees Khandelwal Before 1994				
	9. Year of Construction					
5	10. Applicant's letter No.		24608/Add1.	C.P./LIC. (H)	dated gracin	
	Minimum Standards on fire	1	NBC/BBL	Provided at	Remarks	
No.	prevention and fire safety (	J/R 33	Requirement	site	MR/NMR	
1.	Access to building	The state of the s			TVIII TVIII	
	<ul> <li>Road width</li> </ul>	The second secon	Accessible	12 mts	MR	
	<ul> <li>Gate width</li> </ul>		-	180 cm 8	MR	
	<ul> <li>Width of internal roa</li> </ul>	ad		, 00	1.1/	
2.	Number, Width, Type & Arr	rangement	of Exits	No.	Proc.	
	a. Number of staircases					
	<ul> <li>Upper Floors</li> </ul>		One	<b>A</b> .	No. 1	
	<ul> <li>Basements</li> </ul>		k	One	MR, Being a Old Cos	e
	b. Width of staircases		-do-	-do-	-d8-	
	<ul> <li>Upper Floor</li> </ul>					
	<ul> <li>Basements</li> </ul>			100 cm8	MR, Being a old Ca	se
	c. Protection of exits			120 cmp	-do -	
	<ul> <li>Fire check door</li> </ul>					
	<ul> <li>pressurization</li> </ul>					
	d. No. of continuous stairc	ases to				
	terrace			37 F T 3		
	e. Width of Corridor			One		
	f. Door Size			165cms, 125cms		
				83 cm x 197 cms	and the second s	
3.	Compartmentation			0~ 1.p K 1 / / Cmp		,
	Fire check door					
	<ul> <li>Sealing of electrical s</li> </ul>	hafts	-	•	_	
	• Fire Rating of shaft of	llaits	-	Sealed		
	• Water Curtain	1001	-			
	• Fire Dampers		· ·	All the second s		
	and the second s					
4.	Smoke Management System	n		No.		
	<ul> <li>Basements</li> </ul>		30 a/c per	Exhaust fans		
	<ul> <li>Upper flcors</li> </ul>		hour	are Provided	MR	
	The second secon			lafural Ventilation	MR	

· · · · · · · · · · · · · · · · · · ·	12 a/c per hour	_	
ire Extinguishers			*
• Total numbers	Three at each Floor	+ ^	
• Types	Co, ABC	1 sovided	MR
<ul> <li>IS marking</li> </ul>	ISI marked	-do 7	MR
irst-Aid Hase Pools	1.51 marked	151 Marked	MR
* Total numbers on each floor	One	0	
<ul> <li>Length of hose reel hose</li> </ul>	30 m	Provided	MR
Nozzle diameter	5 mm	-do-	MR
Automatic fire detection and alarming		- do -:	MPR
• Type of detectors	system		
<ul> <li>Location of Main Panel</li> </ul>	•		
<ul> <li>Location of Repeater Panel</li> </ul>	-	_	
<ul> <li>Alternate source of power</li> </ul>	•	_	
<ul> <li>Hooters' Location</li> </ul>		D. G. Set of 125 KVA	
MOEFA	-		
Public Address System	Required	Provided	MR
Automatic Sprinkler System	~ do-	- do -	MiR
Basement			
<ul><li>Dasement</li><li>Upper Floor</li></ul>	Required	Provided	MR
		P	
Sprinkler above false ceiling		1	
Internal Hydrants			
<ul> <li>Size of riser/down-comer</li> </ul>			
<ul> <li>Number of hydrants per floor</li> </ul>	- ~	-	-
<ul> <li>Hose Box</li> </ul>			
Yard Hydrants		1	
<ul> <li>Total number of hydrants</li> </ul>			
• Hose Box	_		
Pumping Arrangements			
<ul> <li>Ground Level</li> </ul>			and the same of th
Discharge of main Pump			> The same of the
<ul> <li>Head of Main pump</li> </ul>			
<ul> <li>Number of main pumps</li> </ul>	•		
Jockey Pump out put	-		
Jockey pump head			
<ul> <li>Standby Pump out put</li> <li>Standby Pump Head</li> </ul>			-
standay i dirip fiead			
Auto Starting/Manual	W There are proportion to the state of the s		
stopping	_	1	

2222, Hardhyan Singh Road, Karol Bagh, New Delli-110005.

Pump House Access							
	450LPM	450LPM	MR				
			MR				
	Required	Provided	me				
Auto Starting of pump	,						
Captive Water Storage for fire fighting							
<ul> <li>Underground tank capacity</li> </ul>	•	-					
	-	. ~					
	~	_					
<ul><li>Access to tank</li><li>Overhead Tank capacity</li></ul>	Name -	-	~				
	Marine .	5000 LAY	MR Cold Care				
Exit Signage.	Required	Provided	MR				
Provision of Lifts.		2					
<ul> <li>Pressurization of Lift Shaft</li> </ul>	•						
<ul> <li>Pressurization of Lift lobby</li> </ul>			-				
<ul> <li>Communication In lift Car</li> </ul>		0					
<ul><li>Fireman's Grounding Switch</li></ul>	0		MR				
<ul> <li>Lift Signage</li> </ul>	Keguired	- do -	MR				
	-do-	-do-	MR				
Standby power supply	Required	Provided	MR				
Refuge Area.							
Total Area	_						
Location			Pare .				
1	_		-				
Fire Control Room							
<ul> <li>Detector System Panel</li> </ul>	•	b	74				
	•	-	-				
	-	-					
<ul><li>Batter backup</li><li>Building Floor Plans</li></ul>	Required	Provided	MR				
	pur on	1,00,000	/ //				
			) <b>6</b> mm				
Special Fire Protection System for	1						
Protection of special Risks, if any:	1	_	~				
	<ul> <li>Underground tank capacity</li> <li>Fire service inlet</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Exit Signage.</li> <li>Provision of Lifts.</li> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> <li>Lift Signage</li> <li>Standby power supply</li> <li>Refuge Area.</li> <li>Total Area</li> <li>Location</li> <li>Fire Control Room</li> <li>Detector System Panel</li> <li>Flow Switch Panel</li> <li>PA System Panel</li> <li>Batter backup</li> <li>Building Floor Plans</li> </ul> Special Fire Protection System for	Discharge of pump Head of the pump Power Supply Auto Starting of pump  Captive Water Storage for fire fighting  Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity  Exit Signage.  Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage  Required  Standby power supply  Refuge Area.  Total Area Location  Fire Control Room Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans  Special Fire Protection System for	• Terrace level				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

seeping in view the above substantial compliance of the minimum standards on fire prevention and Fire Safety measures required under the rules it is recommended to grant Fire Safety ertificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial

Designation ASSH. Divisional Officer.

Signature of Inspecting Officer

Name

Designation