FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [SEE SUB-RULE (1) OF RULE 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

F6 DF5/MS/ BNOT/2013/WZ/523 Dated: 08/07/2013

FIRE SAFETY CERTIFICATE

Certified that the M/s Shubh Nimantran Banquet located at 7/25 Kirti Nagar, Industrial Area, New Delhi, comprised of Basment+Ground+three upper floors, owned/occupied by M/s Shubh Nimantran Banquet have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Fire Service on 14-06-2013 in the presence of Mr. Amit & Parveen Gupta of the Banquet Hall and that the building/premises is fit for occupancy Class-D Assembly with effect under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(SANTOKH SINGH) Chief Fire Officer Delhi Fire Service E-mail:cfowz.dlfire@nic.in Tel No. 011-23414250

Copy to: The Director M/s Shubh Nimantran Banquet 7/25 Kirti Nagar, Industrial Area, New Delhi

Note:- For general fire safety directives please over leaf.

Following fire safety directives must be adhered to:-

- 1) All the fire safety arrangement provided their in shall be maintained in good working conditions at all time.
- 2) Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3) The trained fire fighting staff should be available round the clock.
- 4) Any deviation, with regards to construction etc shall be verified by the concerned building sanctioning agency.
- 5) The basement shall be used strictly as per the provision of building Bye-Laws.
- 6) This certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. This is available on www.dfs. delhigovt. nic.in

Name & address of the building 1.

: Shubh Nimonston, 7)25 Knotionager MD-: Assembly (B+G+terro upper floors)

Type of Occupancy 2.

Type of Case 3.

New

Details of previous NOC 4.

: Nil

Fire Safety directives letter No. 5.

: F6/0Fs/ms/BP/2012/28150+31)7/12

6. Date of inspection : 14-06-2013

Name of the Inspecting Officers 7.

: D.O. Sumil Chandhary

Name and designation of officers 8.

My Amit and Parveon Gujota

From the building side

9. Year of Construction

10. Applicant's letter No.

DHO/13/2/2012/1182 Dt. 12/5/13

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

5. No.	Minimum Standards on fire Prevention and fire safety U/R 33	BBL Requirement	Provided at site	Remarks MR/NMR	
	Access to building				
	Road width	12 mt	25mlr	MR. O	
	• Gate width	5mt	Psevioled 1	MR	
	 Width of internal road 	i.h.	\mathcal{A}	2	
•	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases			3	
	Upper Floors	2 Stair Care	Provided	MR	
	• Basement	1)	1)	"	
	b. Width of staircases				
	No.		A second		

1

1/19

	Upper Floors	1.5 mstr. each	Provided	MR
	• Basement))	"	MR
	c. Protection of exits			
	Fire check door	Required	Provided	MR
	 Pressurization 	Required	Pourided	MR
	d. No. of continuous staircases to terrace			
	e. Width of Corridor	2 mts.	halls only	MR
	f. Door size	2 door of 2 mt a width at each floor	Provided	MR
	Compartmentation.	V 1		
	Fire check door	Regnised /	Provided	MR
	Sealing of electrical shafts	ov.A.	N.A.	MA
Ē	Fire Rating of shaft door	NA	0 0	NA
	Water Curtain	NR	NR	NR
	Fire Dampers	Regunsed	Provided	MR
١.	Smoke Management System.			
	Basements	Regnised /	Prunded	mol
	Upper floor	Required	Provided	MR
5.	Fire Extinguishers			
	Total numbers Water	Co2 9278-2 2 at	Provided	rsp
	• Types Co2 4.5x	Co2 9278-2 2 at g.DCPtype 5Kg each	Provided.	MR
	IS marking	ISI marks	Provided	rsk
ó.	First-Aid Hose Rees.			* -
-				**************************************

N

NIS

		NIS	1	
1			α	
	Total numbers on each floor	two	Provided	MR
	 Length of hose reel hose 	30 m Reguered	11	1/
	 Nozzle diameter 	5 mm	1/	(NY)
7.	Automatic fire detection and alar	ming system.		
	Type of detectors	Smo)ce) Heat	Provided 4/ Functional	MR
	 Location of Main Panel 	GF	Provided -	MR 1
	• Location of Repeater Panel	It each floor	at ocun floo	MRO
	Alternate source of power	Required	Provided	MR
	Hooter's Location	Regissed	Provided	MR
8.	MOEFA	Regissed	Pronded	MR
9.	Public Address System.	Regussed	Provided	MR
10.	Automatic Sprinkler system			
	• Basement	Regurred	Provided	MR
	Upper Floor	Regursed	Provided -	MR
	 Sprinkler above false ceiling 	NA	N)A	MA
11.	Internal Hydrants			
	Size of riser/down-comer	_150 m.n.	: Provided	MR
	 Number of hydrants per floor 	2	P	MR
	Hose Box	Z 2	8/	MR
12.	Yard Hydrants.		L	
·	Total number of hydrants	MA	MA	NA

N) 46

1	Hose Box	NA	NA	MA	
13.	B. Pumping Arrangements.				
	Ground Level				
	Discharge of main pump	2280LPM	Provided 1	MR	
	➤ Head of Main pump	60 mits.	Provided	MR	
	Number of main pumps	One	Two r	NMR	
	➤ Jockey Pump out put	1802PM	Provided 1	MR	
	Jockey pump head	70 mits.	Provided 1	MR	
	Standby pump out put	22801PM	MP 1	NMR	
	Standby pump Head	60 mts.			
	Auto Starting/Manual stopping	Requied	Pronod/	MR	
	Pump Hose Access				
	Terrace level	Jockey Pump 900	olfm (
	Discharge of pump		1 Provided	MP	
	➤ Head of the pump	So mits.	Provided /	MP	
	Power supply	Required	Provided (MR	
	> Auto Starting of pump	Required	Provided /	MR	
14.	Captive Water Storage for fire fi	ghting.			
	Underground tank capacity	50,000 Rts.	Postida	MR	
	Draw -off connection	Registed	Bonded	MR	
	Fire service inlet	Registed	Provide d	7,1	
	Access to tank	Regused) /	1)	
				,	

M

N117

4		. 9			
	Overhead Tank Capacity	10,000 lts.	Posvided	M.R.	
15	Exit Signage.	Regissed	Provided		
16.	Provision of Lifts	List is not	going to bus		
	Pressurization of Lift Shaft	Not Registered	NP n	1 Park W	
	Pressurization of Lift lobby	Nat Requised	NP	6 m 0 11	
	Communication In lift Car	Required	₽80vide N	(MAL	
	Fireman's Grounding Switch	-)/	7/	7)	
	Lift Signage	Regured	Provided	1)/	
17.	Standby power supply	R.	1) 123 KVA 2) 62.516VA	MR	
18.	Refuge Area				
	> Total Area	NR	NR	NK	
	> Location	NR	NP	NR	
19.	Fire Control Room		, , <u>, , , , , , , , , , , , , , , , , </u>	*****	
2	Detector System Panel	Réquised	Provided o	mR	
	Flow Switch Panel	7)	7)	7	
	> PA system Panel	Registard	Poorded	MR	
	➤ Batter backup		7)		
	Building Floor plans				
20.	Special Fire Protection Systems for				
		1			

d.

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/

issue shortcomings as noted at serial number.

Note: -1. Draw off Connection has been provided.

2. Pressursedion of lift lobby, lift & firenum switch has been provided.

Signature of the Inspection Officer

Signature of the Inspection Officer

Signature of the Inspection Officer

Sunil Chawdhary

Name

Designation D.O (W

Designation