GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2013/ 532

Dated: 08/0)//3

FIRE SAFETY CERTIFICATE

Certified that the Guest House **The Pearl- A Royal Residency** located at 7A/43, WEA, Channa Market, Karol Bagh, New Delhi-110005 comprised of Basement, stilt floor, ground floor plus three upper floors, using basement as Hall/Storage, stilt floor as parking, ground floor as reception and 03 guest rooms, first, second & third floor each having 05 guest rooms respectively (Total 18 guest rooms), A pantry for staff in tin shed on terrace was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2010/2480 dated 26.08.2010 owned/occupied by Sh. Kunal Suri. The guest house building was reinspected by the officer concerned of this department on 26.06.2013 in the presence of Sh. Anand Chohan (Manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on 08/07/13 at New Delhi.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

1. The Addl. Commissioner of Police (Lic.)

1st floor, P.S., Defence Colony, New Delhi.

(Re. No.29014/Addl. C.P./Lic.(H), Dated 13.06.2013)

ON ON

2. Sh. Kunal Suri (Owner), G.H The Pearl- A Royal Residency, 7A/43, WEA, Channa Mkt., Karol Bagh, N.D-05. Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

Bosement, Stilt, Ground Floor plus three upper Floors.

	INSPEC	TION REPORT				
	1. Name & address of the building	G. H The Pear	1 0001010			
	4. Type of Occupancy	Residential (C- H ROYAL KES	idency, 7A/43,	WEA,	
	ype of Case	: New Case/Repo	owal	hanna Mkt Karol	Bogh N.	
	The Details of Previous NOC	Letter No 6C/A	edmellula	l a		
	5 Fire Safety directives letter No					
	b Date of inspection					
	Name of Inspecting Officer	A.S.O. P.S. Dahiya Sh. Anand Chohan 2009-10 290141 Addl. C.P/LIC. CHJ dated 13.06.2 NBC/BBL Provided at Remarks Requirement site MR/NMR Accessible 09 mtr MR 140 cms MR One One -do- 125 cms MR, Being a or 125 cms -do-	_			
	8. Name and designation of officers	77,0,0	P.S. Dahiya		_	
	From the building side		. 1 01 1			
	9. Year of Construction	Sh. rina	nd Chohan	the state of the s	-	
	10. Applicant's letter No.	290141 Oddl C 011				
	Minimum Standards on fire	NRC 1 201	CP/LIC.(H) a	ated 13.06.20	13	
Vo.	prevention and fire safety U/R 33		Provided at			
	Access to building	Redairement	site	MR/NMR		
	 Road width 	Accessible	1			
	 Gate width 	ricasine	l .	MR	770777	
	 Width of internal road 	-	140 cms	MR.	or company	
2.	Number, Width, Type & Arrangement			_		
	Number of staircases	orExits				
	* Upper Floors					
	* Basements	One	One	TAR Reina A.A.	May	
	b. Width of staircases	-do-	-do-	do-	0 6436	
	• Upper Floor		And the second s			
	* Basements		12 Come	MO Cale and	10	
	Protection of exits	-		Deing a ola	lase	
	• Fire check door		10.5 (119)	-00-		
			And the control of th	and the same state of the same		
	pressurization					
	d. No. of continuous staircases to terrace					
	e. Width of Corridor	5	A			
	f Door Size		The state of the s			
	0001 3126		163 cms, 125 cms	part of the second seco	100 mm	
3	Compartmentation		86 cm8 x 202 cms		The second secon	
				The same statement where the same statement was a second statement of the same statement		
	Fire check door				-	
	 Sealing of electrical shafts 		A			
	 Fire Rating of shaft door 		Sealed			
	 Water Curtain 					
	 Fire Dampers 				1	
4.	Smoke Management System			_		
	* Basements				1	
	* Upper floors	1	Exhaust fong are		1	
	and the second of the second o	hour	Provided	MR		
		Λ.	1 x 0 00 0 6 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	I STATE OF THE PARTY OF THE PAR	120	

4	<u> </u>	116		
	to the same of the	12 a/c per	A	*
		hour	•	•
Fire Ex	tinguishers			
*	Total numbers	Two at each floor	Provided	0.00
m.	Types	WCG2, ABC	- do r	MR
3	IS marking	ISI marked	1SI Marked	MR
First-A	id Hose Reels		131 IV JURKED	MR
	Total numbers on each floor -	One	Provided	MR
3	Length of hose reel hose	30 m	- do -	
	Nozzle diameter	5 mm	-do:-	MR
Auton	natic fire detection and alarmin	g system	- 40	MR
n	Type of detectors			
p.	Location of Main Panel		•	<u> </u>
9	Location of Repeater Panel	-		<u> </u>
	Alternate source of power		N C C A A	
9	Hooters' Location		D.G. Set of 125KV	
MOEF		Required	Provided	
Public	Address System	Required do-	-do-	MR
	mätic Sprinkler System	- 00-	-00-	L MR
9	Basement	Required	Provided	MR
79	Upper Floor	1 Gueroca	rounded	TIV.
6	Sprinkler above false ceiling		1	
Interr	nal Hydrants			
•	Size of riser/down-comer			
Đ	Number of hydrants per floor			- I
¢	Hose Box			
Yard H	Hydrants		J	
•	Total number of hydrants	The same of the sa		
E.	Hose Box			
Bamb	ning Arrangements	1000		
9	Ground Level			
	Discharge of main Pump		_	
	Head of Main pump			-
	 Number of main pumps 			
	 lockey Pump out put 			
	lockey pump head			
	 Standby Pump out put 			
	Standby Pump Head			
	- Auto Starting/Manual	Name 2		
	stopping	_		-

N/7 7A/43, WEA, Chama MKt., Karol Bagh, New Delli-05.

oldGK

(Clour Dage)					
Pump House Access	-				
 Terrace level 					
Discharge of pump	450LPM	uraipm	MR		
· o i ci sappiy	Required	Parvided	MR		
Auto Starting of pump			-		
Captive Water Storage for fire fighting					
 Underground tank capacity 			-		
		Provided	_		
Access to tank		7 8001464			
 Overhead Tank capacity 	1	Sooo LAY	MR (Old Case		
Exit Signage.	Required	Provided	MR		
Provision of Lifts.					
 Pressurization of Lift Shaft 	_				
			-		
· ·			MR		
	Required	-do-	MR		
	-do-	-do-	MR		
Standby power supply	Required	Provided	MR		
Refuge Area.		* * * * * * * * * * * * * * * * * * * *			
> Total Area					
> Location		_			
	_	-			
Fire Control Room					
 Detector System Panel 		_			
	-		_		
			_		
	Required	Provided	MR		
	-		No.		
	 Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area Location Fire Control Room Detector System Panel Flow Switch Panel PA System Panel Batter backup 	• Terrace level	• Terrace level		

The fire protection systems provided in the building were test checked and found functional at time of inspection.

Fire Safety measures required under the rules it is recommended to grant Fire Safety ertificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial

Signature of Inspecting Officer

same P.S. Dahiya

Designation ASSH. Divisional Officer

Signature of Inspecting Officer

Name

Designation

Date 4-743 Cisty No. 512

Dy. CFO (South) Ale