GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. F6/DFS | MS/School | 2013 | W2/548 Dated: 11 / 07/2013

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction
- 6. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on WWW.dfs.Delhigovt.nic.in

Issued on _______ at New Delhi by

(SANTOKH SINGH) Chief Fire Officer Delhi Fire Service Ph: 011-23414250 cfowz.dlfire@nic.in

AC\$

Copy to:-

- 1. The Principal, Navjeevan Convent School, Shradhanand Colony, Delhi-110042.
- 2. The Director of Education, Old Secretariat, Delhi.

Renewal

INSPECTION REPORT

1. Name & address of the building Nav	Leevan Convo	it School Chro	Theren			
 Name & address of the building Nav Type of Occupancy 2 due	ational.	-Bhalswa	Y Dairy, D			
7 7 6 6	Case/Renewal					
		109/3520 Date	d: 23-11-2			
5. Fire Safety directives letter No Circ	ular Dir. of	Edm., 262-3	62 dt. 17			
o. Date of inspection : 10-	6-2012					
7. Name of the Inspecting Officers:	O- SHYAM	2 LA1-				
from the building side : 7/13	. Shahnaz	Khan ((H)	4.5			
9. Year of Construction 199	U, (Ground	Khan ((H) (only) D3 No (2) 8 No 23-5-2 012	S Pucca Reo			
10. Applicant's letter No.	il lated	(2) 8 No3	sheds.			
	i outa	3-3-2013				
Minimum Standards on fire prevention and fire safety U/R 33	Requirement	Provided at site	Remarks			
	17/1/2005		MR/NMR			
Access to building						
Road width	Accessible	6 m	MIR			
• Gate width	-11-	2.5 m	-4-			
Width of internal road	NIA	NIA	NIA			
Number, Width, Type & Arrangement of Exits						
a. Number of staircases		NIA				
Upper Floors						
• Basements						
b. Width of staircases						
Upper Floors						
• Basements						
c. Protection of exits	***					
Fire check door						
• Pressurization						
e. No. of continuous staircases to terrace						
g. Width of Corridor		1				
h. Door Size	1 m	Im	. di			
Compartmentation.	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	(one door,)	es thous he			
Fire check door		NIR				
 Sealing of electrical shafts 	1	1				
Fire Rating of shaft door						
Water Curtain						
Fire Dampers		<i>a</i> ,				
Smoke Management System.						
Basements	30 a/c per hour	NIR	*			
Upper floors	12 a/c per hour	1				

5	Fire Extinguishers						
	Total numbers	O3 ABC/CO2(2:5%) ABC ISI marked Provided		mIR mIR mIR			
	• Types	ISI marked	B) ABC	MIR			
	IS marking		Provided	MIR			
	First-Aid Hose Reels.		1				
	Total numbers on each floor		NIA				
	Length of hose reel hose	30 m					
	Nozzle diameter	5 mm					
*****	Automatic fire detection and alarming	system.		***			
	Type of detectors		NIR	1			
	 Location of Main Panel 		 				
	 Location of Repeater Panel 	*	1				
	Alternate source of power						
	Hooters' Location		 				
	MOEFA			-			
			NIR				
	Public Address System.		NIR				
()	Automatic Sprinkler System.						
	• Basement		NIR				
	Upper Floor						
	 Sprinkler above false ceiling 						
1	Internal Hydrants						
	Size of riser/down-comer		NR				
	 Number of hydrants per floor 		7				
-	Hose Box		4 7/				
2	Yard Hydrants.		0.1.0				
	Total number of hydrants		NIK				
	Hose Box						
3	Pumping Arrangements.	-	2010	x 2			
	Ground Level		NK				
	Discharge of main Pump						
	> Head of Main pump	`					
	Number of main pumps						
	Jockey Pump out put						
	> Jockey pump head		1 .				
	> Standby Pump out put						
	Standby Pump Head						
	> Auto Starting/ Manual						
	stopping > Pump House Access						
	Terrace level						
	Discharge of pump		-				
	> Head of the pump						
	➢ Power Supply						
	Auto Starting of pump			· ·			

14	Captive Water Storage for fire fighting.	iting.				
	Underground tank capacity		NIK	, i		
	> Draw-off connection					
	> Fire service inlet		40			
	> Access to tank			ź.		
	Overhead Tank capacity	•				
15	Exit Signage.	2 × 1	N/R			
16	Provision of Lifts.					
	 Pressurization of Lift Shaft 		NIT			
	 Pressurization of Lift lobby 					
	Communication In lift Car					
	Fireman's Grounding Switch	- A - A - A - A - A - A - A - A - A - A				
	• Lift Signage					
17	Standby power supply		NIR			
18	Refuge Area.					
	> Total Area		N/X	n n		
	> Location			ž		
19	Fire Control Room					
	Detector System Panel		NIK	8 2		
	Flow Switch Panel			*		
	PA System Panel					
	Batter backup			.* *		
	Building Floor Plans					
20	Special Fire Protection Systems for Protection of special Risks, if any:		NiL			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers. Signature of the Inspecting Officer

11 | 6 | 2013

Signature of the Inspecting Officer

Name

Designation

Name (SHYAM CAL)

Designation Assitt. Divn. Officer