GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2013/ 54

Dated: 10/07/13

FIRE SAFETY CERTIFICATE

Certified that the Guest House **Ridge Maidens** located at 1004, Faiz Road, Naiwala, Karol Bagh, New Delhi-110005 comprised of Basement, ground floor, mezzanine floor plus three upper floors, basement is vacant/storage, ground floor as reception, mezzanine floor as office, first floor having 05 guest rooms, second floor having 06 guest rooms, third floor having 05 guest rooms (Total 16 guest rooms), One staff room with staff kitchen on terrace was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2010/2386 dated 13.08.2010 owned/occupied by Sh. Anoop Nayyar. The guest house building was re- inspected by the officer concerned of this department on 02.07.2013 in the presence of Sh. Ram Singh Bist (Manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

ou

Copy to:-

1. The Addl. Commissioner of Police (Lic.) 1st floor, P.S., Defence Colony, New Delhi. (Re. No.29010/Addl. C.P./Lic.(H), Dated 13.06.2013)

2. Sh. Anoop Nayyar (Owner), G.H Ridge Maidens, 1004, Faiz Road, Naiwala, Karol Bagh, New Delhi-110005. Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

Basement, Ground Floor, Mezzanine plus three upper Floors.

	INSPE(TION REPORT				
	1. Name & address of the building	Residential (Guest House) Karol Bagh, New-05.				
	2 Type of Occupancy	Residential (Greet House) Von Color				
	3 Type of Case	: New Case/Rene	Karol Bagh, N.D.O.S.			
	 Details of Previous NOC 		6 Date 13.08.2010			
	5 Fire Salety directives letter No	1 <u>0 11 1</u>				
	6 Date of inspection	Λ9	.07.2013	2012		
	Name of Inspecting Officer	O. A. A				
	Name and designation of officer	A.D.O P.S. Dahiya				
	From the building side		0. 0. 1 0. 1			
	9 Year of Construction	Sh M	am Singh Bist	(Monager)		
	10. Applicant's letter No.	99 AIN Addl	C D / 1 100 /	/		
S.	Minimum Standards on fire	NBC	C.P./Lic.(H) d			
No.	prevention and fire safety U/R 33	Requirement	Provided at	Remarks		
Į.	Access to building	nequirement	site	MR/NMR		
	 Road width 	Accessible	00.1			
	Gate width	ACCOURTE	09mtx	MR		
	* Width of internal road		175cmp	MR		
2.	Nimber Width Type 9 A			-		
	Number, Width, Type & Arrangement a Number of staircases	t of Exits		American Committee and the committee of		
		and a second sec		The second secon		
	• Upper Floors	One	One	MR Roine a alder		
	Basements	Two	Two	MR, Being a old Case		
	b. Width of staircases			10/1		
	 Upper Floor 		118cme to 1200m	0000		
	Basements	-	1600 to a Car	MR, Being a old Case		
	C. Protection of exits		160 cms, 95 cms	-06-		
	 Fire check door 			AND THE RESIDENCE AND A STATE OF THE PARTY O		
	pressurization	Colonia de Carrella de Carrell	No.	The second secon		
	d. No. of continuous staircases to		Manus.			
	terrace		A	The second secon		
	e. Width of Corridor		One	-		
	f. Door Size		115cmp, 110cmp	-		
-		-	80 cm x 20 Scms			
3.	Compartmentation	The state of the s	, and particular the	THE STREET STREET, STR		
	 Fire check door 			When the control of t		
	 Sealing of electrical shafts 		·	D _{max}		
	 Fire Rating of shaft door 		Sealed			
	Water Curtain	•				
	 Fire Dampers 		Description of the second seco			
۵.		•	No.			
	Smoke Management System			Annual Section (Section 1) (Se		
	* Basements	30 a/c per	Exhaust Fons			
	 Upper flcors 	hour	are Provided	MR		
			Vatural Ventilato			

2	N/12		44	3 3	
		12 a/c per			
		hour	•		
	Fire Extinguishers	2 2		D	
		Three at each floor			
	• Types	Co, WCo, ABC	rodvided	MR	
	 IS marking 	ISI marked	- da-	MR	
	First-Aid Hose Reels	Dilliarked	1SI Marked	MR	
	Total numbers on each floor				
	 Length of hose reel hose 	<u>One</u> 30 m	Provided	MR	
	Nozzle diameter		-do-	MR	
7,		5 mm	- do'-	MR	2
	Automatic fire detection and alarming	system			
	Type of detectorsLocation of Main Panel	•			
		_			
	researion of Webeater Pauel	-			Manager and the state of the st
	race source of power	-	D.G. Set 425 KVA		
	 Hooters' Location MOEFA 				
		•			
10.	Public Address System	Required	Provided	MR	
111	Automatic Sprinkler System			- ///	
	• Basement	NR	Provided	MR (Area les	4 Hay 200
	 Upper Floor 	•		The Grace (to	s (may bec.
1.1	 Sprinkler above false ceiling 	* 1	1		
11.	Internal Hydrants				
	 Size of riser/down-comer 				
	 Number of hydrants per floor 			-	Topic separate
	 Hose Box 				The state of the s
12.	Yard Hydrants		J.	1	
	 Total number of hydrants 	The second secon	_		And and an analysis of
	 Hose Box 				
13.	Pumping Arrangements				
	 Ground Level 	The state of the s			
	Discharge of main Pump			- 0.000	
	 Head of Main pump 				-
	 Number of main pumps 		2		
	lockey Pump out put				
	 Jockey pump head 				
	Standby Pump out put		Person		
	Standby Pump Head		~ (-	
	Auto Starting/Manual			-	
	stopping	•	-		
	The same region was a same			The second of th	1

N/13 1004, faiz Road, Naiwala, Kasol Bagh, New Delli-05.

F	V					
	Pump House Access	•		***		
	i ci i ace level					
	Discharge of pumpHead of the pump	450 LPM	450 LPM	MR		
	Power Supply	30 M		MR		
	Auto Starting of pump	Required	20 M Provided	MR		
	Auto Starting of pump					
14.	Captive Water Storage for fire fighting	,				
	 Underground tank capacity 	,				
	Draw-off connection					
	Fire service inlet					
	Access to tank		_			
	 Overhead Tank capacity 	4	2500 Cts	had 9 at 11 4 a		
		0 . 1		MR, Being a old cape		
15.	Exit Signage.	Required	Provided	MR		
16.	Drovicion of Life		1			
10.	Provision of Lift Shaft			8		
	The Samuel of Lift Shaft	•	_	-		
	1 1 C33 di 12 di lott oi Lill lobby	-	_			
	 Communication In lift Car Fireman's Grounding Switch 		Provided	MR		
			10011464			
	 Lift Signage 		Provided	Old Cift		
		0				
17.	Standby power supply	Required	Provided	MR		
18.	Defe					
10.	Refuge Area.					
	Total AreaLocation	•		-		
	Ededion	_				
19.	Fire Control Room					
	 Detector System Panel 					
	 Flow Switch Panel 					
	 PA System Panel 					
	Batter backupBuilding Floor Plans	00011	P 1			
		Required	Provided	MR		
		•	•			
20.	Special Fire Protection System for					
	Protection of special Risks, if any:		-			
	apositi itisks, ii dily.		- Andrewson - Andr			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Reeping in view the above substantial compliance of the minimum standards on fire prevention and Fire Safety measures required under the rules it is recommended to grant Fire Safety ertificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial

Signature of Inspecting Officer

Name P.S. Dahiya

Designation AssH. Divisional Officer.

Signature of Inspecting Officer

Name

Designation