GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2013/ 564

Dated: 17/07/13

FIRE SAFETY CERTIFICATE

Certified that the Guest House **Shanti Palace** located at Cottage No- 4 A, West Patel Nagar, New Delhi-110008 comprised of Basement, ground floor plus three upper floors, using basement as Storage, ground floor as reception, hall and pantry, first & second floor each having 08 guest rooms respectively (Total 16 guest rooms), third floor has been sealed by the owner was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2010/1603 dated 01.06.2010 owned/occupied by Sh. Anil Kumar Jain. The guest house building was re- inspected by the officer concerned of this department on 11.07.2013 in the presence of Sh. Sunil Vig (G.M) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

The Addl. Commissioner of Police (Lic.)
 1st floor, P.S., Defence Colony, New Delhi.
 (Re. No.32054/Addl. C.P./Lic.(H), Dated 01.07.2013)

ON

Sh. Anil Kumar Jain (Owner),
 G.H Shanti Palace, Cottage No- 4 A,
 West Patel Nagar, New Delhi-110008.

Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

AMOSH

NIG. Basement, Ground Floor plus three apper floors.

	INSPEC	TION REPORT	and the second	The state of the s				
	Name & address of the building G. b. Cha. 1: Potos. Co. 1.							
	2. Type of Occupancy	Residential	I lough the	7-H, West Patel Ngr				
	3. Type of Case	Residential (Guest House) N.D.08. New Case/Renewal						
	4. Details of Previous NOC	letter No Cil Nedanalenda . In -						
	5. Fire Safety directives letter No							
	Date of inspection	11.07.2013						
No. 1.	/ Name of Inspecting Officer :	A.D.O P.S. Dahiya						
	8. Name and designation of officers	H.P.O	P.S. Dahiya					
	From the building side :		11/1- ()					
	9. Year of Construction .	Retain	1 Vig (G.M) 2009					
	10. Applicant's letter No.	2905/1/6/0	0007	Contract and the second				
	Minimum Standards on fire	NBC/BBL	17, C, 1, 4, 1 (, (H)	dated 01.07.2013				
No.	prevention and fire safety U/R 33		Provided at	Remarks				
1.	Access to building	Requirement	site	MR/NMR				
	Road width	Accessible						
	Gate width	MILESOIDIE	12 mts	MR				
		-	152 cm g	MR				
7	* Width of internal road							
No. 1	Number, Width, Type & Arrangement	t of Exits						
	a. Number of staircases							
	• Upper Floors	7000	Two	MO Qui sola				
	Basements	One	One	MR Beingaoid Os.				
	b. Width of staircases			- 00 -				
	Upper Floor		99000 0000	100 0 1 1 1				
	 Basements 		110 cms to 118 cms	MR, Being a old Cape				
	c Protection of exits		110 cm & co 1/8 cm &	- do -				
	 Fire check door 	And the second s						
	pressurization		<i>y</i> -					
	d. No. of continuous staircases to	The Colonian and the Section of the Colonian and the Colo	3					
	terrace		4	damental time the second of th				
	e. Width of Corridor		1000					
	f. Door Size		102 cms, 178 cms	-				
		~	79 cm & x 203 cm	And the second s				
3.	Compartmentation		110 1003011					
	 Fire check door 		And the second s	The state of the s				
	 Sealing of electrical shafts 							
	Fire Rating of shaft door		Sealed					
	Water Curtain	-	-					
	• Fire Dampers	_	5	Annual Control of the				
4		-	1					
200	Smoke Management System		and the same of th					
	 Basements 	30 a/c per	Exhaust Fans					
	 Upper floors 	hour	are Provided	MR				
	The state of the s	1.	ofuxal Vehlilali					

	NIIA		3	· .		
		12 a/c per hour				
	Fire Extinguishers					
	 Total numbers 	Two at each floor	Provided	N 22		
	• Types	WCo2, ABC	- do -	MR		
	 IS marking 	ISI marked	151 Marked	MR		
	First-Aid Hose Reels		131 Marked	MR		
	 Total numbers on each floor 	One	Provided	bae		
	 Length of hose reel hose 	30 m	- do -	MR		
	 Nozzle diameter 	5 mm	- do:-	MR		
	Automatic fire detection and alarming	system	- 00	MR		
	 Type of detectors 					
	 Location of Main Panel 					
	 Location of Repeater Panel 					
	 Alternate source of power 		A9 N C Cat H 1951			
	 Hooters' Location 		02 D.G.Set 7 125	CVA		
	MOEFA	Received	Parallel			
	Public Address System	Required	Provided	MR		
٥.	Automatic Sprinkler System — do					
	Basement	Recuired	Parille 1			
	 Upper Floor 	Required	Provided	MR		
	 Sprinkler above false ceiling 		Provided			
	Internal Hydrants			+		
	Size of riser/down-comer		1000			
	 Number of hydrants per floor 		100 M·M			
	Hose Box		One	5		
	Yard Hydrants	-	- do -			
	 Total number of hydrants 		J			
	* Hose Box					
j.,	Pumping Arrangements		Name -			
	 Ground Level 					
	Discharge of main Pump					
	Head of Main pump Number of main pumps Jockey Pump out put		-			
				•		
		-		_		
	 Jockey pump head 					
	Standby Pump out put			`		
	Standby Pump Head		-	_		
	Auto Starting/Manual	_				
	stopping			-		

N/11. Cottage 4-A, West Pafel Magar, New Delhi-110008.

9						
	Pump House Access					
	 Terrace level 					
	Discharge of pump	4501 PM Fach	576 LPM Each	000 1000		
	Head of the pump	30 M Each		MR (02 Pc		
	Power Supply	Required	36 M Each Provided	MR		
	Auto Starting of pump	1	7 30018120	MR		
14.	Captive Water Storage for fire fighting		A de la constante de la consta			
	 Underground tank capacity 					
	 Draw-off connection Fire service inlet Access to tank Overhead Tank capacity 	-		-		
			Provided	-		
			I FOVIDED			
		10000 (fr	10000 Ctr	MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.					
	 Pressurization of Lift Shaft 					
	 Pressurization of Lift lobby 			•		
	 Communication In lift Car Fireman's Grounding Switch Lift Signage 	,	^	-		
			Provided	MR		
		Kegleired	- do -	MR		
		Required -do-	-do-	MR		
17.	Standby power supply	Required	Provided	MR		
18.	Refuge Area.					
	> Total Area	-				
	Location	•				
19.	Fire Control Room					
	 Detector System Panel 					
	 Flow Switch Panel 	-				
	PA System PanelBatter backupBuilding Floor Plans	-		`		
				-		
		Required	Provided	MR		
		-	~			
20.	Special Fire Protection System for Protection of special Risks, if any:					

he fire protection systems provided in the building were test checked and found functional at he time of inspection.

Geeping in view the above substantial compliance of the minimum standards on fire prevention and Fire Safety measures required under the rules it is recommended to grant Fire Safety ertificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial umhare

Designation ASSH. Divisional Officer.

Signature of Inspecting Officer

Name

Designation