GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2013/S2 / 597

Dated: 23 | 07 | 13

FIRE SAFETY CERTIFICATE

Certified that the Hotel Southern Residency located at 18/5, Arya Samaj Road, Karol Bagh, New Delhi-110005 comprised of Basement, ground floor plus four upper floors, using basement as office & store, ground floor as office & shops, first floor having reception & 07 guest rooms with 01 store, second & third floor each having 07 guest rooms with 01 store respectively (Total 21 guest rooms), forth floor having two big hall & this vide one store issued NOC department No.F.6/DFS/MS/2010/GH/2733 dated 22.09.2010 owned/occupied by Sh. A. Krishna Mohan. The guest house building was re- inspected by the officer concerned of this department on 16.07.2013 in the presence of Sh. B. Surya Rao (G.M) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

1. The Addl. Commissioner of Police (Lic.) 1st floor, P.S., Defence Colony, New Delhi. (Re. No.32652/Addl. C.P./Lic.(H), Dated 02.07.2013)

Out-

2. Sh. A. Krishna Mohan (Owner), Hotel Southern Residency, 18/5, Arya Samaj Rd, Karol Bagh, New Delhi-110005. Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

Basement, Ground Floor plus four apper Floors.

	INSPEC	CTION REPORT	1			
	1. Name & address of the building2. Type of Occupancy3. Type of Case	Hotel Southers	n Residency, 18	15 Arya Samo: A		
	2. Type of Occupancy 3. Type of Case	Residential (C	yest House)	Karol Bagh N.D.		
		· HEW Case/ LANG	M 91			
	Second of Liethon? MOC	: Letter No.F6/DI	33 Date <i>22</i> , 09, 201			
	5. Fire Safety directives letter No6. Date of inspection					
		16.				
	or makecing officel	A.D.O. P.S. Dahiya				
	ocale action of onicers					
	9. Year of Construction	Sh. B. Surya Roo (G.M) Before 2009 32652/ Addl. C.P./Lic. (H) dated 02.07.13				
	10. Applicant's letter No.					
5	Minimum Standards on fire	SABSA MOOT	C.r./Lic.(H) a			
No.	prevention and fire safety U/R 33	NBC BBL	Provided at	Remarks		
1.	Access to building	Requirement	site	MR/NMR		
	Road width	Accessible	09mts	5.1.2		
	Gate width	MCCOSTBIE		MR		
	Width of internal road	-	125cm3	MR		
2.				-		
Accession and a	Number, Width, Type & Arrangemer a. Number of staircases	it of Exits				
	Upper FloorsBasements	One	One	MR, Cold Cas		
	b. Width of staircases	do -	-do-	MR, (old Cas		
	opper 11001		125 cms to 141 cms	MR. Cold Case		
	 Basements Protection of exits 		100 cms	MR, Cold Case		
	Fire check door			1		
			•			
	• pressurization					
	d. No. of continuous staircases to terrace					
	e. Width of Corridor		One			
	f. Door Size	-	256 cm &, 160 cmp			
		-	BICMS X 202 Cmp			
3.	Compartmentation		1			
	 Fire check door 					
	 Sealing of electrical shafts 					
	 Fire Rating of shaft door 		Sealed			
	Water Curtain	•				
	 Fire Dampers 					
4.				· Name		
	Smoke Management System			Andrew Committee of the		
	 Basements 	30 a/c per	Exhaust Fans	h a 0		
	 Upper flcors 	hour	are Provided	MR		
			vatural Ventilation	n MR		

Fire Extinguishers Total numbers Total numbers Types Total numbers Two at each Floor Provided Types	
Fire Extinguishers * Total numbers **Total numbers **Total numbers	· · · · · · · · · · · · · · · · · · ·
Fire Extinguishers Total numbers Two at each floor Provided	-
· Total numbers Two at each Floor Possilad	
Passilad	
1/1/2	MR
* IS marking ISI marked	MR
First-Aid Hose Reels 4.51 Marked 4.51 Marked	MR
* Total numbers on each floor One Possidad	
* Length of hose reel hose 30 m	7R
Nozzle diameter 5 mm	UR.
	MR
• ype of detectors	
* Location of Main Panel Provided	
* Location of Repeater Panel	
• Alternate source of power	
* Hooters' Location - D.G. Set of 125 KVA	
MOFFA	
	1R
	7R
1 Amer System	1
1	
* Upper Floor (Corridor)	
* Upper Floor (Corridor) - Trovided MR * Sprinkler above false ceiling	
* Upper Floor (Corridor) - 1	
* Upper Floor (Corridor) * Sprinkler above false ceiling Internal Hydrants * Size of riser/down-comer	
* Upper Floor (Corridor) * Sprinkler above false ceiling Internal Hydrants * Size of riser/down-comer * Number of hydrants per floor	
* Upper Floor (Coordoor) * Sprinkler above false ceiling Internal Hydrants * Size of riser/down-comer * Number of hydrants per floor * Hose Box	
* Upper Floor (Corridor) * Sprinkler above false ceiling Internal Hydrants * Size of riser/down-comer * Number of hydrants per floor * Hose Box 2 Yard Hydrants	
* Upper Floor (Corridor) * Sprinkler above false ceiling Internal Hydrants * Size of riser/down-comer * Number of hydrants per floor * Hose Box 2. Yard Hydrants * Total number of hydrants	
* Upper Floor (Corridor) * Sprinkler above false ceiling Internal Hydrants * Size of riser/down-comer * Number of hydrants per floor * Hose Box * Total number of hydrants * Hose Box	
* Upper Floor (Corridor) * Sprinkler above false ceiling Internal Hydrants * Size of riser/down-comer * Number of hydrants per floor * Hose Box 2. Yard Hydrants * Total number of hydrants * Hose Box 3. Pumping Arrangements	
* Upper Floor (Corridor) * Sprinkler above false ceiling * Internal Hydrants * Size of riser/down-comer * Number of hydrants per floor * Hose Box * Total number of hydrants * Hose Box	
* Upper Floor (Corridor) * Sprinkler above false ceiling Internal Hydrants * Size of riser/down-comer * Number of hydrants per floor * Hose Box Yard Hydrants * Total number of hydrants * Hose Box Pumping Arrangements * Ground Level	
* Upper Floor (Coroldor) * Sprinkler above false ceiling Internal Hydrants * Size of riser/down-comer * Number of hydrants per floor * Hose Box 2. Yard Hydrants * Total number of hydrants * Hose Box 3. Pumping Arrangements * Ground Level * Discharge of main Pump * Head of Main pump	
* Upper Floor (Coordoor) * Sprinkler above false ceiling Internal Hydrants * Size of riser/down-comer * Number of hydrants per floor * Hose Box 2 Yard Hydrants * Total number of hydrants * Hose Box 3 Pumping Arrangements * Ground Level * Discharge of main Pump * Head of Main pump * Number of main pumps	
* Upper Floor (Corridor) * Sprinkler above false ceiling Internal Hydrants * Size of riser/down-comer * Number of hydrants per floor * Hose Box 2 Yard Hydrants * Total number of hydrants * Hose Box 3. Pumping Arrangements * Ground Level * Discharge of main Pump * Head of Main pump * Number of main pumps * lockey Pump out put	
* Upper Floor (Corridor) * Sprinkler above false ceiling Internal Hydrants * Size of riser/down-comer * Number of hydrants per floor * Hose Box Yard Hydrants * Total number of hydrants * Hose Box Pumping Arrangements * Ground Level * Discharge of main Pump * Head of Main pump * Number of main pumps * Jockey Pump out put * Jockey pump head	
* Upper Floor (Coroldor) * Sprinkler above false ceiling Internal Hydrants * Size of riser/down-comer * Number of hydrants per floor * Hose Box Yard Hydrants * Total number of hydrants * Hose Box Pumping Arrangements * Ground Level * Discharge of main Pump * Head of Main pump * Number of main pumps * Jockey Pump out put * Jockey pump head * Standby Pump out put	
• Upper Floor (Corridor) • Sprinkler above false ceiling Internal Hydrants • Size of riser/down-comer • Number of hydrants per floor • Hose Box Yard Hydrants • Total number of hydrants • Hose Box Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > lockey Pump out put > Jockey pump head > Standby Pump Head	
• Upper Floor (Corridor) • Sprinkler above false ceiling • Sprinkler above false ceiling • Internal Hydrants • Size of riser/down-comer • Number of hydrants per floor • Hose Box • Total number of hydrants • Total number of hydrants • Hose Box • Pumping Arrangements • Ground Level • Discharge of main Pump • Head of Main pump • Number of main pumps • Nockey Pump out put • Jockey Pump head • Standby Pump out put • Standby Pump Head • Auto Starting/Manual	
• Upper Floor (Corridor) • Sprinkier above false ceiling Internal Hydrants • Size of riser/down-comer • Number of hydrants per floor • Hose Box Yard Hydrants • Total number of hydrants • Hose Box Pumping Arrangements • Ground Level > Discharge of main Pump > Head of Main pump > Number of main pumps > lockey Pump out put > Jockey pump head > Standby Pump Head	

18/5, Arya Samaj Road, Karol Bagh, New Delli-05.

	Ratol Day	m, New Der					
	Pump House Access	•	-				
	 Terrace level 						
	Discharge of pump	450LPM	456 LPM	MR Cold Cas			
	Head of the pump	30M		MR			
	Power Supply	Required	30 M Provided	MR			
	Auto Starting of pump	, .					
14.	Captive Water Storage for fire fighting						
	 Underground tank capacity 		1				
	Draw-off connection	_					
	Fire service inlet						
	Access to tank						
	Overhead Tank capacity		6000 Ltr	MR (Old Case			
15.	Exit Signage.	Required	Provided	MR			
16.	Provision of Lifts.						
	 Pressurization of Lift Shaft 						
	 Pressurization of Lift Iobby Communication In lift Car Fireman's Grounding Switch Lift Signage 	Page 100 Carlo Car	1				
			0				
			Provided	MR			
		Required	-do-	MR			
		- do -	-do -	MR			
17.	Standby power supply	Required - do - Required	Provided	MR			
18.	Refuge Area.						
	> Total Area > Location	-					
		-		-			
19.	Fire Control Room						
	 Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans 		•				
		•					
		-		-			
		Required	Provided	MR			
		/_	•				
20.	Special Fire Protection System for Protection of special Risks, if any:			-			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

seeping in view the above substantial compliance of the minimum standards on fire prevention and Fire Safety measures required under the rules it is recommended to grant Fire Safety ertificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serialaumhors -

Name P.S. Dahiya
Designation ASSH. Divisional Officer.

Signature of Inspecting Officer

Name

Designation