GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2013/57 / 592

Dated: 23/07/13

FIRE SAFETY CERTIFICATE

Certified that the **Hotel Vishal Heritage** located at 5/11, WEA, Karol Bagh, New Delhi-110005 comprised of Basement, ground floor plus three upper floors, using basement as Hall/Storage, ground floor as reception and 04 guest rooms, first, second & third floor each having 08 guest rooms respectively (Total 28 guest rooms), A pantry for staff in tin shed on terrace was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2010/2626 dated 08.09.2010 owned/occupied by Sh. Dheeraj Grover. The guest house building was re- inspected by the officer concerned of this department on 16.07.2013 in the presence of Sh. Neeraj Kumar and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on.....23./.9.7.//.3......at New Delhi.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

1. The Addl. Commissioner of Police (Lic.) 1st floor, P.S., Defence Colony, New Delhi. (Re. No.32634/Addl. C.P./Lic.(H), Dated 02.07.2013)

Ony.

2. Sh. Dheeraj Grover (Owner), Hotel Vishal Heritage, 5/11, WEA, Karol Bagh, New Delhi-110005. Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

Basement, Ground Floor plus three Lepper Floors.

	INCREA	TION REPORT			
	 Name & address of the building 	Hotel Vishal A	Heritage, 5/11	, WEA, Karol Bay	
	7. Type of Occupancy	Residential (G	west House)	N.D-65	
	. Type of case	: New Case/Renev	val		
	5. Fire Safety directives letter No	: Letter No. F. 6/D	FS/MS GH/2010/2	626 Date 08 · 09 · 20	
	6. Date of inspection	1.0			
	/ Name of Inspecting Officer	16.07.2013			
	8. Name and designation of officer	c A'U'	o P.S. Dah	iya	
	From the building side		leercy Kuma		
	9. Year of Construction	Retax	e 2010		
	10. Applicant's letter No.	32634/ Addi	C.P. ILIC. CH) dated 02.07.12	
5.	Minimum Standards on fire	NBC/BBL	Provided at	Remarks	
No.	prevention and fire safety U/R 33	Requirement		MR/NMR	
1.	Access to building				
	 Road width 	Accessible	06mtr	MR	
	 Gate width 		180 Cm8	MR	
	 Width of internal road 				
2.	Nilmber, Width, Type & Arrangemer	it of Exits		-	
	a. Number of staircases				
	 Upper Floors 	One	One	me laiden	
	 Basements 	- do -	- do -	MR, Cold Capa - do -	
	b. Width of staircases .		200	- 00	
	 Upper Floor 	· ·	125cms	MR, Cold Cas	
	 Basements 		140 cm 8	1º/K, Cola cus	
	C. Protection of exits	and the second s	1 10 Cmp	- 00	
	 Fire check door 				
	pressurization				
	d. No. of continuous staircases to			7.7	
	terrace		One		
	e. Width of Corridor		230 Cmp, 155cm		
	f. Door Size				
3.	Comportmental		BOCMS X205CH	, -	
	Compartmentation				
	 Fire check door 				
	 Sealing of electrical shafts 	•	Sealed		
	 Fire Rating of shaft door 		0)00(100		
	Water Curtain				
	 Fire Dampers 				
4.	Smoke Management System		All considerations		
	* Basements	30 a/c per	Exhaust Fans		
	 Upper flcors 	hour	are Provided	MR	
			Vatural Ventilar	Sch MR	

		Till.	The state of the s	
		12 a/c per hour	nombosio.	
F	ire Extinguishers			The second section of the second second second
	 Total numbers 	Two ateach floor	0 4 4	
	* Types .	Co, WCo,	roovided	MR
	 IS marking 	ISI marked	-do-	MR
F	irst-Aid Hose Reels		1SI Marked	MR
	 Total numbers on each floor 	One	0	A
	 Length of hose reel hose 	30 m	Poorided	MR
	 Nozzle diameter 	5 mm	- clo -	MR
P	Automatic fire detection and alarming		-do:-	MR
	 Type of detectors 	system		
	 Location of Main Panel 	A CONTRACTOR OF THE CONTRACTOR		
	 Location of Repeater Panel 			
	 Alternate source of power 			
	 Hooters' Location 		D. G. Set of 82.5 KI	A -
P	MOEFA	2	-	+
	Public Address System	Required	Provided	MR
	Automatic Sprinkler System	- 010 -	- do -	MR
	Basement	0		
	Upper Floor	Kegtured	Provided	MR
	 Sprinkler above false ceiling 			-
1	nternal Hydrants			
	Size of riser/down-comer			
			*	
	 Number of hydrants per floor Hose Box 		-	-
- :	rard Hydrants			
	The state of the s		1-	
	Total number of hydrantsHose Box			
	Pumping Arrangements			+
+	Ground Level			
	o section be of main rump			
	Head of Main pumpNumber of main pumps			
	> lockey Pump out put			
	Jockey pump head			
	Standby Pump out put			
	Standby Pump Head		timber.	
	Auto Starting/Manual			
	stopping			
		40.00		

5/11, WEA, Karol Bugh, New Delli - 110005.

	WER DELY .	/(
	Pump House Access			-		
	 Terrace level 	NAME OF THE OWNER O				
	Discharge of pump	450 LPM	825 LPM	MR (Old Ca)		
	Head of the pump	30M		MR		
	Power Supply	Required	30 M Provided	MR		
	Auto Starting of pump			-		
14.	Captive Water Storage for fire fighting					
	 Underground tank capacity 		,			
	Draw-off connection	-		-		
	Fire service inlet		•			
	Access to tank	•		-		
	 Overhead Tank capacity 	-	6000 Ctr	MR COIDC		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.					
10.	Chick of C					
	Pressurization of Lift lobbyCommunication In lift Car					
			0			
			Provided	MR		
	• Fireman's Grounding Switch	Required	-do-	MR		
	 Lift Signage 	Required - do-	-do-	MR		
17.	Standby power supply	Required	Provided	MR		
18.	Refuge Area.					
	> Total Area		* - * · · ·	-		
	> Location			_		
	1					
19.	Fire Control Room					
	Detector System PanelFlow Switch PanelPA System Panel			-		
				-		
	Batter backup	Required	Provided	MR		
	 Building Floor Plans 	4	-			
20.				~		
	Protection of special Risks, if any:					

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the above substantial compliance of the minimum standards on fire prevention Fire Safety measures required under the rules it is recommended to grant Fire Safety ertificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers

Signature of Inspecting Officer

Name P.S. Dahiya
Designation Asptt. Divisional Officer.

Signature of Inspecting Officer

Name

Designation