GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: NEW DELHI-110001 Fax: 23412593, E-mail: cfohq.dlfire@nic.in, Tel:- 011-23414333

NO. F6/DFS/MS/GH/2013/ NDZ \ 589

Dated: 19/07/13

FIRE SAFETY CERTIFICATE

Certified that Kastle Guest House, J-1/16, Darya Ganj, New Delhi-2, comprised of basement (Commercial), ground (03 rooms, Reception, Office & lobby), first floor (06 rooms), Second floor ((06 rooms), third floor (04 rooms), and terrace (Open area + Water tank) Total 19 rooms, was granted NOC by this department vide letter No. F.6/MS/DFS/GH/10/789 Dated: 16-03-10. The premises was re-inspected by the officers concerned of this department on 29-06-2013 in the presence of Chander Kishore, Manager of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy of 19 guest rooms with effect from 1900100 for a period of --0-3-- years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules,2010.

Issued on 19/07/13 at New Delhi by.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE

Copy to: -0/c &

- 1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.
- 2. M/s Kastle Guest House, J-1/16, Darya Ganj, New Delhi-2

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time.
- b. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- c. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- d. The trained fire fighting staff shall be available round the clock.
- e. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: Kastle Guest House, J-1/16, Darya Ganj, New Delhi-2

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: Letter No. F.6/DFS/MS/ /GH/159 Dated: 16-03-10

28

5. Fire Safety directives letter No: F.6/DFS/MS/92/GH/589 Dated: 06-04-92

6. Date of inspection

: 29-06-2013

7. Name of the Inspecting Officers: Sanjay Kumar Tomar, ADO (SPM) & DCFO (NDZ)

8. Name and designation of officers

from the building side

:Sh. Chander Kishore

9. Year of Construction

. _

10. Applicant's letter No.

: Nil dated 25/06/13

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR
1	Access to building			
	Road width	Accessible	6 mtr (Aprox)	MR
	Gate width	N/A	N/A	N/A
	Width of internal road	N/A	N/A	N/A
2	Number, Width, Type & Arrangement	of Exits		
	a. Number of staircases		· · · · · · · · · · · · · · · · · · ·	
	Upper Floors	One	One	MR
	Basements	Two	Two	MR
	b. Width of staircases		2 mg mg	
	Upper Floors	108 Cms	108 Cms	MR
	Basements	100 Cm & 108 Cm	100 Cms & 108 Cms	MR
	c. Protection of exits	N/A	N/A	N/A
	Fire check door	N/A	N/A	N/A
	 Pressurization 	N/A	N/A	N/A
	e. No. of continuous staircases to terrace	Required	Provided	MR
	g. Width of Corridor	N/A	N/A	N/A
	h. Door Size	N/A	N/A	N/A
		N/A	N/A	N/A

3	Compartmentation.				
	Fire check door	N/A	N/A	N/A	
	Sealing of electrical shafts	N/A	N/A	N/A	
	Fire Rating of shaft door	N/A	N/A	N/A	
	Water Curtain	N/A	N/A	N/A	
	Fire Dampers	N/A	N/A	N/A	
4	Smoke Management System.				
	Basements	30 a/c per hour	Exhaust fans	MR	
	Upper floors		provided	95	
		12 a/c per hour	N/A	N/A	
5	Fire Extinguishers				
	Total numbers	Twelve	Provided	MR	
	• Types	Water Co2, Co2, ABC	Provided	MR	
	IS marking	ISI marked	Provided	MR	
6	First-Aid Hose Reels.				
	• Total numbers	Two	Provided	MR	
	• Length of hose reel hose	30 m	Provided	MR	
	Nozzle diameter	5 mm	Provided	MR	
7	Automatic fire detection and alarming system.				
	Type of detectors	N/A	N/A	N/A	
	Location of Main Panel	N/A	N/A	N/A	
	Location of Repeater Panel	N/A	N/A	N/A	
	Alternate source of power	N/A	N/A	N/A	
	Hooters' Location	N/A	N/A	N/A	
8	MOEFA	N/A	N/A	N/A	
9	Public Address System.	Required	Provided	MR	
10	Automatic Sprinkler System.				
	• Basement	Required	Provided	MR	
	• Upper Floor	N/A	N/A	N/A	
	Sprinkler above false ceiling	N/A	N/A	N/A	
11	Internal Hydrants				
11	THECH HAI TTY UT AIRES	·			

-	 Size of riser/down-comer 	N/A	116, Darya Ganj N/A	N/A
	 Number of hydrants per floor 	N/A	N/A	N/A
	• Hose Box	N/A	N/A	N/A
2 Yar	d Hydrants.			
	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
3 Pun	ping Arrangements.			
•	Ground Level	N/A	N/A	N/A
	Discharge of main Pump	N/A	N/A	N/A
	Head of Main pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	Jockey Pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	Standby Pump out put	N/A	N/A	N/A
	Standby Pump Head	N/A	N/A	N/A
	Auto Starting/ Manual	N/A	N/A	N/A
	stopping	N/A		N/A
	Pump House Access		N/A	
•	Terrace level	N/A	N/A	N/A
	Discharge of pump	450 LPM	Provided	MR
	Head of the pump	40 M	Provided	MR
	Power SupplyAuto Starting of pump	Required	Provided	MR
		N/A	Switch Provided	MR
Capt	tive Water Storage for fire fighting.	<u> </u>		
•	Underground tank capacity	N/A	N/A	N/A
		N/A	N/A	N/A
		N/A	N/A	N/A
		N/A	N/A	N/A
•	Overhead Tank capacity	10000 Ltrs	Provided	MR
Exit	Signage.	Required	Provided	MR

16

Provision of Lifts.

	Pressurization of Lift Shaft	Required	Provided	MR	
	Pressurization of Lift lobby	N/A	N/A	N/A	
	Communication In lift Car	Required	Provided	MR	
	• Fireman's Grounding Switch	Required	Provided	MR	
	• Lift Signage	Required	Provided	MR	
7	Standby power supply	Required	Provided	MR	
			DG set (7.5 KVA)		
18	Refuge Area.				
	> Total Area	N/A	N/A	N/A	
	Location	N/A	N/A	N/A	
19	Fire Control Room				
	Detector System Panel	N/A	N/A	N/A	
	• Flow Switch Panel	N/A	N/A	N/A	
	PA System Panel	N/A	N/A	N/A	
	Batter backup	N/A	N/A	N/A	
	 Building Floor Plans 	N/A	N/A	N/A	
20 ERI	Special Fire Protection Systems for	Required	Provided one Co2	MR	
SP	Protection of special Risks, if any:		fire extinguisher		
1	m)		near Elect Panel		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer Name: SANJAY KUMAR TOMAR

Designation: - Asstt. Div. Officer (SPM)