GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. F6/OFS/ans/8chool/2012/W2/684 Dated: 08/08/2013

FIRE SAFETY CERTIFICATE

Certified that the Sarvodaya Kanya Vidyalaya, Nehru Vihar, Delhi is comprised of Ground + three Upper Floor & Ground Only owned/occupied by Sarvodaya Kenya Vidyalaya have complied with the fire prevention and fire safety requirements in accordance with the Circular No F.16/Estate/CC/Fire Safety/2011/3298-3398 dated 01/03/2011 issued by Director of Education NBC Part IV and verified by the officer concerned of Fire Service on 20/07/2013 in the presence of Sh. Sushma J Toppa and that the building / premises is fit for occupancy of Educational building with effect from 0% / 2013 for a period of three years, in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Conditions for the validity of Fire Safety Certificate:

- All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- The trained fire fighting staff should be available round the clock.
- Any deviation with regard to the construction etc shall be verified by the concerned sanctioning agency.
- The basement shall be used strictly as per the provision of building bye laws.
- This certificate cannot be treated in any case for regularizations of unauthorized construction
- The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form WWW.dfs.Delhigovt.nic.in

Issued on <u>8/58/12</u> at New Delhi

(SANTOKH SÍNGH) Chief Fire Officer Delhi Fire Service Ph: 011-23414250 cfowz.dlfire@nic.in

Copy to:

The Principal, Sarvodaya Kanya Vidyalaya, Nehru Vihar, Delhi

2. The Director of Education, old Secretariate, Delhi. 800

INSPEC	CTION RI	EPORT

1. Name & address of the building Sarve 2. Type of Occupancy	oleya Kanus	lidualous Not	
2. Type of Occupancy	atonal	wysinga ji sent	(I.D 120 For
	Case/ Renewal		700
4. Details of previous NOC : Letter		Ni L Date	d·
5. Fire Safety directives letter No Circ	ular Dir	of Ednn. 1	
6. Date of inspection	7-2013	27 20mm. 1	(3)201)
7. Name of the Inspecting Officers:	O-SHVA	m 1.41	
8. Name and designation of officers			
from the building side	Sushma J	Toppo. (for old + 3 upper fla	
9. Year of Construction / 198	4. (Groun	1+21200	ncipal)
10. Applicant's letter No.	(0)	& block)	or and Greenedo
	-		LKW
Minimum Standards on fire	Techno, DI)	Provided at site	Remarks
prevention and mesalety 0/R 33	Requirement		MR/NMR
Access to building	the state of the s		
Road width	Accessible	9 m	mIR
• Gate width	-06-	4.5 m	MIR
 Width of internal road 	-rlo-	6 m	MIR
Number, Width, Type & Arrangement		6 7-1	126/00
a. Number of staircases			
Upper Floors	4	4	mik
• Basements	4	4	MIR
b. Width of staircases	NiL	Nic	NiL.
Upper Floors		1.5 m (Two No	5)
Basements	1.5 m	1.33m (Two)	is) m/K
c. Protection of exits	Niz	NiL	NiL
Fire check door		NIR	
Pressurization		1,1,1	
e. No. of continuous staircases to terrace	0	1	
g. Width of Corridor	R	2	MIR
h. Door Size	R	2.65 m	MIR
50 COM 50	1m	1.07m (twood	
Compartmentation.		Cre ruan n	Strelint each ch
Fire check door		NIK	
 Sealing of electrical shafts 			7
 Fire Rating of shaft door 			
Water Curtain		/	
• Fire Dampers			•
Smoke Management System.	hard of the second		
• Basements	30 a/c per hour	NIG	
 Upper floors 	12 a/c per hour	1	

	Fire Extinguishers	The second secon			
	Total numbers	45	Provided.	MIR	
V. 1	Types	ISI marked	Poorided	MIR	
	• IS marking	131 marked	Provided	5 mil	
6.	First-Aid Hose Reels.		B	Α.	
	Total numbers on each floor	Two	Two	M)R	
	• Length of hose reel hose	30 m	Provided	MIR	
	Nozzle diameter	5 mm	Provided	MIR	
7	Automatic fire detection and alarming	system.	1-0010co	747K	
	Type of detectors		NIR		
	Location of Main Panel	3561	1		
9	• Location of Repeater Panel				
	Alternate source of power				
	Hooters' Location				
8	MOEFA				
9	Public Address System.		NIR	-	
	,		NIR		
1()	Automatic Sprinkler System.	A Colored Color	1.10		
	• Basement		NIC	4	
	• Upper Floor		/ /		
	Sprinkler above false ceiling				
11	Internal Hydrants				
	Size of riser/down-comer	NIK	100 mm (100)	NIR	
	Number of hydrants per floor	N)R NIR	2 No's from	NIR NIR	
12	Number of hydrants per floorHose Box	N)K N/R N/R	2 Not Provide	W NIR	
12	Number of hydrants per floorHose BoxYard Hydrants.	N)R N/R N/R	2 Nos Provide	W NIR	
12	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants 	N)R N/R N/R	2 No's from	W NIR	
	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box 	N)R N/R N/R	2 Nos Provide	W NIR	
12	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. 	N)R N/R N/R	2 Nos Provide	W NIR	
	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level 	N)R N/R N/R	2 Nos Provide	W NIR	
	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump 		2 Nos Provide	W NIR	
	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump 	N)R N/R N/R	2 Nos Provide	W NIR	
	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps 		2 Nos Provide	W NIR	
	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put 		2 Nos Provide	NIR NIR	
	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements: Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head 		2 Nos Provide	NIR NIR	
	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put 		2 Nos Provide	NIR NIR	
	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head 		2 Nos Provide	NIR NIR	
	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head 		2 Nos Provide	NIR NIR	
	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level 		2 Nos Provide	NIR NIR	
	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements: Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump 		2 Not 9 Provided NIR NIR	NIR NIR	
	 Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level 		2 No!3 formides NIR NIR	Y NIR	

14	Captive Water Storage for fire fighting	<i>z</i> .	2	•
	 Underground tank capacity Draw-off connection 	NIR	50 000 14.	NIR
	Fire service inlet			
	> Access to tank	·		
	Overhead Tank capacity		<u> </u>	4
		10000 Lts.	. 15000 Lts.	MIR
5	Exit Signage.	R	Provided	MIR
6	Provision of Lifts.			
	Pressurization of Lift Shaft		NIA	
	Pressurization of Lift lobby	(A.)	1	
	Communication In lift Car			
	Fireman's Grounding Switch			
	Lift Signage	on ,		
7	Standby power supply		NIR	· · · · · · · · · · · · · · · · · · ·
8	Refuge Area.			
	➢ Total Area		NIA	
	> Location		1	Q 2
9	Fire Control Room			3 - 2 - a ⁵
-	Detector System Panel		NIR	
	Flow Switch Panel		7770	
	PA System Panel	-	 	
	Batter backup			
	Building Floor Plans			
()	Special Fire Protection Systems for Protection of special Risks, if any:		- NiL -	

The fire protection systems provided in the building were test checked and found functional at the time

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers....

Signature of the Inspecting Officer

Name

Designation

Signature of the Inspecting Officer

Name (SHYAM LAL)

Designation Assitt. Divn. officer

Delo lur)