GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. F6/DF5/ms/school/2013/W2/683

Dated: 08 / 08 /2013

FIRE SAFETY CERTIFICATE

Certified that the <u>Yadavendra Public School</u>, B-2097, Sant Nagar, Burari, Delhi110084 is comprised of <u>Ground + One upper floor having School on G.F only and residence</u>
at first floor owned/occupied by <u>Yadavendra Edmn. Society</u> complied with the fire prevention and fire safety requirements in accordance with the <u>Circular No F.16/Estate/CC/Fire</u>
Safety/2011/3298-3398 dated 01/03/2011 issued by Director of Education and verified by the officer concerned of Fire Service on 10/07/2013 in the presence of <u>Ms. Jyoti</u> and that the building / premises is fit for occupancy of <u>Educational</u> building with effect from <u>organical for a period of three years</u>, subject to following conditions.

Conditions for the validity of Fire Safety Certificate:

- 1 All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2 Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

3 The trained fire fighting staff should be available round the clock.

4 Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.

The basement shall be used strictly as per the provision of building bye laws.

6 This certificate cannot be treated in any case for regularizations of unauthorized construction

7 The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>WWW.dfs.Delhigovt.nic.in</u>

Issued on <u>68/68/12</u> at New Delhi

(SANTOKH SINGH)
Chief Fire Officer
Delhi Fire Service
Ph: 011-23414250
cfowz.dlfire@nic.in

Copy to:

- 1. The Principal, Yadavendra Public School, B-2097, Sant Nagar, Burari, Delhi-110084.
- 2. The Addl. Director of Education, North MCD, Civic Centre New Delhi.

| 6 | INSPEC | CTION REPORT | | |
|-----|---|--|------------------|--|
| | 1. Name & address of the building Vad 2. Type of Occupancy | vonder l. 11 | Se Se / 18-70 | 97 Co. + 01 |
| | 2. Type of Occupancy | rena la judi | C SEMOUT, D 20 | Parcerial |
| | 3. Type of Case : New C | Case/ Renewal | | Dusaos, De |
| 4 | 4. Details of previous NOC : Letter | | N'C Date | d· |
| | | NAME AND ADDRESS OF THE OWNER, WHEN PERSONS NAME AND ADDRESS OF TH | of Edm. 1 | |
| (| | 7-2013 | 1 40000 | 10/2011 |
| 7 | 7. Name of the Inspecting Officers : | 00-A.S. | HVAMLAL | The state of the s |
| 8 | 3. Name and designation of officers | | | 2 2 |
| | from the building side : Ms. | Tayoli | | |
| 9 | Year of Construction 200 | 8 School | A Greand & | loor only & - floor is residence |
| 1 (| 0. Applicant's letter No. | | - firs | floor is resident |
| | 27 | dated 81 | 6/2013 | |
| S. | , | A | | |
| No. | Minimum Standards on fire prevention and fire safety U/R 33 | Requirement | Provided at site | Remarks |
| 1 | | 1/3/2011 | | MR/NMR |
| 1 | Access to building | 1 | | |
| | Road width | Accessible | 6 m | MIR |
| a | • Gate width | -do- | 2.5m x 2 | mIR |
| | Width of internal road | NIA | NIA | NIA |
| 2 | Number, Width, Type & Arrangement | of Exits . | | |
| | a. Number of staircases | | NIR | |
| | • Upper Floors | | | |
| 81 | • Basements | | | |
| 8 | b. Width of staircases | | 1 | , |
| | • Upper Floors | | | |
| | Basements | | | |
| | c. Protection of exits | | | |
| | Fire check door | | | |
| | • Pressurization | | | |
| | e. No. of continuous staircases to terrace | | | |
| - (| g. Width of Corridor | | | |
| | h. Door Size | 1 | 1 m (one do | mil |
| 3 | Compartmentation. |) m | | Stuclus |
| | Fire check door | 2 | NIR | |
| | Sealing of electrical shafts | | 1111 | |
| | • Fire Rating of shaft door | | / | |
| | Water Curtain | | | |
| | • Fire Dampers | | | |
| 1 ; | Smoke Management System. | | .1 | |
| | Basements | 30 a/c per hour | MIL | |
| | • Upper floors | 12 a/c per hour | 1 1 1 | |

N-2

| | Fire Extinguishers | | | |
|---|---|--|-------------------------------------|--|
| | Total numbers | 4 | Provided 2(2:5kg) Provided Provided | mla |
| | • Types | ABC/co | 2(2:5kg) Provioled | miR |
| | IS marking | 101 market | Provided | " mil |
| | First-Aid Hose Reels. | and description of the second | | |
| | Total numbers on each floor | | NIR | <i>k</i> |
| | • Length of hose reel hose | 20 | 1 | 11 |
| | Nozzle diameter | 30 m 5 mm | | |
| - | Automatic fire detection and alarming s | N/A | | |
| | Type of detectors |] | NIB | |
| | Location of Main Panel | | 747- | |
| | • Location of Repeater Panel | | | |
| | | | | v |
| | Alternate source of power | | | |
| - | Hooters' Location | | | |
| | MOEFA | | NIR | |
| | Public Address System. | | NIR | The state of the s |
| | Automatic Sprinkler System. | | 747 | |
| | • Basement | · · · · · · · · · · · · · · · · · · · | NIR | |
| | Upper Floor | | | |
| | Sprinkler above false ceiling | | | : |
| | Internal Hydrants | NAME OF TAXABLE PARTY O | | |
| | Size of riser/down-comer | | NIR | ¥ |
| | Number of hydrants per floor | | 7 7 7 7 | |
| | Hose Box | | | 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 |
| | Yard Hydrants. | The second secon | | |
| | Total number of hydrants | | NIR | |
| | • Hose Box | | | 1 1 1 |
| | Pumping Arrangements. | | | |
| | Ground Level | and post because the state of t | NIR | |
| | Discharge of main Pump | The second secon | 4 4 /01 | |
| 1 | > Head of Main pump | , ma uses articles recognision of participations of as 4 and among a | | |
| | Number of main pumps | ners and configurational descriptions and a first spine is | | |
| | > Jockey Pump out put | | | *: |
| | > Jockey pump head | | | |
| - | > Standby Pump out put | the time and the state of the s | | • |
| - | > Standby Pump Head | and the amountained and an arrangement of the first base for | | |
| | > Auto Starting/ Manual | 2 | | |
| | stopping > Pump House Access | | | |
| | Terrace level | the state and st | | |
| - | Discharge of pump | ter tilg viden enterseringstadere forestelligenhaving. To 1 fine filter bree | | |
| | Head of the pumpPower Supply | The second secon | | |
| | Power Supply | | | |

| | | and the |
|-------|-----|---------|
| _ | | |
| - 8 1 | 100 | Texas. |
| 644 | 330 | 28 |

| 14 | Captive Water Storage for fire fighting. | | 0 | · · | | |
|----|--|---------------------------------------|-----|------|--|--|
| | Underground tank capacity | | NIK | | | |
| | Draw-off connection | | | | | |
| | > Fire service inlet | | | A*** | | |
| | > Access to tank | | | 4 | | |
| а, | Overhead Tank capacity | | | | | |
| 15 | Exit Signage. | | NIR | | | |
| 16 | Provision of Lifts. | | | | | |
| | Pressurization of Lift Shaft | | NIN | | | |
| | Pressurization of Lift lobby | 27 | | * | | |
| | Communication In lift Car | | | | | |
| | Fireman's Grounding Switch | в. | | | | |
| | • Lift Signage | | | | | |
| 17 | Standby power supply | | NIR | | | |
| 18 | Refuge Area. | | | | | |
| | ➢ Total Area | | NIB | | | |
| | > Location | | 1 | | | |
| 19 | Fire Control Room | | | | | |
| | Detector System Panel | | NIR | | | |
| | Flow Switch Panel | | | | | |
| | PA System Panel | · · · · · · · · · · · · · · · · · · · | | | | |
| | Batter backup | | a . | | | |
| | Building Floor Plans | | | | | |
| 20 | Special Fire Protection Systems for Protection of special Risks, if any: | | NiL | | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers....

Signature of the Inspecting Officer

Name

Designation

Signature of the Inspecting Officer 12/7/2013

Name (SHYAM LAL)

Designation Assitt. Divn officer