## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: cfohq.dlfire@nic.in, Tel:- 011-23414333

No. F6/DF5/ms/2013/6n/52/716

Dated: 16/08/13

## **FIRE SAFETY CERTIFICATE**

Certified that Subham Palace guest house located at 330/A/3, Madanpur Khadar, opp. Poket-E, Sarita Vihar, New Delhi comprised of ground floor (Reception + 05 guest rooms), first floor (store room + 05 guest rooms), second floor (store room + 05 guest rooms) & third floor (08 guest rooms) was granted NOC by this department vide letter No. F.6/DFS/MS/GH/2010/2061 dated 13-07-2010. The premises was re-inspected by the officer concerned of this department on 02-08-2013 in the presence of Mr. Akash, manager of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class residential (guest house) with effect from 16/08/17 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules, 2010.

Issued on 16/8/13 at New Delhi by.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

2. The Manager, Shubam guest house, 330/A/3, Madanpur Khadar, opp. Poket-E, Sarita Vihar, New Delhi.

## Conditions for the validity of fire safety certificate

a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.

b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.

c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.

d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

## **INSPECTION REPORT**

1. Name & address of the building: Shubham Palace Guest House, located at 330/A/3, Madanpur

Khadar, opp. Pocket-E, Sarita Vihar New Delhi-110076.

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : Letter No. F.6/DFS/MS/GH/2010/2061 Dated: 13.07.2010

5. Fire Safety directives letter No: Nil

6. Date of inspection : 02-08-2013

7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(M.Rd)

8. Name and designation of officers

from the building side : Mr. Akash, Manager

9. Year of Construction : 1996

10. Applicant's letter No. : 25270/Addl. C.P/Lic.(H) dated 29.05.13.

Guest House is comprised of ground floor (Reception + 05 guest rooms), first floor (store room + 05

guest rooms), second floor (store room + 05 guest rooms) & third floor (08 guest rooms)

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC/BBL Requirement	Provided at site	Remarks MR/NMR
1	Access to building			
	Road width	06 mts	More than 06 mts	MR
	• Gate width		Directly accessible from the Road	MR
	Width of internal road	N/A	N/A	N/A
2	Number, Width, Type & Arrangement of	of Exits		
	a. Number of staircases	-	-	-
	Upper Floors	02	02	MR
	Basements	N/A	N/A	N/A
	b. Width of staircases		-	
	Upper Floors	1.25, 1.0 mts	Provided	MR
	Basements	N/A	N/A	N/A
	c. Protection of exits	N/A	N/A	N/A
	Fire check door	N/A	N/A	N/A
	<ul> <li>Pressurization</li> </ul>	N/A	N/A	N/A
	e. No. of continuous staircases to terrace	01	01	MR
	g. Width of Corridor	N/A	N/A	N/A
	h. Door Size	N/A	N/A	N/A



N	0
1	7

3	Compartmentation.			4 E		
	Fire check door	N/A	N/A	N/A		
	<ul> <li>Sealing of electrical shafts</li> </ul>	N/A	N/A	N/A		
	• Fire Rating of shaft door	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.		, a	# # # # # # # # # # # # # # # # # # #		
	Basements	30 a/c per hour	N/A	N/A		
	Upper floors	12 a/c per hour	Provided	MR		
5	Fire Extinguishers	1711				
	Total numbers	08	Provided	MR		
	• Types	ABC	Provided	MR		
	IS marking	ISI marked	Provided	MR		
6	First-Aid Hose Reels.	,		# ************************************		
	Total numbers on each floor	01	Provided	MR		
	• Length of hose reel hose	30 m	Provided	MR		
KI 6	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming system.					
	Type of detectors	N/A	N/A	N/A		
	Location of Main Panel	N/A	N/A	N/A		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	N/A	N/A	N/A		
6	Hooters' Location	N/A	N/A	N/A		
3	MOEFA	Required	Provided	MR		
	Public Address System.	Required	Provided	MR		
0	Automatic Sprinkler System.	,		a <sup>3</sup>		
	• Basement	N/A	N/A	N/A		
# ## ## ## ## ## ## ## ## ## ## ## ## #	• Upper Floor	N/A	N/A	N/A		
E E	Sprinkler above false ceiling	N/A	N/A	N/A		
1	Internal Hydrants			a .		
	Size of riser/down-comer	N/A	N/A	N/A		



7		MIO		8 0 8		
	Hose Box	N/A	N/A	N/A		
12	Yard Hydrants.					
	<ul> <li>Total number of hydrants</li> </ul>	N/A	N/A	N/A		
19	Hose Box	N/A	N/A	N/A		
13	Pumping Arrangements.					
	Ground Level		" . <del>-</del> "			
	Discharge of main Pump	N/A	N/A	N/A		
W	➤ Head of Main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
2	Jockey Pump out put	N/A	N/A	N/A		
N E	> Jockey pump head	N/A	N/A	N/A		
49 H 15	> Standby Pump out put	N/A	N/A	N/A		
a sid	Standby Pump Head	N/A	N/A	N/A		
28 21 20	➤ Auto Starting/ Manual	N/A	N/A	N/A		
	stopping	N/A	N/A	N/A		
	<ul><li>Pump House Access</li><li>Terrace level</li></ul>	N/A	N/A	N/A		
	<ul><li>Discharge of pump</li></ul>	225 LPM	Provided	MR		
	Head of the pump	30 mt	Provided	MR		
6	> Power Supply	Required	Provided			
	➤ Auto Starting of pump	Required	provided	MR MR		
14	Captive Water Storage for fire fighting.			IVIIX		
8 8	Underground tank capacity	N/A	N/A	N/A		
2	Draw-off connection	N/A	N/A	N/A		
	Fire service inlet	N/A	N/A	N/A		
	> Access to tank	N/A	N/A	N/A		
	Overhead Tank capacity	5, 000 liters	Provided	MR		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.	ovision of Lifts.				
- a	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of Lift lobby	N/A	N/A	N/A		
	Communication In lift Car	N/A	N/A	N/A		



	•	N)U		
	Fireman's Grounding Switch	N/A	N/A	N/A
	Lift Signage	N/A	N/A	N/A
17	Standby power supply	Required	Provided (D.G 7KVA)	MR
18	Refuge Area.	8 8 8 E		
	> Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19	Fire Control Room			2 X
	Detector System Panel	N/A	N/A	N/A
794	<ul> <li>Flow Switch Panel</li> </ul>	N/A	N/A	N/A
	<ul> <li>PA System Panel</li> </ul>	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
	<ul> <li>Building Floor Plans</li> </ul>	N/A	N/A	N/A
20 5	Special Fire Protection Systems for Protection of special Risks, if any:	Required	01 CO <sub>2</sub> type fire extinguishers found provided near elect. panel	MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

20(57)

148/13

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY

Designation: - Asstt. Div. Officer (M.Rd)