GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DLEHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2013/ \$ 10

Dated: 26/8/17

FIRE SAFETY CERTIFICATE

Certified that the Guest House Amrapali Grand located at 2/16, East Patel Nagar, New Delhi-110008 comprised of Basement, ground floor plus three upper floors, using basement as Hall/Storage, ground floor as reception, lobby, kitchen, hall and office, first, second & third floor each having 12 guest rooms respectively (Total 36 guest rooms) was issued NOC by this department vide letter No.F.6/MS/DFS/GH/2006/140 dated 16.01.2006 owned/occupied by Sh. Harvinder Singh. The guest house building was re-inspected by the officer concerned of this department on 17.08.2013 in the presence of Sh. Harvinder Singh (Owner) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on $\frac{26/8}{13}$ at New Delhi.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

The Addl. Commissioner of Police (Lic.) 1st floor, P.S., Defence Colony, New Delhi. (Re. No.40938-42/Addl. C.P./Lic.(H), Dated 07.08.2013)

2. Sh. Harvinder Singh (Owner), Guest House Amrapali Grand, 2/16, East Patel Nagar, New Delhi-110008. Following fire safety directives must be adhered to –

1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.

3. The trained staff should be available round the clock.

4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.

5. The basement shall be used strictly as per the provisions of the Building Bye

Laws, 1983.

6. The certificate may not be treated in any case for regularization of unauthorized

construction, if any.

7. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

	INSPEC	TION REPORT				
	1. Name & address of the building:	Amaga bal' 6	1 9/10 0	1		
	1. Name & address of the building: 2. Type of Occupancy:	Parison line (sand, 2/16, Eas	st Padel Nagar, N		
	3. Type of Case	Residential (Gruest House) New Case/Renewal Letter No. F. 6/ms/DFS/GH/2006/140 Date 16.01.200				
	4. Details of Previous NOC					
	5. Fire Safety directives letter No :	2000 10./16/19	S/DFS/GH/2006/19	o Date 16.01.20		
	Date of inspection	11	7 00 2.10			
	7. Name of Inspecting Officer	17.08.2013				
	8. Name and designation of officers	rs A.D.O P.S. Dahiya				
	From the building side			A		
	9. Year of Construction	Rodans	Cinder Singh (C	(wher)		
	10. Applicant's letter No.	Before 2000 - 2081 10938-42/Addl. C.P./LIC. (H) dated 07.08.1				
	Minimum Standards on fire	NBC/BBL	1, L, P, 1/L1C, (H)	duted 07.08.1		
0.	prevention and fire safety U/R 33	Requirement	Provided at	Remarks		
	Access to building	[wedan ement	site	MR/NMR		
	Road width	Accessible	14.1	:		
	• Gate width	TICCOSTOTE	12 mtr	MR		
	Width of internal road	-	112 cms Each	MR (029a		
-	Number Width Type 8 A			_		
	Number, Width, Type & Arrangement a. Number of staircases	of Exits				
	• Upper Floors					
	1 11	Two	Two	MR		
	Basements Width of staircases	-do-	-do-	MR		
	1 11					
	Upper Floor	-	125cms, 76cms	MR Cold Ca,		
	• Basements	-	117cms, 105cms	- do -		
	c. Protection of exits		11 / CITY, 103 CITY	~ ~ ~		
	Fire check door					
	• pressurization					
	d. No. of continuous staircases to					
	terrace		One			
	e. Width of Corridor					
	f. Door Size		146 cmp			
3.			87 cm & x 198 cms	¥		
	Compartmentation	1	/			
	Fire check door					
	 Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 					
		-	Sealed	-		
			Management .	_		
	Smoke Management System					
	• Basements		Exhaust Fans	h = 0		
	Upper floors		are Provided	MR		
		<u> </u>	latural Ventilation	MR		

	N/14			1
		12 a/c per hour		
5.	Fine F. Air ' I			1
Э.	Fire Extinguishers	Four at each floor		
9	• Total numbers	Co, WCo, ABC	Provided	MR
	• Types		- do -	MR
6.	• IS marking	ISI marked	1SI Marked	MR
0.	First-Aid Hose Reels			
	Total numbers on each floor	_One	Provided	MR
	Length of hose reel hose	30 m	- do -	MR
-	Nozzle diameter	5 mm	-do:-	MR
7.	Automatic fire detection and alarming	system		
	Type of detectors	•		
	 Location of Main Panel 	-	-	
	 Location of Repeater Panel 	-		4
	 Alternate source of power 	-	D. G. Set of 125 KVA	
	 Hooters' Location 	_		
8.	MOEFA	Required	Provided	MR
9.	Public Address System	- do -	- do -	MR
10.	Automatic Sprinkler System		1 1	
	 Basement 	Required	Provided	MR
	Upper Floor	-		
	 Sprinkler above false ceiling 		1 1	
11.	Internal Hydrants		4	2 · · · · · · · · · · · · · · · · · · ·
	 Size of riser/down-comer 	-	100 M·M	MR
	 Number of hydrants per floor 	-	Ohe	MR
	Hose Box	-	-do-	INDR
12.	Yard Hydrants		J	-1 //
	 Total number of hydrants 	•		
	 Hose Box 			
13.	Pumping Arrangements	- 2		3 0 Va V
	 Ground Level 		-	a Land
	Discharge of main Pump		-	
-	Head of Main pump			
	Number of main pumps			
	Jockey Pump out put	-		-
	Jockey pump head			
	> Standby Pump out put		4	
	> Standby Pump Head			
	Auto Starting/Manual		i	
	stopping			
i	The second state of the se			

2/16, East Patel Magar, New Delli-110008.

		· · · · · · · · · · · · · · · · · · ·		\$.
V.	Pump House Access	-	1	
	Terrace level			
	Discharge of pump	~	450 LPM	MR Cold Co
	Head of the pump			-do -
	Power Supply	Required	30 M Provided	MR.
	Auto Starting of pump			
14.	Captive Water Storage for fire fighting			!
	 Underground tank capacity 			
	Draw-off connection	-	_	1
	> Fire service inlet	-	Provided	MR
	Access to tank		7 55 . 101201	
	Overhead Tank capacity		10000 Ctr	MR (old)
	,	0 1		
15.	Exit Signage.	Required	Provided	MR
±3,	Exit Signage.			2
16.	Provision of Lifts.		·	
	Pressurization of Lift Shaft	-		
	 Pressurization of Lift lobby 			
	Communication In lift Car		0 1 1	h - 0
	• * Fireman's Grounding Switch		Provided	MR
	Lift Signage	Regileired	-do-	MR
	• Lift Signage	Required do-	-do -	MR
		Required	Provided	MR
17.	Standby power supply	V		
18.	Refuge Area.			
	> Total Area	e o	- *	_
	> Location		The state of the s	9
19.	Fire Control Room	£ ,		
	Detector System Panel	_		_
	Flow Switch Panel	1		
	PA System Panel			
	Batter backup	0	0- 11-1	100
-	Building Floor Plans	required	Provided	MR
			-	
20.	Special Fire Protection System for Protection of special Risks, if any:		_	-

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the above substantial compliance of the minimum standards on fire prevention and Fire Safety measures required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial

Note: - The Guest House building is comprised of basement, Ground Floor plus three upper floors. The basement is served by two staircases having width 117cms & 105cms respectively. The lepper floors are served by two staircases having width 125cms & 75cms respectively. The Guest House building issued NOC by this department viole letter No. F.6 [MS]DFS] Cit | 2006 | 140 dated 16.01. 2006 for 38 Guest Rooms. The FSC is recommended for 36 Guest Rooms as per Addi. C.P Letter No. 40938-42 | Addi. C.P/Lic.CH) dated 07.08.2013.

Designation ASSH. Divisional Officer

Dy. CAO (South)

971313

Signature of Inspecting Officer

Name

Designation

