GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

Ph - 23414333 Fax - 23412593 Email - cfohq.dlfire@nic.in

No. F6/DF5/ms/2013/ NO2/839

Dated: 03 | 09 /13

FIRE SAFETY CERTIFICATE

(Dr. G.C. Misra)
Chief Fire Officer
Delhi Fire Service

To

Mr. Satpal Singh

City Palace (Banquet Hall), 447, Jheel Khurenja, Delhi-51.

Copy to-

The Dy. Health Officer,

MCD Health Department,

Shahdara (South) Zone, 5th Floor, Karkardooma, Shahdara, Delhi

CONDITIONS:

- 1. All the means of escape shall be kept free of all the type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 5. This Fire Safety Certificate can not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building : City Palace (Banquet Hall), 447, Jheel Khurenja, Delhi-51.

2. Building is comprised of

: G+1

3. Type of Occupancy

: Assembly (Banquet Hall)

4. Type of Case

: New Case

5. Details of Previous NOC

: Nil

6. Fire Safety direction letter No

: F6/DFS/MS/BP/2013/1622 dated 18.06.13

7. Date of Inspection

: 17.07.13

8. Name of the Inspecting Officers: : Suresh singh (ADO)

9. Name of the designation of Officer

from the building side

: Mr. Satpal Singh, Owner

10. Year of Construction

11. Applicant's letter No.

: DHO/Shd. (S) Zone/2013/1391 dated 12.06.13

| 11. Ap | oplicant's letter No : DHO/Shd. | (S) Zone/2013/1391 d | ated 12.06.13 | | |
|--------|---|----------------------|------------------|----------------|--|
| S.No | Minimum Standards on fire prevention | Requirement/NBC | Provided at Site | Remarks MR/NMR | |
| | and fire safety U/R33 | | | | |
| 1 | Access to building | Required | Provided | MR | |
| | Road width | 6 m | 17 m | MR | |
| | Gate width | N.A. | N.A. | N.A. | |
| | Width of internal road | N.A. | N.A. | N.A. | |
| 2 | Number, Width, Type and Arrangement of Exits Required Provided MR | | | | |
| | a. Number of Staircases | 2 no. | 02 no. | MR | |
| | Upper Floor | 2 no. | 02 no. | MR | |
| | Basement | N.A. | N.A. | N.A. | |
| | b. Width of Staircases | 1.5 m | 2 m, 1.65 m | MR | |
| | Upper Floor | 1.5 m | 2 m, 1.65 m | MR | |
| | Basement | N.A. | N.A. | N.A. | |
| | c. Protection of exits | | Y x z z | | |
| | Fire check door | 2hr rating | Provided | MR | |
| | Pressurization | N.A. | N.A. | N.A. | |
| | e. No. of continuous staircases to terrace | 01 no. | Provided | MR | |
| | g. Width of Corridor | N.A. | N.A. | N.A. | |
| | h. Door Size | 2 m | 2 m, 2 m | MR | |
| 3 | Compartmentation. | Required | Provided | MR | |
| | Fire check door | Required | Provided | MR | |
| | Sealing of electrical shafts | N.A. | N.A. | N.A. | |
| | Fire rating of shaft door | N.A. | N.A. | N.A. | |
| | Water curtain | N.A. | N.A. | N.A. | |
| | Fire Dampers | N.A. | N.A. | N.A. | |
| 4 | Smoke Management System. | Ventilated | | | |
| | Basement | 30a/c per hour | N.A. | N.A. | |
| | Upper floor | 12 a/c per hour | N.A. | N.A. | |
| | | 1 | 1 | | |



IRNe/ 10

| 5. | Fire Extinguisher | Required | Provided | MR |
|----|--|------------|------------|------|
| P | Total numbers | 06 no. | 06 no. | MR |
| | types | Co2 & ABC | Co2 & ABC | MR |
| | IS marking | ISI marked | ISI marked | MR |
| 6 | First-aid-Hose Reels. | Required | Provided | MR |
| | Total numbers of each floor | 1 no. | 1 no. | MR |
| | Length of hose reel hose | 30 m | 30 m | MR |
| | Nozzle diameter | 5 mm | 5 mm | MR |
| 7 | Automatic fire detection and alarming system. N.A. | | N.A. | N.A. |
| | Type of detectors | N.A. | N.A. | N.A. |
| | Location of main panel | N.A. | N.A. | N.A. |
| | Location of repeater panel | N.A. | N.A. | N.A. |
| | Alternate source of power | N.A. | N.A. | N.A. |
| | Hooters's location | N.A. | N.A. | N.A. |
| 8 | MOEFA | Required | Provided | MR |
| 9 | Public address System. | N.A. | N.A. | N.A. |
| 10 | Automatic Sprinkler System. | N.A. | N.A. | N.A. |
| | basement | N.A. | N.A. | N.A. |
| | upper floor | N.A. | N.A. | N.A. |
| | sprinkler above false ceiling | N.A. | N.A. | N.A. |
| 11 | Internal Hydrants | Required | Provided | MR |
| | size of riser/down-comer | 100 mm | 100 mm | MR |
| | Number of hydrants of each floor | 1 no. | 01 no. | MR |
| | Hose Box | 01 no. | 01 no. | MR |
| 12 | Yard Hydrants. | N.A. | N.A. | N.A. |
| | Total number of hydrants | N.A. | N.A. | N.A. |
| | Hose Box | N.A. | N.A. | N.A. |
| 13 | Pumping Arrangements. | Required | Provided | MR |
| | Ground Level | N.A. | N.A. | N.A. |
| | Discharge of main Pump | N.A. | N.A. | N.A. |
| | Head of Main Pump | N.A. | N.A. | N.A. |
| | Number of main pumps | N.A. | N.A. | N.A. |
| | Jockey pump out put | N.A. | N.A. | N.A. |
| | Jockey pump head | N.A. | N.A. | N.A. |
| | Standby pump out put | N.A. | N.A. | N.A. |
| | Standby pump Head | N.A. | N.A. | N.A. |
| | Auto Starting /Manual stopping | N.A. | N.A. | N.A. |
| | Pump House Access | N.A. | N.A. | N.A. |
| | Terrace Level | | | |
| | Discharge of pump | 900 LPM | 900 LPM | MR |
| | > Head of the Pump | 40 m | 40 m | MR |
| | Power supply | N.A. | N.A. | N.A. |
| | Auto Starting of pump | N.A. | N.A. | N.A. |

TRN /11

City Palace (Banquet Hall), 447, Jheel Khurenja, Delhi-51.

| 14 | Captive Water Storage for Fire Fighting. | Required | Provided | MR |
|----|--|---------------|-----------------------|------|
| | Underground tank capacity | N.A. | N.A. | N.A. |
| | Draw-off connection | N.A. | N.A. | N.A. |
| | Fire service inlet | N.A. | N.A. | N.A. |
| | Access to tank | N.A. | N.A. | N.A. |
| | Overhead Tank capacity | 15,000 Liters | 15,000 Liters | MR |
| 15 | Exit Signage. | Required | Provided | MR - |
| 16 | Provision of Lifts. | N.A. | N.A. | N.A. |
| | Pressurization of Lift Shaft | N.A. | N.A. | N.A. |
| | Pressurization of Lift lobby | N.A. | N.A. | N.A. |
| | Communication in lift car | N.A. | N.A. | N.A. |
| | Firemen's grounding switch | N.A. | N.A. | N.A. |
| | Lift Signage | N.A. | N.A. | N.A. |
| 17 | Standby power supply | Required | 62 KVA Genrator | MR |
| | | | Provided - | |
| 18 | Refuge Area. | N.A. | N.A. | N.A. |
| | Total area | N.A. | N.A. | N.A. |
| | Location | N.A. | N.A. | N.A. |
| 19 | Fire Control Room | N.A. | N.A. | N.A. |
| | Detector system panel | N.A. | N.A. | N.A. |
| | Flow switch panel | N.A. | N.A. | N.A. |
| | PA system panel | N.A. | N.A. | N.A. |
| | Batter backup | N.A. | N.A. | N.A. |
| | Building Floor Plans | N.A. | N.A. | N.A. |
| 20 | Special Fire Protection systems for | Description | CO ₂ local | MR |
| | protection of special Risks, if any: | Required | application in | 3 |
| | | | electrical pannel | |
| | | | provided | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer

Name

Suresh Singh

Designation

ADO (Shah)

10