## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

Fax:- 011-23412593

E-mail ID: cfohq.dlfire@nic.in

No F 6/DFS/MS/GH/2013/NO2/941

Dated 20/08/13

## **FIRE SAFETY CERTIFICATE**

Certified that **B. B. Palace at 2638-42, Bank Street Karol Bagh New Delhi** comprised of ground floor (reception + office + Shops), 1<sup>st</sup> floor (11 guest rooms), 2<sup>nd</sup> floor (02 guest rooms and others property), 3<sup>rd</sup> floor (11 guest rooms), 4<sup>th</sup> floor (02 office rooms + 2 staff rooms) and terrace having 01 staff room sealed with brick wall by MCD, total 24 guest rooms was granted NOC by this department vide letter No. F6/DFS/MS/GH/2010/2179 dated 23-07-2010. The premises was re-inspected by the officer concerned of this department on 02-09-2013 in the presence of Mr. Nitin (Front Manager) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy of 24 guest rooms with effect from 22-1-2-1-12 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Dr G. C Misra) Chief Fire officer Delhi Fire Service Ph – 011-23414333

of c Mc

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi -110049 w.r.t. letter No. 42668-69/Joint.C.P./Lic(H) New Delhi 26-08-2013.
- 2. B. B. Palace at 2638-42, Bank Street Karol Bagh New Delhi.
- 3. Deputy Commissioner (MCD). Sadar Pahar ganj zone : with a request to get measure the height of building and intimate this deptt.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

N/2)

## **INSPECTION REPORT**

1. Name & address of the building :

B.B. Palace 2638-42 Bank Street Karol Bagh New Delhi.

2. Type of Occupancy

Residential Guest house (B+Gr.+5 floor)

3. Type of Case

RENEWAL

4. Details of previous NOC

F6/DFS/MS/GH/2010/2179 Date 23/07/2010

5. Fire Safety directives Letter No.

NA

6. Date of inspection

02-09-2013

7. Name of the Inspecting Officer

: M.K. Sharma (A.D.O.)

8. Name and designation of Officer

from the building side

: Mr. Nitin (Front Manager) 9711439987

9. Year of Construction

: 1998

10. Applicant's letter No.

: 42668-69/Joint.Cp.Lic(H) dated 26-08-2013

S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requirements	Provided at site (PSS Area)	Remarks MR/NMR	
1.	Access of building	rtoquirements	(F33 Area)	(P.S.S Area)	
	<ul> <li>Road width</li> </ul>	NA	15 mtrs	MD	
	<ul> <li>Gate width</li> </ul>	NA	1.5 mtr	MR	
	<ul> <li>Width of internal road</li> </ul>	N/A	N/A	N/A	
				IV/A	
2.	Number, width, Type & Arrangements of exits				
	a. Number of staircases	01	Р	MR	
	<ul> <li>Upper floors</li> </ul>	01	P	MR	
	<ul> <li>Basements sealed</li> </ul>	N/A	N/A	N/A	
	b. Width of staircases	. 8 mt	1120 cm to 11 Tours MR		
	<ul> <li>Upper floors</li> </ul>	01	P	MR	
	<ul> <li>Basements sealed</li> </ul>	-	-	IVITY	
	c. Protection of exits	N/A	N/A	 N/A	
	<ul> <li>Fire check door</li> </ul>	N/A	N/A	N/A	
	<ul> <li>Pressurization</li> </ul>	N/A	N/A	N/A	
	d. No of continuous staircase	01	P	MR	
	to terrace		•	IVIT	
	e. Width Of Corridor	1 mt	1200 mm	MR	
	f. Door Size	NA	NA	N/A	
	Compartmentation			IN//\	
	Fire check door	N/A	N/A	N/A	
	<ul> <li>Sealing of electrical shafts</li> </ul>	N/A	N/A	N/A	
	<ul> <li>Fire Rating of shaft door</li> </ul>	N/A	N/A	N/A	
	Water Curtain	N/A	N/A	N/A	

K1122

· T	Eiro Domners	N/A	N/A	N/A
	Fire Dampers     Smoke managements System			
	-	30 ACPH	NA	NA
		N/A	NATURAL	MR
	• Upper floors			
	Fire Extinguishers	20	Р	MR
	<ul> <li>Total numbers 12</li> </ul>	A.B.C. Co <sub>2</sub> ,		MR
	<ul> <li>Types</li> </ul>	W.Co <sub>2</sub>	Р	
		VV.002	·	MR
	<ul> <li>IS marking</li> </ul>	Yes	Р	
	First – Aid Hose Reels			
i		01	Р	MR
	Total numbers on each floor	01		
	1 Attend floor	30 Mt	Р	MR
	<ul> <li>Length of hose reel hose</li> </ul>	5 mm	P	MR
	<ul> <li>Nozzle diameter</li> </ul>			
	Automatic fire detection and alarming	g system	NI/A	N/A
	<ul> <li>Type of detectors</li> </ul>	N/A	N/A	N/A
	<ul> <li>Location of Main Panel</li> </ul>	N/A	N/A	N/A
	<ul> <li>Location of Repeater Panel</li> </ul>	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
		N/A	N/A	14//-4
V	STORY STORY	NR	Р	MR
8.	MOEFA	NR	Р	MR
).	Public Address System Automatic Sprinkler System	TALL		
0.		N/A	N/A	N/A
	Basements sealed	N/A	N/A	N/A
	Upper Floor	NI/A	N/A	N/A
	<ul> <li>Sprinkler above false ceiling</li> </ul>	1077		
11.	Internal Hydrants	D1/A	N/A	N/A
	<ul> <li>Size of riser/down-comer</li> </ul>	N/A	N/A N/A	N/A
	<ul> <li>Number of hydrants per</li> </ul>	N/A		N/A
	floor	N/A	N/A	14// (
	Hose Box			· · · · · · · · · · · · · · · · · · ·
12.	Yard Hydrants			
14.	Total number of hydrants	N/A	N/A	N/A
40	Hose Box	N/A	N/A	N/A
				<u> </u>
13.	Pumping Arrangements  • Ground Level			
	00 00 00 00 00 00 00 00 00 00 00 00 00	N/A	N/A	N/A
	<ul><li>Discharge of main pump</li><li>Head of main pump</li></ul>	N/A	N/A	N/A
		N/A	N/A	N/A
	Number of main pumps  Leabour pump out put	N/A	N/A	N/A
	Jockey pump out put  Lealers nump bond	N/A	N/A	N/A
	Jockey pump head     Property put	N/A	N/A	N/A
	Standby Pump out put  Standby Pump Head	N/A	N/A	N/A
	Standby Pump Head	N1/A	N/A	N/A
	auto Staring/Manual stopping	N/A	N/A	N/A
	Pump House Access	14// \		
	Terrace level	450 lpm	Р	MR
	<ul> <li>Discharge of pump</li> </ul>	30 mt	P	MR
	<ul> <li>Head of the pump</li> </ul>	YES	Р	MR
	<ul> <li>Power supply</li> </ul>	120		

	Auto starting of pump	NA	NA	NA	
14.	Captive water Storage for fire fighting				
	Under ground tank capacity	N/A	N/A	N/A	
	Draw off connection	N/A	N/P	N/A	
	Fire service inlet	N/A	Р	N/A	
	<ul> <li>Access to tank</li> </ul>	YES	P	MR	
10	Overhead Tank capacity	(2500)	Р	MR	
15	Exit Signage	R	N	MR	
16.	Provision of Lifts				
	<ul> <li>Pressurization of Lift Shaft</li> </ul>	N/A	N/A	N/A	
	Pressurization of lift lobby	N/A	N/A	N/A	
	<ul> <li>Communication in lift Car</li> </ul>	YES	Р	MR	
	<ul> <li>Fireman's Grounding</li> </ul>	YES	Р	MR	
	Switch	YES	P	MR	
	Lift Signage				
17.	Standby power supply	NR	125 KVA	MR	
18.	Refuge Area				
	Total area	N/A	N/A	N/A	
	<ul> <li>Location</li> </ul>	N/A	N/A	N/A	
19.	Fire control room				
	<ul> <li>Detector system panel</li> </ul>	N/A	N/A	N/A	
	<ul> <li>Flow Switch Panel</li> </ul>	N/A	N/A	N/A	
	<ul> <li>PA System Panel</li> </ul>	N/A	N/A	N/A	
	Batter backup	N/A	N/A	N/A	
	Building Floor Plans	N/A	N/A	N/A	
20.	Special Fire Protection Systems for	R	One ABC, type	MR <sup>7</sup>	
	Protection of special Risks, if any;		F E. provided		

The fire protection systems provided in the building were tested checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules 35 of the Delhi Fire Service Rules 2010. fire safety certificate in recommended, Basement and 5<sup>th</sup> floor is sealed by MCD: No- LPG shall be used at upper floors.

Do((1)) submitted please -

Signature of the Inspecting Office

Name :- M.K. Sharma Designation :- A. D.O. (C.C.)