GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS : DELHI FIRE SERVICE : NEW DELHI - 110001

No 156/DF3/MS/GN/2015/52/989

DATED 30/09/2017

FIRE SAFETY CERTIFICATE

Certified that the Hotel AAVA Surya Continental lacated at J-14, community Centre, Rajouri Garden, New Delhi-110027 comprised of Basement, Ground plus three upper floors having Restaurant, Banquet Hall & 20 Guest Rooms(second floor having 07 guest rooms, third floor having 13 guest rooms) was issued NOC by this department vide letter NO. F.6/DFS/MS/GH/2009/271 dated 02.02.2009 owned/occupied by Sh. Samir Nawalgaria. The hotel was reinspected by the officer concerned of this department on 17.09.2013 in the presence of Sh. Deepak Aggarwal (Project Head) and found that the management of hotel have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules ,2010 and that the building /premises is fit for occupancy class-A Sub Div A-5 with effect from 2.9/09/1/2. for a period of three years in accordance with 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 30/09/2013 at New Delhi

(Dr.G.C.Misra) Chief Fire Officer Delhi Fire Service Tel:- 011-23414333

E-Mail:- cfohq.dlfire@nic.in

Copy to:-

The Joint Commissioner of Police(Lic.)
 !st floor,P.S.,Defence Colony,New Delhi
 (RE.No.41961/Addl.C.P./Lic.(h),20.08.2013)

2. Sh. Samir Nawalgaria(Owner),
Hotel AAVA Surya Continental,
J-14, Community Centre, Rajouri Garden, N.D.-27

Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

	The state of the s	The second secon						
	1. Namo & add	INSPEC	TION REPORT					
-	2. Type of Occurs of the							
	3. Type of Case	•	Residential (A-5)					
	4. Details of Previous No		New Case/Rene	ewal	5 NV -27			
	5. Fire Safety Hispania	JC :	Letter No. F6	DESIME KH bomal	271 Data calcala			
	5. Fire Safety directives6. Date of inspection	letter No :	F6/DFS/MS	93/808	211 Date 02 02 0			
* 8	7. Name of Inspecting O	:	17/09/2013		Ni			
	8. Name and doctor	fficer :	Dycfo (52) Atul	Garg and AD				
	8. Name and designation From the building side	of officers	J	and AD	o sandeep Dugga			
	9. Year of Construction		Mr Deebak	Aggarwal (P)	Charle Land			
	10. Applicant's letter No.	•			yell nead)			
S.	Minimum Standards on fire	41961 - 66	Jt.C.P/Lic (H)	dated 20-0	8-2013			
No.	prevention and fire safety	2	NBC	Provided at	Remarks			
1.	Access to building	J/R 33	Requirement	site	MR/NMR			
96					T MINIMINIK			
	Road width		Accessible	12 mtg	140			
	• Gate width		_		MR			
2.	• Width of internal roa	iq		07mtn 407mm	MR			
۷.	Number, Width, Type & Arr	angement o	of Exits					
	or staircases			T				
	• Upper Floors			Ground to First -02 No	45			
	• Basements			First to Third = 01 No	MR (Being old ase			
	b. Width of staircases			Two Nous	MR			
	Upper Floor			GF to FF = 160 \$1240				
	• Basements		-	FF TOTF = 124 CMS	MR (Beingold			
	c. Protection of exits			160 £ 120 cms	MR (Being old)			
	Fire check door				V Cane			
	• pressurization							
	d. Not of continuous stairca	ses to						
	rerrace	}						
	e. Width of Corridor		-	01				
	f. Door Size			143 cms				
			-	And the second s				
3.	Compartmentation			77 × 200 cms				
	Fire check door				:			
	Sealing of electrical st	_ F:						
	Fire Rating of shaft do	ЗЛЬ		Sealed				
	• Water Curtain	or						
	Fire Dampers							
1. 5	Smoke Management System							
	• Basements		20 /					
	 Upper floors 		30 a/c per	ventilation through	1			
			hour	Natural ve wi) ahan	MR			

	N/VP	and the second	· *				
		12 a/c per					
1		hour		-			
5.	Fire Extinguist			0 0 0			
	Fire Extinguishers						
	• Total numbers	22 NO15	Provided	MR			
	Types	ABC CO2	- do	MR			
6.	IS marking First Aid III	ISI marked	151 marked	MX			
0.	First-Aid Hose Reels		- MINKEY	INIX			
	 Total numbers on each floor 	one	Provided	1 0			
,	 Length of hose reel hose 	30 m	- do	MR			
-	Nozzle diameter	5 mm	-do	MR			
7.	Automatic fire detection and alarming	system	7,0	MR			
	 Type of detectors 	Required	Ometer II La				
	 Location of Main Panel 	The square of	smoke defectors	MR			
	 Location of Repeater Panel 			-			
	 Alternate source of power 	Racional		1 + + -			
	 Hooters' Location 	Required	Provided	MR			
8.	MOEFA		Near Shaircase				
9.	Public Address System	Required	Provided	MR			
10.	Automatic Sprinkler System	Required	Provided	MR			
	• Basement						
4	• Upper Floor	Required	Provided	Me			
	 Sprinkler above false ceiling 		Provided				
11.	Internal Hydrants						
	Size of riser/down-comer		1				
	Number of hydrants per floor	100 mm	Provided	MR			
	Hose Box	one	one	Me			
12.	Yard Hydrants	one	one	MK			
	 Total number of hydrants 	T	j.				
	* Hose Box						
13.	Pumping Arrangements						
	Ground Level			S. Carrier			
			*	4			
	Discharge of main Pump Head of Main pump		1260 LPM	MR (Being old case)			
	rieda or walli pullip		58.5 mtm	do			
	Number of main pumpsJockey Pump out put		one	d=			
5	> Jockey pump head		360 LPM	-de-			
	Standby Pump out put	-	40 mhx	_1_			
	Standby Pump Head	•		- 600			
	> Auto Starting/Manual		· .				
-							
The second secon	stopping		Auto mode				

AAVA SURYA, J-14, Communing Centre, Rajouri Garden, New Delhi-140027.

1	Pump House Access	Required	frovided	MR
	Terrace level	<i>V</i>		
8 9	Discharge of pump		900 UM	MR Being
	Head of the pump		40 mm	Lood case
	Power Supply		40 MM	- 0
	Auto Starting of pump			
	,			<u> </u>
14.	Captive Water Storage for fire fighting			
	 Underground tank capacity 	50000 UM	SOUDD UM	MR Beingold
	Draw-off connection			Scare
	Fire service inlet			
	Access to tank		On id a	
	Overhead Tank capacity	•	Prided 2000 lm	MR Being old
			2000211	MR (Being old
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.		- 90	
	 Pressurization of Lift Shaft 		-	MR (Being old Cas
	 Pressurization of Lift lobby 			Till J cos
	Communication In lift Car	1	Provided	
	• * Fireman's Grounding Switch	0 0	rioviaeg	MR
	Lift Signage	Required	- do	MR
		Required	-do	MR
17.	Standby power supply	0 - 1	0	
-/.	Standby power suppry	Required	Provided	MR
18.	Refuge Area.			
	> Total Area		2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	
	Location			
			or Ty	
19.	Fire Control Room			
	Detector System Panel			
	Flow Switch Panel			
	PA System Panel		-	
	Batter backup			
	Building Floor Plans			
				# F
20.	Special Fire Protection System for Protection of special Risks, if any:			
		2 "	ş	8

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the above substantial compliance of the minimum standards on fire prevention and Fire Safety measures required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers....

Signature of Inspediting Officer

Designation Dy. C. Fo. (South zone)

Signature of Inspecting Officer

Name Sandeep Duggal
Designation Asst. Divisional Officer.