GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEADQUATERS: DELHI FIRE SERVICE: NEW DELHI-110001**

Fax: 23412593, E-mail: cfohq.dlfire@nic.in, Tel:- 011-23414333

NO.F6/DFS/MS/GH/2013/ <2 1006

Dated: 30/09/13

FIRE SAFETY CERTIFICATE

Certified that The Lazeez Guest House located at I-87, Central Market, Lajpat Nagar-II, New Delhi-110024 comprised of basement floor (storage-used by other party), ground floor (restaurant-used by other party), first floor (reception + 05 guest rooms), second floor (05 guest rooms) and third floor (owner's residence) have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi fire service Rules 2010 and verified by the officer concerned of Delhi fire service on 18.09.2013 in presence of Shri Devinder Sehgal and that the building/premises is fit for occupancy class residential (Guest house) with effect from ______ for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 300917 at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER **DELHI FIRE SERVICE** 90

Copy to: -

1. The Addl. C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

2. The Manager, M/s Lazeez Guest House, I-87, Central Market, Lajpat Nagar-II, New Delhi-110024.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: The Lazeez guest house, I-87, Lajpat Nagar-II, New Delhi-24.

2. Type of Occupancy

: Lodging House

3. Type of Case

: New case

: N/A

4. Details of previous NOC

5. Fire Safety directives letter No : Nil

6. Date of inspection

: 18-09-2013

7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(M.Rd)

8. Name and designation of officers

from the building side

: Mr. Devinder Sehgal

9. Year of Construction

: 2009

10. Applicant's letter No.

: Nil dated 04-09-2013

Basement Floor (Storage- for other party), Ground Floor (Restaurant- for other party), First Floor

(05 guest rooms), Second Floor (05 guest rooms), and Third Floor (owner's residence) Remarks Provided at site BBL Minimum Standards on fire S. MR/NMR prevention and fire safety U/R 33 Requirement No. Access to building 1 MR More than 06 mts. 06 mts Road width N/A Directly accessible 4.5 mts Gate width N/A N/A N/A Width of internal road Number, Width, Type & Arrangement of Exits 2 a. Number of staircases Provided MR 01 Upper Floors MR Provided 01 **Basements** b. Width of staircases 1.0 mt MR 1.0-1.05 mts Upper Floors 1.0 mt MR Provided **Basements** c. Protection of exits N/A Fire check door N/A N/A N/A Pressurization N/A N/A MR e. No. of continuous staircases to terrace 01 01 N/A g. Width of Corridor N/A N/A h. Door Size N/A N/A N/A 3 Compartmentation.

		MY	6 9			
-	• Fire check door	Required	Provided			
	Sealing of electrical shafts	Required	Provided	1		
-	• Fire Rating of shaft door	N/A		MA		
	Water Curtain	N/A	N/A N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.		IVA	N/A		
	• Basements	30 a/c per hour	Provided	8		
	Upper floors	12 a/c per hour	STOUGHER ST	MR		
5	Fire Extinguishers	1	Provided	MR		
	Total numbers	11				
	• Types	ABC, CO_2	Provided	MR		
	 IS marking 	ISI marked	Provided	MR		
6	First-Aid Hose Reels.	- saurited	Provided	MR		
	 Total numbers on each floor 	01				
	 Length of hose reel hose 	30 m	Provided	MR		
×	Nozzle diameter	5 mm	Provided	MR		
7			Provided	MR		
	Automatic fire detection and alarming system. • Type of detectors N/A N/A					
		N/A	N/A	N/A		
	Location of Main Panel	N/A	N/A	N/A		
	 Location of Repeater Panel 	N/A	N/A			
	Alternate source of power		IV/A	N/A		
	Hooters' Location	N/A	N/A	N/A		
2		N/A	N/A	N/A		
9	MOEFA	N/A	N/A	N/A		
	Public Address System.	Required	Provided			
)	Automatic Sprinkler System.					
	BasementUpper Floor	Required	Provided	MR		
	 Sprinkler above false ceiling 	N/A	N/A	N/A		
+		N/A	N/A	N/A		
+	Internal Hydrants		e e 5	0 8 9		
	Size of riser/down-comer Number of hydronta and G	N/A	N/A	N/A		
	Number of hydrants per floor	N/A	N/A	N/A		



		M8		
	Hose Box	N/A	N/A	N/A
2	Yard Hydrants.	3		
	 Total number of hydrants 	N/A	N/A	N/A
V	Hose Box	N/A	N/A	N/A
3	Pumping Arrangements.			
	Ground Level	-	-	, =
	Discharge of main Pump	N/A	N/A	N/A
	> Head of Main pump	N/A	N/A	N/A
	> Number of main pumps	· N/A	N/A	N/A
	Jockey Pump out put	N/A	N/A	N/A
	> Jockey pump head	N/A	N/A	N/A
	> Standby Pump out put	N/A	N/A	N/A
	> Standby Pump Head	N/A	N/A	N/A
	> Auto Starting/ Manual	N/A	N/A	N/A
	stopping > Pump House Access	N/A	N/A	N/A
		N/A	N/A	N/A
	Terrace level Discharge of nump	450 LPM	Provided	MR
	Discharge of pumpHead of the pump	40 mt	Provided	MR
	Power Supply	Required	Provided (125 KVA)	MR
	➤ Auto Starting of pump	Required	provided	MR
14	Captive Water Storage for fire fighting		g 2 2	
	YY 1 14-11	N/A	N/A	N/A
	 Underground tank capacity Draw-off connection 	N/A	N/A	N/A
	Fire service inlet	N/A	N/A	N/A
	Access to tank	N/A	N/A	N/A
	Overhead Tank capacity	10, 000 liters	Provided	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.	F		
it	Pressurization of Lift Shaft	N/A	N/A	N/A
	Pressurization of Lift lobby	N/A	N/A	N/A
	Communication In lift Car	N/A	N/A	N/A



. 11		Ms		B			
	Fireman's Grounding Switch	N/A	N/A	N/A			
	Lift Signage	N/A	N/A	N/A			
17	Standby power supply	Required	Provided (D.G Set)	MR			
18	Refuge Area.						
	> Total Area	· N/A	N/A	N/A			
	> Location	N/A	N/A	N/A			
19	Fire Control Room						
	Detector System Panel	N/A	N/A	N/A			
	Flow Switch Panel	N/A	N/A	N/A			
	PA System Panel	N/A	N/A	N/A			
	Batter backup	N/A	N/A	N/A			
-	Building Floor Plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	01 CO ₂ type fire extinguishers found provided near elect. panel	MR			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY

Designation: - Asstt. Div. Officer (M.Rd)