GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI- 110001 Fax: 011-23412593, Email :- cfohq.dlfire@nic.in, Ph:- 011-23414333

NO.F6/DFS/MS/School/2013/SZ/ 1015

DATED: 03/10/13

FIRE SAFETY CERTIFICATE

Certified that the New Ring Midways Public School at E-109, Nanhey Park, Uttam Nagar, New Delhi-110059 comprised of ground plus two upper floors owned/occupied by New Ring Midways Public School. The inspection of school was carried out & found complied with the fire prevention and fire safety requirements in accordance with Circular No. F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.2011 issued by Directorate of Education, Gove of NCT of Delhi and verified by the officers concerned of Fire Service on 28.09.2013 in the presence of Mr. Mahesh Solanki (Manager), and that the building is fit for occupancy class B "Educational building" with effect from...03.1.9.13.... for a period of three years, subject to condition as mentioned below.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service

Copy to,

- 1. The Principal, New Ring Midways Public School at E-109, Nanhey Park, Uttam Nagar, New Delhi-110059.
- 2. The Director (Edu.), SDMC, 23rd floor, Civic Centre, Minto Road, New Delhi.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules-2010. The form is available on www.dfs.delhigovt.nic.in.

| | | INSPECTION REP | WOODS AND WOODS CONTROL TO THE PROPERTY OF THE | |
|--------|---|--|--|---------------------|
| 71 | Name & address of the building | New Ring Midways Public School at E-109, Nanhey Park, Uttam Nagar, New Delhi-110059 | | |
| 2 | Type of Occupancy | Educational Building "B" | | |
| 3 | Type of case | New | | |
| 4 | Details of previous NOC | No. | | |
| | | Edu. Circular. No. F.16/Estate/CC/Fire Safety/2011/3298 dated | | |
| 5 | Fire safety directives letter No | 01.03.2011. | | |
| 6 | Date of inspection | 28.09.2013 | | |
| 7 | Name of the inspecting Officers : | ADO S.P. Bhardwaj | | |
| | Name and designation of officers from the building side | Sh. Mahesh Solanki (| Manager) | |
| 8 | nom the building side | | | |
| 9 | Year of construction | | | |
| 10 | Applicant's letter No. | Nil Dated 30.0 | 08.2013 (Ground p | lus two upper |
| 10 | Applicant stetter No. | | 11001) | |
| | | | | / |
| S. NO. | Minimum Standards on fire prevention and fire safety U/R 33 | Edu. Circular/NBC Requirement | Provided at site | Remarks MR / NMR |
| 1 | Access to building | | | |
| | 1) Road width | Required | 6 Mtr Provided | MR |
| | 2) Gate width | Required | 3 & 1.75 Mtrs Provided | MR |
| | 3) Width of internal road | N/A | N/A | N/A |
| 2 | Number, width Type & arrangement of | exits | | |
| | a. Number of staircases | | | |
| | 1. Upper floors | 2 Nos | 2 Nos. Provided | MR \ |
| | 2. basements | N/A | N/A | N/A |
| | b. Width of staircase | | | |
| | 1. Upper floors | 1.25 Mtr | 1 25 Mbs cook Descrided | 100 |
| | 2. basements | | 1.25 Mtr each Provided N/A | MR |
| | c. Protection of exits | N/A | | N/A |
| | 1. Fire check door | N/A | N/A | N/A |
| | 2. Pressurization | N/A | N/A | N/A |
| | d. No. of continuous staircase to | | One Provided | MR |
| | terrace | | | |
| | e. Width of corridor | N/A | N/A | N/A |
| | f. Door size | Required | 1 Mtr Provided | MR |
| 3 | Compartmentation. | | | |
| | 1. Fire check door | N/A | N/A | N/A |
| | 2. Sealing of electrical shafts | N/Ä | N/A | N/A |
| | 3. Fire Rating of shaft door | N/A | N/A | N/A |
| | 4. water curtain | N/A | N/A | N/A |
| | 5. Fire dampers | N/A | N/A | N/A |
| 4 | Smoke Management system. | 20/- | | |
| | basement | 30 a/c per hour 12 a/c per hour | N/A | N/A |
| | | The second secon | | IVA |
| * | upper floors | | Natural Vent. | MR |
| 5 | Fire Extinguishers | | | |

| | First-Aid Hose Reels. | One | Provided | MR |
|----|--------------------------------------|------------|-----------------|---|
| | total numbers on each floor | | Provided | MR |
| | Length of Hose reel hose | 30 Mtr | Provided | MR |
| | Nozzle Diameter | 5mm | 11001000 | |
| | Automatic fire detection and alarmin | g system | N/A | N/A |
| | Type of detectors | N/A | N/A | N/A |
| | location of Main Panel | N/A | N/A | N/A |
| | location of Repeater panel | N/A | N/A | N/A |
| | Alternate source of power | N/A | N/A | N/A |
| | hooter's location | N/A | N/A | N/A |
| 3 | MOEFA | N/A | Provided | MR |
| 9 | Public Address System. | Required | Plovided | |
| 0 | Automatic Sprinkler System. | | N/A | N/A |
| | basement | N/A | | N/A |
| | upper floors | N/A | N/A | N/A |
| | sprinkler above false ceiling | N/A | N/A | p.o/ c |
| 11 | Internal Hydrants | <u> </u> | N/A | N/A |
| | Size of riser/down-corner | N/A | N/A | N/A |
| | Number of Hydrants per floor | N/A | N/A | N/A |
| | hose Box | N/A | N/A | IN/A |
| 12 | Yard Hydrants. | | 1 | N/A |
| | total number of hydrants | N/A | N/A | N/A |
| | hose box | N/A | N/A | IN/A |
| 13 | Pumping arrangements | | | |
| | 1. Ground level | - | | N/A |
| | a. Discharge of main Pump | N/A | N/A | N/A |
| | b.Head of main pump | N/A | N/A | |
| | c.Number of main pumps | N/A | N/A | N/A |
| | d.jockey pump out put | N/A | N/A | N/A |
| | e.jockey pump head | N/A | N/A | N/A |
| | f. Standby Pump output | N/A | N/A | N/A |
| | g.Stanby Pump head | N/A | N/A | , N/A |
| | h.Auto Starting/Manual stopping | N/A | N/A | N/A |
| | pump house access | N/A | N/A | N/A |
| | 2.Terrace level | | | IMR |
| | a. Discharge of pump | 450 LPM | Provided | |
| | b. head of the pump | Required | 35 Mtr Provided | MR |
| | c. Power supply | Required | Provided | MR |
| | d. Auto starting of pump | Required | Provided | MR |
| | | | V | Total Control of the |
| 14 | Captive water storage for fire figh | | N/A | N/A |
| | 1. Underground tank capacity | N/A | N/A | N/A |
| | a. Draw-off connection | N/A | N/A | N/A |
| | b. fire service inlet | N/A | N/A | N/A |
| | c.Access to tank | N/A | Provided | MR |
| | Over head tank Capacity | 10,000 Ltr | Provided | MR |
| 15 | Exit Signage. | Required | Provided | |
| 16 | Provision of lifts. | | NIA | N/A |
| 10 | a. Pressurization of lift shaft | N/A | N/A | N/A |
| | b. pressurization of lift lobby | N/A | N/A | N/A |
| | c. communication in lift car | N/A | N/A | N/A |
| | d. Fireman's grounding switch | N/A | N/A | N/A |
| | e. Lift signage | N/A | N/A | IN/A |

| | N/A | N/A | N/A | |
|---|---|---|------------|--|
| Refuge Area. | Not Required | | | |
| total area location | | | | |
| Fire control room | | | | |
| a. detector system Panel | N/A | N/A | N/A | |
| b. Flow switch Panel | N/A | N/A | N/A | |
| c. PA system Panel | N/A | N/A | N/A | |
| d. Batter backup | N/A | N/A | N/A | |
| e. Building floor plans | N/A | N/A | N/A | |
| Special Fire Protection systems for protection of special risks, if any: N/A | | | | |
| | total area location Fire control room a. detector system Panel b. Flow switch Panel c. PA system Panel d. Batter backup e. Building floor plans | total area location Fire control room a. detector system Panel N/A b. Flow switch Panel N/A c. PA system Panel N/A d. Batter backup N/A e. Building floor plans N/A | total area | |

The fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rules 35 of the Delhi Fire Service Rules 2010/

Accordingly DFA is put up for your approval and signature please.

Signature of the Inspecting Officer

Name

S.P. Bhardwaj

Designation

ADO (Dwarka)