## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. F6/085/ms/EH/2013/WZ/1041

Dated: 08/10/2013

## **FIRE SAFETY CERTIFICATE**

Certified that M/s Gola North End Restaurant located at plot No-3, LSC, Gujrawala Town, Delhi 110009 was granted NOC by this department vide letter no F-6 / DFS / MS / EH / 2010 / 2641 Dated 09/09/2010. The premises was re-inspected by the officers concerned of this department on 13 / 09 / 2013 in the presence of Sh. S P Singh, (Manager) and Sh Ashok Kapoor and found that the building have deem complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and premises is fit for Assembly occupancy with effect from 7 / 10 / 2013 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of Delhi Fire Service Rules, 2010.

- 1. Means of escape shall not be kept locked or bolted from outside and shall be easily open able by guests in an event of emergency.
- 2. All employees shall be acquainted with the use and maintenance of all the fire fighting installation/equipments.
- 3. The fire suppression / protection arrangements provided in the restaurant are to minimize losses, if maintained in good working condition. These systems cannot give any guarantee that there will be no fire or losses in the event of one.
- 4. Any loss of life and property due to non-functional of fire safety arrangements and other installations shall be the responsibility of the licensee.
- 5. This report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.Delhigovt.nic.in"><u>WWW.dfs.Delhigovt.nic.in</u></a>

Issued on \_\_\_\_\_\_\_ at New Delhi by

(SANTOKH SINGH) Chief Fire Officer Delhi Fire Service Ph: 011-23414250 cfowz.dlfire@nic.in

## Copy to:

- 1. The Dy Health Officer, North Delhi Municipal Corporation, Health Department, Civil Lines Zone, 16, Rajpur Road, Delhi-54 for information w r t letter No DHO/CLZ/2013/943 dated 16/08/2013
- 2. The authorized signatory, Smt Meenakshi Kapoor, M/s Gola North End Restaurant located at plot No -3, LSC, Gujrawala Town, Delhi 110009

ac a

B+9+3)

## **INSPECTION REPORT**

1. Name & address of the building: M/S Gola North End Restaurant PNo-3, LSC Gujrawala

2. Type of Occupancy

: Restaurant

3. Type of Case

: Renewal

4. Details of previous NOC

: F-6/DFS/MS/EH/2010/2641 Dated 09/09/2010.

**5.** Fire Safety directives letter No :

6. Date of inspection

: 13/09/2013

7. Name of the Inspecting Officers: DCFO (WZ) & DO (NW)

8. Name and designation of officers

from the building side

: Sh. Ashok Kapoor & Sh. S.P Singh

9. Year of Construction

: 2006

10. Applicant's letter No.

: DHO/CLZ/2013/943 Dated 16/08/2013.

21	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR
1	Access to building	2	: ,	-
	Road width	Accessible	Accessible	M/R
	Gate width			, a
	Width of internal road			
2	Number, Width, Type & Arrangemen	t of Exits	· ·	* _a!
	a. Number of staircases		·	
	Upper Floors	02	02	M/R
	Basements	01	01	M/R
	b. Width of staircases		3	
	Upper Floors	Old case	Old case 🔨	M/R
	Basements	Old case	Old case	M/R
	c. Protection of exits			
	Fire check door			~ ~ ~ ~

	1	I	
<ul> <li>Pressurization</li> </ul>			
e. No. of continuous staircases to terrace			
g. Width of Corridor			
h Door Size			
II. Door Size			
Compartmentation.		-	
Fire check door	N/A	N/A	N/A
<ul> <li>Sealing of electrical shafts</li> </ul>	N/A	N/A	N/A
<ul> <li>Fire Rating of shaft door</li> </ul>			
• Water Curtain			
• Fire Dampers			
Smoke Management System.			
• Basements	30 a/c per hour	Natural/ Exhaust	M/R
• Upper floors	12 a/c per hour		
Fire Extinguishers			
Total numbers	14 ABC Type	14	M/R
• Types		08 ABC, 3	M/R
• IS marking	ISI marked	co2, 3 wco2	
		Yes	M/R
First-Aid Hose Reels.	1		*
Total numbers on each floor	one	Provided	M/R
• Length of hose reel hose	30 m	P	M/R
Nozzle diameter	5 mm	P	M/R
Automatic fire detection and alarming system.			
		N.A	N.A
Type of detectors	N.A	N.A	14.71
	e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size  Compartmentation.  Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers  Smoke Management System.  Basements Upper floors  Fire Extinguishers  Total numbers Types IS marking  First-Aid Hose Reels.  Total numbers on each floor Length of hose reel hose Nozzle diameter	e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size  Compartmentation.  • Fire check door • Sealing of electrical shafts • Fire Rating of shaft door • Water Curtain • Fire Dampers  Smoke Management System.  • Basements • Upper floors  Total numbers • Total numbers • Types • IS marking  ISI marked  First-Aid Hose Reels.  • Total numbers on each floor • Length of hose reel hose • Nozzle diameter  5 mm	e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size  Compartmentation.  • Fire check door • Sealing of electrical shafts • Fire Rating of shaft door • Water Curtain • Fire Dampers  Smoke Management System.  • Basements • Upper floors  • Total numbers • IS marking  First-Aid Hose Reels.  • Total numbers on each floor • Length of hose reel hose • Nozzle diameter  • Total numbers • Total numbers • Total numbers on each floor • Length of hose reel hose • Nozzle diameter

	Location of Repeater Panel			
	Alternate source of power		·	
	Hooters' Location			
8	MOREA	D	,	1.670
0	MOEFA	R	P	M/R
9	Public Address System.	R	P	M/R
10	Automatic Sprinkler System.			
0	Basement	R	P	M/R
8 ,	Upper Floor	R	P	M/R
	Sprinkler above false ceiling			
11	Internal Hydrants		•	
	Size of riser/down-comer	04"	P	M/R
	Number of hydrants per floor	01	P	M/R
180	Hose Box	01	P	M/R
12	Yard Hydrants.			<u> </u>
le	Total number of hydrants	01	P	M/R
i.	Hose Box	01	P	M/R
13	Pumping Arrangements.			
	Ground Level		•	
	Discharge of main Pump	N/A	N/A	N/A
	Head of Main pump			
	Number of main pumps			
	<ul><li>Jockey Pump out put</li></ul>	180 LPM	P	M/R
	<ul><li>Jockey pump head</li></ul>	40 M	P	M/R
	, vocacy pamp nead			

	a				
	> Standby Pump out put	a		····	
	> Standby Pump Head				
	> Auto Starting/ Manual				
	stopping				
	> Pump House Access				
	• Terrace level				
	Discharge of pump	450 LPM	P	M/R	
	> Head of the pump	40 m	P	M/R	
	> Power Supply	R	P	M/R	
	Auto Starting of pump	R	P	M/R	
14	Captive Water Storage for fire fightin	g.			
-	Underground tank capacity	N/A	N/A	N/A	
	> Draw-off connection	·			
	➤ Fire service inlet				
	Fire service finet				
	> Access to tank	5000 ltr	5000 ltr	M/R	
	Overhead Tank capacity	3000 10	e tio.		
15	Exit Signage.				
16					
	Pressurization of Lift Shaft	N/A	N/A	N/A	
	Pressurization of Lift lobby				
	Communication In lift Car				
	Fireman's Grounding Switch				
	• Lift Signage				

17	Standby power supply	R	P (1) 62 KVA (2) 125 KVA	M/R
		u.	(2) 123 KVA	
18	Refuge Area.			
	> Total Area	N/A	N/A	N/A
	> Location	· N/A .	N/A	N/A
19	Fire Control Room			a .
	Detector System Panel			
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel			
		-	_	-
	Battery backup			
	Building Floor Plans			
20	Special Fire Protection Systems for			
	Protection of special Risks, if any:		2	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name

Name

Designation

Designation