GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. FOLDESIMS 1614/2013/W2/1059

Dated: /0/ /0/2013

FIRE SAFETY CERTIFICATE

Certified that the New Mayur Guest House, A-11, Panchwati Azadpur, G.T Road, Delhi Comprised of Basement + Ground + two upper floors, guest house at 1st and 2nd floor heavy 16 room owned and occupied by Smt. Neeru Sachdeva has already been issued fire safety certificate vide Letter No F-6/DFS/MS/95/GH/930 dated 03/07/1995. The premises was reinspected by the officer from this department on dated 19/08/2013 in the presence of Sh. Shyam Lal (Manager) and observed that all the fire prevention & fire safety arrangements as provided in the premises found in good working condition. The premises have there fore deemed complied with the fire prevention and fire safety in accordance with rule 33 of the Delhi Fire Service Rule, 2010 for a period of three years, in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provision of building bye laws.
- 6. This certificate cannot be treated in any case for regularizations of unauthorized construction
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>WWW.dfs.Delhigovt.nic.in</u>

Issued on 10/10/2013 at New Delhi by

(SANTOKH SINGH) Chief Fire Officer Delhi Fire Service Ph: 011-23414250 cfowz.dlfire@nic.in

Copy to:-

- 1. The Additional Commissioner of Police (Lic), 1st floor, Police Station, Defense Colony, New Delhi.
- 2. The owner, New Mayur Guest House, A-11, Panchwati Azadpur, G.T Road, Delhi

INSPECTION REPORT

1. Name & address of the building : New Mayur Guest House, A-11, Panchwati Azadpur, G.T Road, Delhi

2. Type of Occupancy : Guest House (B + G + 02 upper floors) Guest house on 1^{st} and 2^{nd} floor

3. Type of Case : Renewal

4. Details of previous NOC : F-6/DFS/MS/95/GH/2010/930 dated 03/07/1995

5. Fire Safety directives letter No : --

6. Date of inspection : 19/08/20137. Name of the Inspecting Officers : DO NW

8. Name and designation of officers

from the building side : Sh. Shyam Lal (Manager)

9. Year of Construction : 1989

10. Applicant's letter No. : 36681-85/Addl.CP/Lic(H) Dated 17/07/2013

PA-354 SQ Mtr, CA

| S. No. | Minimum Standards on fire prevention and fire safety U/R 33 | NBC Requirement | Provided at site | Remarks MR/NMR | | | |
|-----------|---|--------------------|------------------|-------------------|--|--|--|
| 1 | Access to building | | | | | | |
| | Road width | Accessible | Accessible | M/R | | | |
| | Gate width | | | | | | |
| | Width of internal road | | | | | | |
| 2 | Number, Width, Type & Arrangement of Exits | | | | | | |
| | | | | | | | |
| | a. Number of staircases | 32 | | | | | |
| | Upper Floors | Old case | Old case | M/R | | | |
| | Basements | | | | | | |
| | b. Width of staircases | | | | | | |
| | Upper Floors | Old case | Old case | M/R | | | |
| | Basements | | | | | | |
| | c. Protection of exits | E R | | | | | |
| | Fire check door | Old case | Old case | M/R | | | |
| | Pressurization | | | | | | |
| | d. No. of continuous staircases to terrace | 01 | 01 | M/R | | | |
| | e. Width of Corridor | | | | | | |
| | f. Door Size | Old case | Old case | M/R | | | |
| 3 | Compartmentation. | | 8 | | | | |
| | Fire check door | N.A. | N.A. | N.A. | | | |
| | Sealing of electrical shafts | N.A. | N.A. | N.A. | | | |
| | Fire Rating of shaft door | N.A. | N.A. | N.A. | | | |
| | Water Curtain | N.A. | N.A. | N.A. | | | |
| | Fire Dampers | N.A. | N.A. | N.A. | | | |
| 4 | Smoke Management System. | | | | | | |
| | Basements | 30 a/c per hour | N.A. | N.A. | | | |
| | Upper floors | 12 a/c per hour | N.A. | N.A. | | | |

| | Total numbers | 04 (i) 2 wco2 (ii) 2 co2 | Provided | M/R | | | |
|--------|---|-----------------------------|----------------------|--------|--|--|--|
| | • Types | | | | | | |
| W N | IS marking | ISI marked | <u> </u> | | | | |
| 6 | First-Aid Hose Reels. | | | | | | |
| | Total numbers on each floor | 1 | Provided | M/R | | | |
| | Length of hose reel hose | 20 | | 171/10 | | | |
| | Nozzle diameter | 30 m 5 mm | | . == | | | |
| ' | Automatic fire detection and alarming system. | | | | | | |
| | Joseph Stein. | | | | | | |
| | Type of detectors | N.A. | N.A. | N.A. | | | |
| | Location of Main Panel | N.A. | N.A. | N.A. | | | |
| | Location of Repeater Panel | N.A. | NI A | | | | |
| | Alternate source of power | N.A. | N.A. | N.A. | | | |
| | Hooters' Location | N.A. | N.A. | N.A. | | | |
| 141 | MOEFA | R | P | N.A. | | | |
| | Public Address System. | | | | | | |
|) | Automatic Sprinkler System. | | | | | | |
| | Basement | N.A. | N.A. | 3.T. 4 | | | |
| | Upper Floor | N.A. | N.A. | N.A. | | | |
| | Sprinkler above false ceiling | | | N.A. | | | |
| | Internal Hydrants | N.A. | N.A. | N.A. | | | |
| | Size of riser/down-comer | N. A. | | | | | |
| | Number of hydrants per floor | N.A. | N.A. | N.A. | | | |
| | Hose Box | N.A. | N.A. | N.A. | | | |
| | Yard Hydrants. | N.A. | N.A. | N.A. | | | |
| | • Total number of head | | | | | | |
| | Hose Box | N.A. | N.A. | N.A. | | | |
| | | N.A. | N.A. | N.A. | | | |
| | Pumping Arrangements. | | | - | | | |
| | • Ground Level | | | | | | |
| | Discharge of main Pump | N.A. | N.A. | N.A. | | | |
| | Head of Main pump Number of main pumps | N.A. | N.A. | N.A. | | | |
| | or main pumps | N.A. | N.A. | N.A. | | | |
| | Jockey Pump out put Jockey pump head | N.A. | N.A. | N.A. | | | |
| | Jockey pump headStandby Pump out put | N.A. | N.A. | N.A. | | | |
| | Standby Pump out put Standby Pump Head | N.A. | N.A. | N.A. | | | |
| | | N.A. | N.A. | N.A. | | | |
| | - Transact Stopping | N.A. | N.A. | N.A. | | | |
| | > Pump House Access | N.A. | N.A. | N.A. | | | |
| | • Terrace level | | | | | | |
| | Discharge of pump | 225 LPM | Provided | M/R | | | |
| | Head of the pump | | | : | | | |
| | ➤ Power Supply | | agala (j. jagalaenn) | | | | |
| | ➤ Auto Starting of pump | | | | | | |

| , | ➤ Access to tank | N.A. | N.A. | N.A. | | | |
|-----|--|---------|----------|------|--|--|--|
| | Overhead Tank capacity | 2500Ltr | 2800 Ltr | M/R | | | |
| 15 | Exit Signage. | R | Provided | M/R | | | |
| 16 | Provision of Lifts. | | | | | | |
| | Pressurization of Lift Shaft | N.A. | N.A. | N.A. | | | |
| | Pressurization of Lift lobby | N.A. | N.A. | N.A. | | | |
| | Communication In lift Car | N.A. | N.A. | N.A. | | | |
| | · • Fireman's Grounding Switch | N.A. | N.A. | N.A. | | | |
| | Lift Signage | N.A. | N.A. | N.A. | | | |
| 17 | Standby power supply | R | P | M/R | | | |
| 18 | Refuge Area. | | | | | | |
| 0 2 | > Total Area | N.A. | N.A. | N.A. | | | |
| | > . Location | N.A. | N.A. | N.A. | | | |
| 19 | Fire Control Room | | | | | | |
| | Detector System Panel | N.A. | N.A. | N.A. | | | |
| | Flow Switch Panel | N.A. | N.A. | N.A. | | | |
| | PA System Panel | N.A. | N.A. | N.A. | | | |
| , | Batter backup | N.A. | N.A. | N.A. | | | |
| | Building Floor Plans | N.A. | N.A. | N.A. | | | |
| 20 | Special Fire Protection Systems for Protection of special Risks, if any: | | , | | | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.....

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name

Name

Designation

Designation