## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2013/52/1678

Dated: 15/10/13

## **FIRE SAFETY CERTIFICATE**

Certified that the Guest House **Bonlon Inn** located at 7A/39, WEA, Channa Market, Karol Bagh, New Delhi-110005 comprised of Basement, Stilt, ground floor plus three upper floors, using basement as hall & office, stilt floor for parking, ground floor as reception & 04 guest rooms, first, second & third floor each having 06 guest rooms respectively (Total 22 guest rooms), A pantry for staff in tin shed on terrace was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2010/2106 dated 16.07.2010 & letter No.F.6/DFS/MS/GH/2010/3206 dated 19.11.2010 owned/occupied by Sh. Arun Kumar Jain. The guest house building was re- inspected by the officer concerned of this department on 05.10.2013 in the presence of Sh. Arun Kumar Jain (Owner) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on 15/10/13 at New Delhi.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

- 1. The Joint. Commissioner of Police (Lic.) 1<sup>st</sup> floor, P.S., Defence Colony, New Delhi. (Re. No.47489/Joint. C.P./Lic.(H), Dated 16.09.2013)
- 2. Sh. Arun Kumar Jain (Owner), Guest House Bonlon Inn, 7A/39, WEA, Channa Market, Karol Bagh, N.D-05.

Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used strictly as per the provisions of the Building Bye Laws, 1983.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

	INSPECT	ION REPORT					
	<ol> <li>Name &amp; address of the building: (</li> </ol>	n. H Bonlan Th	n JAIOO LIVE	Clara habit	4		
		Residential (Guest House) MEA, Channa MKK, Karola Residential (Guest House)					
	. The or case	: New Case (Rangwal					
	4. Details of Previous NOC	: Letter No. F. 6/NEC/Mc/CH/2014/2014 Date 10					
	5. Fire Safety directives letter No	: Letter No. F. 6/AFS/MS/GH/2010/2/06 Date 16.07.2010 ter No : F. 6/DES/MS/GH/2010/3206 date 19.11.2010					
	- see of hispeelion	AC 10 2012					
	7. Name of Inspecting Officer	A. N. A. P. C. Aalia					
	8. Name and designation of officers		Burnga				
	From the building side :	Sh. Aru	n Kumar Jain (	"Oliher)			
	9. Year of Construction	Before	2010	Conco			
c	10. Applicant's letter No.	17489 / Toint	:P/Lic. CH) dat	ed 16.08.3	1012		
S.	Translation of all all all all all all all all all al	NBC/BBL	Provided at	Remarks	6/3		
No.	prevention and fire safety U/R 33	Requirement	1	MR/NMR			
1.	Access to building			14114 14114			
	<ul> <li>Road width</li> </ul>	Accessible	09mtr	MR			
	<ul> <li>Gate width</li> </ul>	_	175 cmp	MR	22		
	Width of internal road			1 1			
2.	Number, Width, Type & Arrangement of	of Exits					
	a. Number of staircases	LATES					
	• Upper Floors	One	<u>M.</u>				
	• Basements		One	MR, Being	0010		
	b. Width of staircases	-do-	_do -	- do -			
	Upper Floor						
	Basements		125cms	MR, Being	a Otol C		
	c. Protection of exits	-	125 cms	- olo -			
	Fire check door			1			
	• pressurization			-			
	d. No. of continuous staircases to		_				
	terrace						
	e. Width of Corridor		One				
	f. Door Size		220 cms, 118 cms	_			
			79cms x 20Scms				
3.	Compartmentation				-		
	Fire check door						
	Sealing of electrical shafts						
	Fire Rating of shaft door		Sealed	-			
	Water Curtain						
	Fire Dampers			-			
4.	Smoke Management System				-		
	Basements	30 a/c per	Exhaust Fans				
	Upper floors	hour	are Provided	MR			
			latural Ventilahon	MR			

		12 2/0 202		4	
		12 a/c per hour	,	1	
1		TIOU?	-	-	
5.	Fire Extinguishers				
	<ul> <li>Total numbers</li> </ul>	Two at each floor	Provided	MR	
	<ul><li>Types</li></ul>	Co, WCo, ABC	-do-		
1	<ul> <li>IS marking</li> </ul>	ISI marked	1SI Marked	MR	
6.	First-Aid Hose Reels		131 Marked	I IVX	
	<ul> <li>Total numbers on each floor</li> </ul>	One	Provided	MR	
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	- do -	MR	
!	<ul> <li>Nozzle diameter</li> </ul>	5 mm	- de 1	MR	
7.	Automatic fire detection and alarming	system	7 00 5	1 17/1/	
	Type of detectors		_		
j	<ul> <li>Location of Main Panel</li> </ul>				
	<ul> <li>Location of Repeater Panel</li> </ul>				
	<ul> <li>Alternate source of power</li> </ul>	,	D.G. Set of 125kv	+++-	
	Hooters' Location		O O SET / IZS KV		
8.	MOEFA	Required	Provided	No.O	
9.	Public Address System	- do -	alo	MR	
10.	Automätic Sprinkler System		- 00 -	I IVIX	
	• Basement	Required	Provided	MR	
	Upper Floor	- July Ca	I SOVICE	/ / K	
-	<ul> <li>Sprinkler above false ceiling</li> </ul>		1		
11.	Internal Hydrants				
	<ul> <li>Size of riser/down-comer</li> </ul>	. 1			
	<ul> <li>Number of hydrants per floor</li> </ul>	120		-	
	<ul> <li>Hose Box</li> </ul>	1			
12.	Yard Hydrants		j.		
	<ul> <li>Total number of hydrants</li> </ul>				
The second state of the second	<ul> <li>Hose Box</li> </ul>				
13.	Pumping Arrangements				
*	<ul> <li>Ground Level</li> </ul>		* ,	- (x)	
	Discharge of main Pump	1		20 Cale	
(Pe)	Head of Main pump				
	Number of main pumps				
	> Jockey Pump out put				
	Jockey pump head				
	Standby Pump out put			-	
	Standby Pump Head				
	Auto Starting/Manual				
	stopping	-			

117

## 7A/39, WEA, Channa Market, Karol Bagh, New Delli-05.

				· ·
	Pump House Access			
	Terrace level			
	Discharge of pump		456 LPM	200 0 1 411
	Head of the pump			MR, Being a Old (
	Power Supply	Required	30 M Provided	-do-
	Auto Starting of pump	1 4 4 4	rsoviaea	MR -
14.	Captive Water Storage for fire fighting			i
	<ul> <li>Underground tank capacity</li> </ul>	•		
	Draw-off connection			
	<ul><li>Fire service inlet</li><li>Access to tank</li></ul>	-	Provided	
			rovioled	
	Overhead Tank capacity		0	
			6000 CF2	MR, Being a ciol
15.	Exit Signage.	Required	Provided	MR, Being a Coll
16.	Provision of Lifts.	·	a	4 -
	<ul> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication In lift Car</li> <li>* Fireman's Grounding Switch</li> <li>Lift Signage</li> </ul>			
			3-	
			ρ	h. a
		0	Provided	MR
		Keglured	- olo -	MR
		Required - olo -	-do -	MR
17.	Standby power supply	Required	Provided	MR
18.	Refuge Area.			, A
	> Total Area			
	> Location			
		2 2		
19.	Fire Control Room			
	Detector System Panel			
	Flow Switch Panel			. 4
	PA System Panel			:
	<ul><li>Batter backup</li><li>Building Floor Plans</li></ul>	0	0	
		Required	Provided	MR
		-		,
20.	Special Fire Protection System for Protection of special Risks, if any:			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the above substantial compliance of the minimum standards on fire prevention and Fire Safety measures required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.....

Signature of Inspecting Officer

Designation AssH. Divisional Officer

Do (SW) On ell.

Signature of Inspecting Officer

Name

Designation