Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

0/9

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/School/2013/ \$2 //086

Dated: 15/10/13

FIRE SAFETY CERTIFICATE

Certified that the building of S. K. R Public School located at Bohrianwala Thalla, Inderpuri, New Delhi-110012 comprised of Basement/Lower ground, ground floor plus three upper floors but the school is running at ground floor plus three upper floors only, having total 50 rooms (Including Class Rooms, Office, Staff Rooms, Labs, Library, Sports Room, Examination Room, Music Room & Store etc.) owned/occupied by the Goswami Sati Kewal Ram Ji (Bohrianwala) Memorial Society was re-inspected by the officer concerned of this department on 01.10.2013 in the presence of Smt. Uma Dwivedi (Principal) and found that the Goswami Sati Kewal Ram Ji (Bohrianwala) Memorial Society have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for (Ground floor plus three upper floors only) occupancy class Educational w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on 15/10/20/3 at New Delhi.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

The Principal,
 S. K. R. Public School,
 Bohrianwala Thalla, Inderpuri, N.D-12.

2. Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi – 110 054.

	INSP	ECTION REPORT		:			
	1. Name & address of the buildin	g: S. K. R. Public	c School Boha	ian era la Tra lla			
	 Name & address of the building Type of Occupancy Type of Case 	: Educational	(School) 7	noter Pun N.D.12.			
**	The or case	: New Case/Rene	wal				
	4. Details of Previous NOC	· Letter No		Data			
	5. Fire Safety directives letter No		Letter No Date				
	6. Date of inspection		10.2013				
	7. Name of Inspecting Officer	. A.Λ. M	D C N-11	1			
	8. Name and designation of office	Prs Prs	P.S. Dahir	ja			
	From the building side	· C. / //.	na Dwivedi (00.			
	9. Year of Construction	$\frac{\sqrt{mq}}{\sqrt{mq}}$	ra DWIVEdi (Principal)			
	10. Applicant's letter No.	190		Employee and appropriate to be a secure of the secure of t			
S.	Minimum Standards on fire	NIC day	ed 08.08.2	The second secon			
No.	prevention and fire safety U/R 33	NBC/BBL	Provided at	Remarks			
1.	Access to building	Requirement	site	MR/NMR			
	Road width						
	a contract to the contract to	Accessible	06mts	MR			
	Gate width	_	345cmp	MR			
	 Width of internal road 		_	1			
2.	Number, Width, Type & Arrangeme	nt of Exits					
	a. Number of staircases						
	• Upper Floors	TE	T				
	• Basements	Three	Three	MR (Old Bidg.)			
	b. Width of staircases	One	One	Not use for school purpose,			
	Upper Floor		100.00000				
	• Basements		164,85,80 to 120cm	B MR (Old Blog.)			
	c. Protection of exits	Grany	1	- :1			
	Fire check door						
A .	• pressurization						
	d. No. of continuous staircases to	,	-				
	terrace	1	3 1 5 3				
	e. Width of Corridor		One				
	f. Door Size		228 cms				
	1. 0001 3126		109 cm \$ x 202 cm \$				
3.	Composition		91 cm & x 199 cms	-			
J,	Compartmentation			The state of the s			
	Fire check door						
	 Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers 						
		100	Sealed				
			-				
4							
4.	Smoke Management System		I manufacture and the second				
	 Basements 	30 a/c per		Not lese for School			
	• Upper floors	hour	-	burpose.			
		11001	Natural Ventila	Shi Me			

		an article de la constant de la cons	N/10		CO THE
		12 a/c per			1
		hour			
-			2		1
5.	Fire Extinguishers				
	 Total numbers 	Four at each floor	Provided	MR	
	Types	Co2, WCo2, ABC	- da -	MR	
:	 IS marking 	ISI marked	151 Marked	MR	
6.	First-Aid Hose Reels				
	 Total numbers on each floor 	One	Provided	MR	
	 Length of hose reel hose 	30 m	- do -	MR	
1	 Nozzle diameter 	5 mm	- do:-	MR	-
7.	Automatic fire detection and alarming	system		1	-
	 Type of detectors 				
1	 Location of Main Panel 				-
	 Location of Repeater Panel 				
朝	Alternate source of power			+-1	
	 Hooters' Location 			+ 1	
8.	MOEFA				_
9.	Public Address System		Parill		-
10.	Automatic Sprinkler System		Provided		**************************************
	Basement			Not used for	Cakout beart
	Upper Floor			1,4,4	School
	 Sprinkler above false ceiling 		<u> </u>		
11.	Internal Hydrants				
11.		:	·		
	Size of riser/down-comer	-			
	 Number of hydrants per floor 				-
12	Hose Box		+-		
12.	Yard Hydrants		j.		
	Total number of hydrants	-	-		-
10	Hose Box				
13.	Pumping Arrangements		-	2 - 6 - 7	
	Ground Level				
	Discharge of main Pump				*
G80	Head of Main pump			1.	
	> Number of main pumps	-			
	> Jockey Pump out put		-		
	> Jockey pump head	-			
	> Standby Pump out put	-			
	> Standby Pump Head		1		
	> Auto Starting/Manual	-			
	stopping	-			

	Pump House Access		-	-				
	Terrace level							
	Discharge of pump	450 LPM	450LPM	MR				
-	Head of the pump	30M	30 M	MR				
	Power Supply	5077	3077					
	Auto Starting of pump							
4.	Captive Water Storage for fire fighting		a a	i				
	Underground tank capacity	-	-					
	Draw-off connection	-						
8	Fire service inlet		-	_				
2	Access to tank			-				
	Overhead Tank capacity	10000 /tx	10000 Ctr	MR				
15.	Exit Signage.	10000 Ur Required	Provided	MR				
16.	Provision of Lifts.							
	Pressurization of Lift Shaft	-		No. Ciff				
	Pressurization of Lift lobby			- do -				
	Communication In lift Car			-do-				
	Fireman's Grounding Switch			A :				
	Lift Signage			-do -				
	Elit Signage		**	-do-				
17.	Standby power supply		_					
17.	Statically power supply							
18.	Refuge Area.							
	> Total Area			-				
	> Location		- 14					
19.	Fire Control Room							
	Detector System Panel							
	Flow Switch Panel		-	-				
	PA System Panel							
	Batter backup							
	Building Floor Plans							
		-	y = 1	-				
20.	Special Fire Protection System for Protection of special Risks, if any:			-				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the above substantial compliance of the minimum standards on fire prevention and Fire Safety measures required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Mote: The school building is comprised of basement | Lower Ground, Ground Floor plus
three lipper Floors. The basement | Lower Ground is not used for school purpose as per
letter submitted by the manager of the school. There are total so Rooms including
Office, Class Rooms, Staff Room, Labs, Library, Sports Room, Examination Room, Music Room
& Store etc. The school is running at Ground Floor plus three lipper Floors. FSC is
recommended for Ground Floor plus three lipper Floors.

Signature of Inspecting Officer

Name P.S. Dahiya

Designation ASSH. Divisional Officer

Name

Designation

Signature of Inspecting Officer