GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: <u>cfohq.dlfire@nic.in</u>, <u>Tel:-</u> 011-23414333 NO.F6/DFS/MS/GH/2013/52/1155 Dated: 31 10 13

FIRE SAFETY CERTIFICATE

Certified that M/s Rajput Guest House located at 22A, Nangli Rajapur, East Nizamuddin, New Delhi-110013 comprised of ground floor (Reception + 01 guest rooms), first floor (03 guest rooms), second floor (03 guest rooms) & third floor (03 rooms for private use) was granted NOC for 07 guest rooms up to second floor by this department vide letter No. F.6/DFS/MS/GH/2010/3138 dated 11-11-2010. The premises was re-inspected by the officer concerned of this department on 21.09.2013 in presence of Mr. Arjun Verma, Manager of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi fire service Rules 2010 and that the building/premises is fit for occupancy class residential (Guest house) with effect from 5110 113 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 21 10 13 at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE

Copy to: -

0

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

2. The Manager, M/s Rajput Guest House, 22A, Nangli Rajapur, East Nizamuddin, New Delhi-110013.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: Rajput Guest House, 22A, Nangli Rajapur, East Nizamuddin,

New Delhi-110013.

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: F.6/DFS/MS/GH/2010/3138 dated 11-11-2010

5. Fire Safety directives letter No : Nil

6. Date of inspection

: 21.09.2013

7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(M. Road)

8. Name and designation of officers

from the building side

: Mr. Arjun Verma, Manager

9. Year of Construction

: 2006

10. Applicant's letter No.

: 44160/joint C.P/Lic(H) dated New Delhi the 03-09-2013

Rajput Guest House is comprised of ground floor (Reception + 01 guest rooms), first floor (03 guest

rooms), second floor (03 guest rooms) & third floor (03 rooms for private use).

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC/BBL Requirement	Provided at site	Remarks MR/NMR
1	Access to building	- additionent		MINIMIN
	Road width	06 mts	More than 06 mts	MR
	Gate width		Directly accessible from the road	MR
	Width of internal road	N/A	N/A	N/A
2	Number, Width, Type & Arrangement	of Exits		д — — — — — — — — — — — — — — — — — — —
	a. Number of staircases	-		,
	• Upper Floors	01	01	MR
	• Basements	N/A	N/A	N/A
8 9	b. Width of staircases	-	-	n _
	• Upper Floors	Old Case	0.91 mt	MR
	 Basements 	N/A	N/A	N/A
	c. Protection of exits	-	-	= = =
	• Fire check door	N/A	N/A	N/A
	 Pressurization 	N/A	N/A	N/A
	e. No. of continuous staircases to terrace	.01	01	MR
	g. Width of Corridor	N/A	N/A	N/A
	h. Door Size	N/A	N/A	N/A
3	Compartmentation.			a = = = = = = = = = = = = = = = = = = =
	Fire check door	N/A	N/A	N/A



	Sealing of electrical shafts	N/A	N/A	N/A	
	Fire Rating of shaft door	N/A	N/A	N/A	
	Water Curtain	N/A	N/A	N/A	
	• Fire Dampers	N/A	N/A	N/A	
4	Smoke Management System.	A Secretary	2000	9	
	• Basements	30 a/c per hour	N/A	N/A	
	• Upper floors	12 a/c per hour	N/A	N/A	
5	Fire Extinguishers				
	Total numbers	06	Provided	MR	
	• Types	ABC, W.CO ₂	Provided	MR	
	IS marking	ISI marked	Provided	MR	
6	First-Aid Hose Reels.	,		*	
	Total numbers on each floor	01	Provided	MR	
	• Length of hose reel hose	30 m	Provided	MR	
	Nozzle diameter	5 mm	Provided	MR	
7	Automatic fire detection and alarming system.				
	Type of detectors	N/A	N/A	N/A	
£	Location of Main Panel	N/A	N/A	N/A	
	Location of Repeater Panel	N/A	N/A	N/A	
	Alternate source of power	N/A	N/A	N/A	
	Hooters' Location	N/A	N/A	N/A	
8	MOEFA	Required	Provided	MR	
9.	Public Address System.	N/A	N/A	N/A	
10	Automatic Sprinkler System.		• 1		
	Basement	N/A	N/A	N/A	
	Upper Floor	N/A	N/A	N/A	
, . s	Sprinkler above false ceiling	N/A	N/A	N/A	
11	Internal Hydrants				
	Size of riser/down-comer	, N/A	N/A	N/A	
	Number of hydrants per floor	N/A	N/A	N/A	
	Hose Box	la la	N/A	N/A	



12	Yard Hydrants.	9			
	Total number of hydrants	N/A	N/A	N/A	
1	Hose Box	N/A	N/A	N/A	
13	Pumping Arrangements.	y		,	
	Ground Level				
11 12 13 13 13 13 13 13 13 13 13 13 13 13 13	Discharge of main Pump	N/A	N/A	N/A	
	Head of Main pump	· N/A	N/A	N/A	
	Number of main pumps	N/A	N/A	N/A	
	Jockey Pump out put	N/A	N/A	N/A	
	> Jockey pump head	N/A	N/A	N/A	
	Standby Pump out put	N/A	N/A	N/A	
	Standby Pump Head	N/A	N/A	N/A	
	Auto Starting/ Manual stopping	N/A	N/A	N/A	
	Pump House Access	N/A	N/A	N/A	
	Terrace level				
	Discharge of pump	225 LPM	Provided	MR	
	Head of the pump	30 mts	Provided	MR	
	Power SupplyAuto Starting of pump	Required	Provided (Inverter)	MR	
	- 1300 Starting of pump	Required	Provided	MR	
4	Captive Water Storage for fire fighting.		e jedin		
	Underground tank capacity	N/A	N/A	N/A	
×	Draw-off connection	N/A	N/A	N/A	
	Fire service inlet	N/A	N/A	N/A	
	Access to tank Overhead Tank	N/A	N/A	N/A	
e	Overhead Tank capacity	2,500 lts	2,500 lts	MR	
5	Exit Signage.	Required	Provided	MR	
5	Provision of Lifts.				
	Pressurization of Lift Shaft	N/A	N/A	N/A	
	Pressurization of Lift lobby	N/A	N/A	N/A	
	Communication In lift Car	N/A	N/A	N/A	
	• Fireman's Grounding Switch	N/A	N/A	N/A	



	Lift Signage	N/A	N/A	N/A
17	Standby power supply	Required	Provided (Inverter)	MR 🌦
18	Refuge Area.			•
	> Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19	Fire Control Room	a		2
	Detector System Panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
E 1	Building Floor Plans	· N/A	N/A	N/A
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	One ABC type fire extinguisher found provided near elect panel	MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

DFA is put up for approval & signature please.

1088)

DO (57)

W 2/19/13

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY

Designation: - Asstt. Div. Officer (M.Rd)