FORM 'H'

## FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

**NEW DELHI** 

No. F6/DFS/MS/EH/2013/W2/1197

Dated: 19 | 11 | 13

## FIRE SAFETY CERTIFICATE

Certified that the Sanjha Chulha Restaurant Pvt. Ltd. located at 361, Kohat Enclave, Pitam Pura, New Delhi – 110034 comprised of Basement, Ground plus Three Upper Floors was issued FSC vide letter no. F.6/DFS/MS/EH/2009/1971 dated 06-09-2009. The premises was re inspected by the officer concerned of this department on 21-10-2013 in the presence of Mr. Pawan Sharma (Managing Director) and found that the said Restaurant have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Assembly Building" Group D of Sub Division-D 5 with effect from 19 11 13 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Santokh Singh) Chief Fire Officer Ph: 011-23414250

Copy to:

Pawan Sharma (Managing Director)
 Sanjha Chulha Restaurant Pvt. Ltd.,
 361, Kohat Enclave, Pitam Pura, New Delhi – 110034.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The basement shall be used as per building bye laws 1983.
- 6. The certificate may not be treated in any casé for the regularization of the unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

**INSPECTION REPORT** 1. Name & address of the building: Sanjha Chulha Rastament Prt. Ltd. 361, Kohat Endeve, Pitam Pura, New Yel 2. Type of Occupancy 3. Type of Case : Letter No. 66/765/M5/BH/2009/1971 deAld 06/07/09 4. Details of previous NOC 5. Fire Safety directives Letter No.: . 21-10-13 6. Date of inspection 7. Name of the Inspecting Officer: Mukesh Vesma ADO(MV) Paran Sharma : (Managing Director) 8. Name and designation of Officer from the building side 9. Year of Construction 10. Applicant's letter No. : Nil Dated 30-9-13

S	Minimum standards on fire	BBL	Provided at	Remarks MR/NMR	
No	prevention and fire safety U/R 33	Requirements	site		
1.	Access of building				
	Road width	9m	Revided Revided	MR	
	Gate width	5m		MR	
	Width of internal road	NA.	NA	NA	
2.	Number, width, Type & Arrangements of exits				
	a. Number of staircases				
	Upper floors	2	Provided	MR	
	• Basements	2	Provided	MR	
	b. Width of staircases			a 5 ° ,02	
	Upper floors	Old Case	Old lose	Old lose	
	• Basements	Old Gre	ald lese	Old ase	
	c. Protection of exits				
	Fire check door	NR	NR	NR	
	Pressurization	NR	NR	NR	
	d. No of continuous staircase to terrace	Required.	Provider	L MR	
	e. Width Of Corridor	Required.	NA	NA	
	f. Door Size	Old Case	Old Case	e Old less	

3.	Compartmentation			
	Fire check door	NA	NA	NA
	Sealing of electrical shafts	NA	NA	MA
	Fire Rating of shaft door	NA	NA	NA
	Water Curtain	NA	NA	NA
	Fire Dampers	NA	NA	NA
4.	Smoke managements System			
	Basements	30 a/c per hour	Provided	MR
	• Upper floors	12 a/c per hour	Rionides Rionides	MR
5.	Fire Extinguishers			
	<ul><li>Total numbers</li><li>Types</li></ul>	8	Provides	MR
	• IS marking	ABL ELOZ ISI marked	Provided	MR
		5	Yes	MR
6.	First – Aid Hose Reels			
	Total numbers on each floor	1	Revided	MR
	Length of hose reel hose	30 m	Provides Provides	MR
	Nozzle diameter	5mm	provided.	MR
7.	Automatic fire detection and alarmin	g system	A	
	Type of detectors	NR	MR	NR
	Location of Main Panel	MR	NR	NR
	Location of Repeater Panel	NR	MR	NR
	Alternate source of power	NR	NR	MR
	Hooters' Location	NR	NR	NR
8.	MOEFA		Prevides	MR
9.	Public Address System	Requires	Provided NA	NA
10.	Automatic Sprinkler System			
	Basements	Required	Reprises	MR
	Upper Floor	Required Required	Provided Provided	MR
	Sprinkler above false ceiling		Paralina	MR
	optimizer above raise certifing	D Junes	1) willed	1.17

Chi /

				0
11.	Internal Hydrants			
	Size of riser/down- comer	100mm	Provides	MR
	<ul> <li>Number of hydrants per floor</li> </ul>	1	Provided Provided	MR
	Llaga Day	Regulad	Pravided	MR
12.	Hose Box  Yard Hydrants		mari cae	
12.	Total number of hydrants	111	NA	NA
	<ul><li> Total number of hydrants</li><li> Hose Box</li></ul>	NA	NA	NA
13.	Pumping Arrangements	M	/~ A	MA
13.	Ground Level			
	<ul> <li>Discharge of main pump</li> </ul>			/
	Head of main pump			
	Number of main pumps			
	Jockey pump out put			
	> Jockey pump head		NIA	
	> Standby Pump out put			<u></u>
	> Standby Pump Head			
	Auto Staring/Manual stopping			
	Pump House Access			*
	Terrace level	225lpm	Provides	MR
	Discharge of pump	450.lpm 40 m	Provided	MR
	➤ Head of the pump		Provide A	MR
	➤ Power supply	Required	Provided	MR
	Auto starting of pump	15 years and	1000	
14.	Captive water Storage for fire fighting			
	<ul> <li>Under ground tank capacity</li> </ul>	NA	NA	NA
	> Draw of connection	NA	NA	NA
	Fire service inlet	Requires.	Provided	MR
	Access to tank	Requires	Provides	MR
	Overhead Tank capacity	6000Sts.	Provided	HR
15	Exit Signage	Requires	provided	MR
16.	Provision of Lifts			

	Pressurization of Lift Shaft			· ·
	7 Tessurization of Ent Shart			
	Pressurization of lift lobby	8.,80		
	Communication in lift Car		NIA	
	<ul><li>Fireman's Grounding Switch</li></ul>		NIN	
	➤ Lift Signage			
17.	Standby power supply	Required	Provided	MR
18.	Refuge Area			
	> Total area			
9	> Location		N/A -	
19.	Fire control room			
	Detector system panel		ě	
	Flow Switch Panel			
	> PA System Panel		NA	
	Batter backup		,	
	Building Floor Plans			
20.	Special Fire Protection Systems for Protection of special Risks, if any;	Required of LP4 being	Provides	MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Fire Service Rules 2010/issue shortcomings as noted at

Signature of the Inspecting Officer

Name

MUKUSH VUMA

Designation

ADO (MW)

Signature of the Inspecting Officer

Name

Designation