HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI- 110001
Fax: 011-23412593, Email: cfohg.dlfire@nic.in, Ph. 011-23414333

NO. F6/DFS/MS/Ind./ 2013/SZ/ 1229

DATED: 26/11/13

FIRE SAFETY CERTIFICATE

Certified that the M/s Sonu Exim Pvt. Ltd., Plot No. 47/10, Block-E, Okhla Industrial Area, Phase-2, New Delhi-110020 comprised of basement, ground, two upper floors owned/occupied by M/s Sonu Exim Pvt. Ltd have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of this department on 13.11.2013 in the presence of Sh. Ved Parkash (Director), of the Industrial and that the building is fit for occupancy class G "Industrial building" with effect from 2.4.11.13.... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rule, 2010, subject to condition as mentioned below.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service

Copy to,

- 1. The Executive Engineer (Bldg) HQ, Building Department, SDMC, 8th floor, Civic Centre, Minto Road, New Delhi110002.
- 2. Sh. Ved Parkash (Director), M/s Sonu Exim Pvt. Ltd., Plot No. 47/10, Block-E, Okhla Industrial Area, Phase-2, New Delhi-110020.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The basement shall be used strictly as per the provisions of Building Bye laws.
- e. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules-2010. The form is available on www.dfs.delhigovt.nic.in

10	•	g and also gas a			. 7		
1	Name & address of the building		ON REPOR				
			M/s Sonu Exim Pvt. Ltd. , Plot No. 47/10, Block-E, Okhla Industrial Area, Phase-2, New Delhi-110020.				
2	Type of Occupancy	Industrial building "G"					
3	Type of case	New					
4	Details of previous NOC	No	No				
5	Fire safety directives letter No	F6/DFS/MS/	BP/2013/236	61 dated 03.	10.2013		
6	Date of inspection	13.11.2013					
7	Name of the inspecting Officers	- I will to originally av					
8	Name and designation of officer	Sh. Ved Parkash (Director)					
	from the building side						
9	Year of construction	1986		1			
	Applicant's letter No.	Nil	16.10.2013		basement, ground, two uppe		
	× 8				floors	and, the app	
10			"				
S. NO.	Minimum Standards on fire	BBL-19	83/NBC	Prov	vided at site	Remarks	
	prevention and fire safety U/R		rement		at one	MR / NMR	
1	Access to building			,		1	
1	Access to building 1) Road width	_					
	2) Gate width	Required		10 Mtr Pro		MR	
	3) Width of internal road	Required		5 Mtr Prov	rided	MR	
		N/A		N/A		N/A	
2	Number, width Type & arrange	ment of exits					
	a. Number of staircases						
	1. Upper floors	Two		Provided		MR	
	2. basements	Two		Provided	3	MR	
	b. Width of staircase						
	1. Upper floors	1.25 Mtr		1.25 & 1.1	6 Mtr Provided	MR	
	2. basements	1.25 Mtr		1.2 & 1.25	Mtr Provided	MR	
	c. Protection of exits	Ÿ				1	
	1. Fire check door	Required		Provided		MR	
	2. Pressurization	N/A)	N/A	,	-	
	d. No. of continuous staircase		R ;=	Two Provid	hed	N/A MR	
	to terrace			1100110010	10u	INIU	
	e. Width of corridor	N/A		NI/A	ž	1	
	f. Door size			N/A	-	N/A	
3	Compartmentation.	Required		1 Mtr	9)	N/A	
	1. Fire check door	N/A		NI/A			
	2. Sealing of electrical shafts	Required		N/A		N/A	
	3. Fire Rating of shaft door	N/A		Provided		MR	
	4. water curtain			N/A		N/A	
	5. Fire dampers	N/A		N/A		N/A	
4	Smoke Management system.	N/A		N/A		N/A	
	omore management system.	30 a/c per hou		Tyber 5	- D		
	basement	a/c per hour	r 12	Exhust Far	is Provided	MR	
	upper floors		· 0	Natural Ve	ntilation	MR	
5	Fire Extinguishers						
	total numbers			26 Nos.Pro	vided	MR	
	Types				& Water Co2	MR	
	ISI marking	ISI		Provided		MR	
6	First-Aid Hose Reels.			1		IVII t	
	total numbers on each floor	One		Provided		MR	
	Length of Hose reel hose	30 Mtr		Provided		MR	
	Nozzle Diameter	5mm	•	Provided	1	MR	

7	Automatic fire detection and al			
	Type of detectors	Required	Smoke Provided	MR
	location of Main Panel	Required	Ground Floor Provided	MR
	location of Repeater panel	N/A	N/A	N/A
	Alternate source of power	Required	Battery Provided	MR
	hooter's location	Required	Staircase Provided	MR
8	MOEFA	Required	Provided	MR
9	Public Address System.	N/A	N/A	, N/A
10	Automatic Sprinkler System.	*	and the second s	V
	basement	Required	Provided	MR
	upper floors	Required	Provided	MR
	sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			
	Size of riser/down-corner	150 MM	Provided	MR
	Number of Hydrants per floor	Required	One Provided	MR
	hose Box	Required	One Provided	MR
12	Yard Hydrants.	. loquilou	Tono i Tovidod	TIVII I
12	total number of hydrants	Required	4 Nos. Provided	MR
	house box	Required	4 Nos. Provided	MR
13	Pumping arrangements	ricquired	4 1103. 1 10vided	IVIII
10	1. Ground level			T
	a. Discharge of main Pump	2280 LPM	Provided	MR
	b.Head of main pump	60 Mtr	Provided	MR
	c.Number of main pumps	One	Provided	MR
	1 ' '			
	d.jockey pump out put	180 LPM	Provided Provided	MR
	e.jockey pump head	60 Mtr		MR
	f. Standby Pump output	2280 LPM	Provided	MR
	g.Stanby Pump head	60 Mtr	Provided	MR
	h.Auto Starting/Manual stopping	Required	Provided	MR
	pump house access	Required	Provided	MR
	2.Terrace level	000 DM	IOOO I DIA Duestidad	T
	a. Discharge of pump	900 LPM	900 LPM Provided	MR
	b. head of the pump	40 Mtr	40 Mtr	MR
	c. Power supply	Required	Provided	MR
	d. Auto starting of pump	Required	Provided	MR
14	Captive water storage for fire fighting			
	Underground tank capacity	75,000 ltr	Provided	MR
	a. Draw-off connection	Required	Provided	MR
	b. fire service inlet	Required	Provided	MR
	c. Access to tank	Required	Provided	MR
	d. Over head tank Capacity	20,000 Ltr	Provided	MR
	d. Over fload tarm capacity			
15	Exit Signage.	Required	MR	
16	Provision of lifts.	1	1	
	a. Pressurization of lift shaft	N/A N/A		N/A
	b. Pressurization of lift lobby	N/A N/A		N/A
	c. Communication in lift car	N/A	N/A	N/A
	d. Fireman's grounding switch	N/A	N/A	N/A
	e. Lift signage	N/A	N/A	N/A
17	Standby power supply	Required	Provided	MR

8	Refuge Area.	Not Required				
	total area		- Interviolation			
	location					
19	Fire control room					
	a. Detector system Panel	N/A	N/A	N/A		
	b. Flow switch Panel	N/A	N/A	N/A		
	c. PA system Panel	N/A	N/A	N/A		
	d. Batter backup	N/A	N/A	N/A		
	e. Building floor plans	N/A	N/A	N/A		
20	Special Fire Protection syst	Il Fire Protection systems for protection of special risks, if any: Co2 Fire Extinguishers Prov				
				The Extinguishers Prov		

The fire protection systems provided in the building were checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rule it is recommended to grant of Fire Safety Certificate under rules 35 of the Delhi Fire Service Rules 2010/

Accordingly DFA is put up for your approval and signature please.

Name

Signature of the inspecting officer

Signature of the inspecting officer

Name Dharampal Bhardwaj

M.K. Chattopadhyay

Designation : Divisional Officer

Designation: ADO