GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

Ph.23414333,Fax:23412593,E-mail:cfohq.dlfire@nic.in

No.

F6/DF5/Ms) 2013/HD2) 1259

Dated: 28/11/20/3

FIRE SAFETY CERTIFICATE

Certified that the Cross River Mall at plot no. 9B & 9C,CBD,Shahdra, Delhi-32, owned/occupied by M/s STC Developers Pvt. Ltd., comprising of two basements, ground plus three upper floors was granted NOC vide letter no.F6/DFS/MS/2006/459 dated 23.02.2006. The Multiplex building was inspected by the officer concerned of this department on 15.10.13 & 09.11.13 in the presence of Sh.Dharmendra Singh (Security Manager) and found that the Multiplex building have deemed complied with the fire prevention and fire safety requirements in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and that the building is fit for occupancy Group "Multiplex Building" with effect from ... 9.8. 1... for a period of three years, subject to conditions printed overleaf.

(Dr.G.C.Misra) Chief Fire Officer Delhi Fire Service

M/s STC Developers Pvt. Ltd. Cross River Mall Plot no.9B& 9C,CBD, Shahdra, Delhi -110032.

CONDITIONS:

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures,

management shall be responsible.

4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc. may be got verified from the authorities concerned.

5. This Fire Safety certificate can not be treated in any case for regularizations of

unauthorized construction unauthorized use of land if any.

6. Basements shall be used as per BBL.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building :Cross River Mall at plot no. 9B& 9C,CBD,

Shahdra, Delhi-32.

2. Building is comprised of

:2 basements, Ground + 3 upper floors.

3. Type of Occupancy

: Multiplex (Mall)

4. Type of Case

: Renewal

5.Details of Previous NOC letter :F6/DFS/MS/2006/459 dated 23.02.2006

6. Fire Safety direction letter No : F.6/DFS/MS/BP/2004/1629 Dated 27.07.2004.

7.Date of Inspection

: 15.10.13 & 09.11.2013

8. Name of the Inspecting officers: DO Virendra Singh & ADO Suresh Singh

9. Name and designation of Officer

from the building side

:Sh.Dharmendra Singh (Security Manager)

10.Year of Construction

:2006

11. Applicant's letter No

: 21.10.2013

S.NO.	Minimum Standards on fire prevention	NBC/BBL	Provided at Site	Remarks MR/NMR			
	and fire safety U/R33	Requirement		* ************************************			
1	Access to building						
ì	Road width	12 Mtrs.	24 Mtrs.	MR			
	 Gate width Width of internal road	4.5 Mtrs.	7 Mtrs.	MR			
		6 Mtrs.	6 Mtr.	MR			
2	Number, Width, Type and Arrangement of Exits						
	a. Number of StaircasesUpper FloorBasementB. Width of Staircases	11 Nos.	13 Nos.	MR			
		11 nos.	13 Nos.	MR			
		11 nos.	13 Nos.+2 ramp	MR			
				A. C			
S.	 Upper Floor 	1.5 Mtrs.	1.5 & 2.0 Mtrs.	MR			
	 Basement 	1.5 Mtrs.	1.5 & 2.0 Mtrs.	MR			
	c. Protection of exits						
	Fire check door	Required	Provided	MR			
	 Pressurization e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size 	Required	Provided	MR			
		04 nos.	06 nos.	MR			
		2.0 Mtrs.	2.5 Mtrs.	MR			
		1.25 M	1.0 M& 1.25 M	MR			
3	Compartmentation.						
	Fire check door	Required	Provided	MR			
	 Sealing of electrical shafts 	Required	Sealed	MR			
	Fire rating of shaft door	0 2 hrs.	0 2 hrs.	MR			
	Water curtainFire Dampers	N/A	N/A	N/A			
		Required	Provided	MR			

	Smoke Management System.						
	 Basement 	Required	Provided	MR			
	 Upper floor 	Required	Provided	MR			
5.	Fire Extinguisher						
	 Total numbers 	120 nos.	200 Nos.	MR			
	types	ABC & Co2	ABC & Co2	MR			
	IS marking	ISI marked	ISI marked	MR			
6	First-aid-Hose Reels.						
	Total numbers of each floor						
	 Length of hose reel hose 	06 nos.	06 nos.	MR			
	 Nozzle diameter 	30 m	30 m	MR			
7		5 mm	5 mm	MR			
	Automatic fire detection and alarming system.						
	Type of detectors	Heat & smoke	Provided	MR			
	Location of main panel Location of repeater panel	Control room	Provided	MR			
	Location of repeater panelAlternate source of power	Security Room	Provided	MR			
	Atternate source of power	Battery & DG Set	Provided	MR			
	 Hooters's location 	Staircase	Provided	MR			
8	MOEFA	Required	Provided				
9	Public address System.	Required	Provided	MR			
10	Automatic Sprinkler System.	Required	riovided	MR			
	• basement	Required	Provided	MR			
	upper floor	Required	Provided	MR			
	 sprinkler above false ceiling 	Required	Provided				
11	Internal Hydrants		riovided	MR			
	size of riser/down-comer	150 mm	150 mm	MD			
	 Number of hydrants per floor 	06 nos.	06 nos.	MR			
	Hose Box	06 nos.	06 nos.	MR			
12	Yard Hydrants.	00 1103.	OU HOS.	MR.			
	Total number of hydrants	11 nos.	13 nos.	NAD			
	Hose Box	11 nos.	13 nos.	MR			
13	Pumping Arrangements.	11103.	13 1105.	MR			
	Ground Level	Required	Drovidad	NAD:			
	Discharge of main Pump	2850 LPM	Provided	MR			
	> Head of Main Pump	60 Mtrs.	2850 LPM	MR			
	> Number of main pumps	2 Nos.	60 Mtrs.	MR			
	> Jockey pump out put	180 LPM	2 Nos. 180 LDN4	MR			
	Jockey pump head	60 Mtrs.	2 Nos. 180 LPM	MR			
	> Standby pump out put	2850 LPM	60 Mtrs.	MR			
	> Standby pump Head	60 Mtrs	2850 LPM	MR			
	Auto Starting /Manual stopping	Required	60 Mtrs	MR			
	J. J	Requireu	Auto	MR			
	Pump House Access	Required	Provided	NAD.			
		nequileu	Provided	MR			

	Terrace Level	N/A	N/A	N/A
	Discharge of pump	N/A	N/A	N/A
	Head of the Pump	N/A	N/A	N/A
	Power supply	N/A	N/A	N/A
	Auto Starting of pump	N/A	N/A	N/A
14	Captive Water Storage for Fire Fighting.			
	 Underground tank capacity 	2,00,000 Ltrs.	2,00,000 Ltrs.	MR
	Draw-off connection	Required	Provided	MR
	Fire service inlet	Required	Provided	MR
	Access to tank	Required	Provided	MR
	 Overhead Tank capacity 	50,000 Ltrs.	50,000 Ltrs.	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			
	 Pressurization of Lift Shaft 	Required	Provided	MR
	 Pressurization of Lift lobby 	Required	Provided	MR
	 Communication in lift car 	Required	Provided	MR
	 Firemen's grounding switch 	Required	Provided	MR
	Lift Signage	Required	Provided	MR
17	Standby power supply	Required	Provided	MR
18	Refuge Area.			1711
	 Total area 	N/A	N/A	N/A
	 Location 	N/A	N/A	N/A
19	Fire Control Room			
	 Detector system panel 	Required	Provided	MR
	 Flow switch panel 	Required	Provided	MR
Co Co Co	PA system panel	Required	Provided	MR
EERD	Batter backup	Required	Provided	MR,
1.8	Building Floor Plans	Required	provided	MR
20 -13 14/3	special Fire Protection systems for protection of special Risks, if any:	Required	Provided in all	MR

The fire protection systems provided in the building were tested checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

85 mgh

Signature of the Inspecting Officer

Name

Designation

Signature of the Inspecting Officer
Name VIRENDA SINGN

Designation DOCE