GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

Fax:- 011-23412593 E-mail ID: cfohq.dlfire@nic.in,

Tel:- 011- 23414333

No F 6 / DFS / MS / GH / 2013 / NO2/1201

Dated 6 / 12 / 13

FIRE SAFETY CERTIFICATE

Certified that Le-Roi guest house located at 2206, Chuna Mandi, Paharganj, New Delhi - 55 comprised of ground floor (Reception + Parking + Lobby), mezzanine floor (02 guest rooms), first floor (10 guest rooms), second floor (10 guest rooms) & third floors (10 guest rooms) was granted NOC by this department vide letter No. F.6/DFS/MS/GH/2010/1310 dated 05-05-2010. The premises was re-inspected by the officer concerned of this department on 30-04-2013 in the presence of Mr. Mandeep Singh, Propreiter of the guest house and found that the said guest house have altered few rooms at 1^{st} , 2^{nd} & 3^{rd} floor & now the floorwise occupancy is ground floor (Reception + Parking + Lobby), mezzanine floor (02 guest rooms), first floor (17 guest rooms), second floor (17 guest rooms) & third floors (17 guest rooms) and have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises / building is fit for occupancy class residential (Guest house) with effect from _6/12/1/3__ for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 1010.,

(Dr. G. C. Misra) Chief Fire Officer Delhi Fire Service

- 1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi w.r.t. yours letter No 14884-86/Addl.C.P./Lic(H) dated 19-03-12.
- 2. The Manager, Le-Roi guest house located at 2206, Chuna Mandi, Paharganj, New Delhi 55.

Condition for the validity of fire safety certificate

- a. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- b. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- c. The trained fire fighting staff should be available round the clock.
- d. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- e. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

INSPECTION REPORT

1. Name & address of the building: Hotel Le Roi, 2206, Chuna Mandi, Paharganj, New Delhi-55.

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal/Addition of Rooms

4. Details of previous NOC

: Letter No. F.6/DFS/HQ/GH/2010/1310 Dated: 05/05/2010

5. Fire Safety directives letter No : N/A

6. Date of inspection

: 30.04.2013

7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(HQ); Dharamvir Singh Yadav, DO(CD)

8. Name and designation of officers

from the building side

: Mandeep Singh, Owner/proprietor

9. Year of Construction

: 2009-10

10. Applicant's letter No.

:14884-86/Addl.C.P./Lic.(H) dated 19/03/2012

	10. Applicant's letter No. :14884-86/Addi.C.P./Lic.(H) dated 19/03/2012					
S.	Minimum Standards on fire	NBC	Provided at site	Remarks		
No.	prevention and fire safety U/R 33	Requirement		MR/NMR		
1	Access to building					
	Road width	06 mts	More than 06 mts. wide main road	MR		
	Gate width	N/A	Directly accessible from main road	MR		
	Width of internal road	N/A	N/A	N/A		
2	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases		, a.e., s			
	• Upper Floors	02	02	MR		
	• Basements	N/A	N/A	N/A		
	b. Width of staircases			41		
	 Upper Floors 	0.80 mts.	1.30 & 0.83 mts.	MR		
	• Basements	N/A	N/A	N/A		
	c. Protection of exits	N/A	N/A	N/A		
	 Fire check door 	N/A	N/A	N/A		
	 Pressurization 	N/A	N/A	N/A		
	e. No. of continuous staircases to terrace	01	01	MR		
	g. Width of Corridor	-	1.50 mts.	MR		
	h. Door Size	-	2.10 X 0.90 mts	MR		
3	Compartmentation.					
	Fire check door	N/A	N/A	N/A		

	Sealing of electrical shafts	N/A	N/A	N/A		
	• Fire Rating of shaft door	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	• Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.					
	Basements	30 a/c per hour	N/A	N/A		
	• Upper floors	12 a/c per hour	N/A	N/A		
5	Fire Extinguishers					
	Total numbers	12	Provided	MR		
	• Types	ABC, CO ₂	Provided	MR		
	IS marking	ISI marked	Provided	MR		
5	First-Aid Hose Reels.					
	Total numbers on each floor	01	Provided	MR		
	Length of hose reel hose	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming system.					
	Type of detectors	Smoke	Smoke	MR		
	Location of Main Panel	Ground Floor	Provided	MR		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	UPS/Generator	UPS/Generator	MR		
	Hooters' Location	Near Staircase	Near Staircase	MR		
8	MOEFA	Required	Provided	MR		
9	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System.					
	Basement	N/A	N/A	N/A		
	• Upper Floor	Not Required	Provided in common corridor	MR		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants					
	Size of riser/down-comer	100 mm	Provided	MR		
	Number of hydrants per floor	01	01	MR		
	Hose Box					

2	Yard Hydrants.	NT/A	N/A		
	 Total number of hydrants 	N/A			
	Hose Box	N/A	N/A		
3	Pumping Arrangements.	77/4	NI/A		
	Ground Level	N/A	N/A		
	Discharge of main Pump	N/A	N/A		
	Head of Main pump	N/A	N/A		
	Number of main pumps	N/A	N/A		
	Jockey Pump out put	N/A	N/A		
	Jockey pump head	N/A	N/A		
	Standby Pump out put	N/A	N/A		
	Standby Pump Head	N/A	N/A		
	Auto Starting/ Manual	N/A	N/A		
	stopping	N/A	N/A		
	Pump House Access			0	
	Terrace level	(1)1620LPM	(1)1620LPM	MR	
	Discharge of pump	(2)1620LPM	(2)1620LPM		
		(3)180 LPM	(3)180 LPM		
	➤ Head of the pump	40 mts each	40 mts each	MR	
	> Power Supply	Required	Provided (62 KVA)	MR	
	> Auto Starting of pump	Required	Provided	MR	
14	Captive Water Storage for fire fightin	g.			
	Underground tank capacity	N/A	N/A		
	> Draw-off connection	N/A	N/A		
	> Fire service inlet	N/A	N/A	N/A	
	> Access to tank	N/A	N/A	N/A	
	Overhead Tank capacity	20000 liters	Provided	MR MR	
15	Exit Signage.	Required	Provided	MR	
16	•				
	Pressurization of Lift Shaft	N/A	N/A		
	Pressurization of Lift lobby	N/A	N/A		
	Communication In lift Car	Required	Provided	MR	

				AND THE RESERVE OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED
	Fireman's Grounding Switch	Required	Provided	MR
	Lift Signage	Required	Provided	MR
17	Standby power supply	Required	62 KVA Provided	MR
18	Refuge Area.			
	> Total Area	N/A	N/A	
	> Location	N/A	N/A	
19	Fire Control Room			
	Detector System Panel	N/A	N/A	
	Flow Switch Panel	N/A	N/A	
	PA System Panel	N/A	N/A	
	Batter backup	N/A	N/A	
	Building Floor Plans	N/A	N/A	
20	Special Fire Protection Systems for	Required	01 CO ₂ fire	MR
	Protection of special Risks, if any:	-	extinguisher provided	
			near elect. Panel	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate and addition of 21 rooms under rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY

Signature of the Inspecting Officer
Name DHARAMVIR SINGH YADAV