GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: cfohq.dlfire@nic.in, Tel:- 011-23414333

NO.F6/DFS/MS/EH/2013/52 /13/2

Dated: |3 |12 |13

FIRE SAFETY CERTIFICATE

Certified that **China Garden restaurant** (A unit of Four Seasons Cuisine India Private Limited) located at ground & three upper Floors of M-73, Greater Kailash-II, New Delhi-48 was inspected by the officer concerned of this department on 09-12-2013 in the presence of Mr. Kishore Nath, manager of the restaurant and found that the said restaurant have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class **Assembly group-D** (restaurant) with effect from 13 12 13 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules, 2010.

Issued on 13 12 13 at New Delhi by.

(Dr. G.C. Misra) CHIEF FIRE OFFICER DELHI FIRE SERVICE

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

2. Deputy Health Officer, South Zone, SDMC, Health Department, Aurbindo Marg, Green Park, New Delhi.

3. The Managing Director, China Garden restaurant (A unit of Four Seasons Cuisine India Private Limited), M-73, Greater Kailash-II, New Delhi, New Delhi-48

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building : China Garden restaurant (A unit of Four Seasons Cuisine India

Private Limited), M-73, Greater Kailash-II, New Delhi

2. Type of Occupancy : Restaurant (Assembly group-D)

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/EH/2010/2602 dated 07-09-2010

5. Fire Safety directives letter No : Delhi Fire Service Act 2007 & Rules 2010

6. Date of inspection : 01-12-2013

7. Name of the Inspecting Officers : M.K.Chattopadhyay, ADO(M.Rd)

8. Name and designation of officers

from the building side : Mr. Kishore Nath, Manager

9. Year of Construction : 2007 (starting year)
10. Applicant's letter No. : Nil dated 05.11.2013.

Restaurant is located on **ground & three upper floors** of a building comprised of basement, ground &

three upper floors.

S.	Minimum Standards on fire	NBC/BBL	Provided at site	Remarks
No.	prevention and fire safety U/R 33	Requirements		MR/NMR
1	Access to building			
	Road width	09 mts	Provided	MR
	Gate width	4.5 mts	Directly accessible	MR
	Width of internal road	N/A	N/A	N/A
2	Number, Width, Type & Arrangement of	of Exits	, me.q	· · · · · · · · · · · · · · · · · · ·
	a. Number of staircases	-		- -
	Upper Floors	02	Provided	MR
		02	Provided	MR MR
	Basements b. Width of staircases	-	-	e: -
	Upper Floors	Old case	1.25 mts & 1.10 mts	MR
	Basements	Old case	1.25 mts & 1.10 mts	MR
	c. Protection of exits			
	Fire check door	N/A	N/A	N/A
	D	N/A	N/A	N/A
	Pressurization e. No. of continuous staircases to terrace	01	01	MR
	g. Width of Corridor	Old case	1.5 mts	MR
	h. Door Size	Old case	1.5 mts	MR
3	Compartmentation.	0.		-



M12

	1	-	1	
Fire check door	N/A	N/A	N/A	
 Sealing of electrical shafts 	N/A	N/A	N/A	
	N/A	N/A	N/A	
	N/A		N/A	
Fire Dampers	N/A		N/A	
Smoke Management System.				
• Basements	30 a/c per hour	N/A but provided	1	
Upper floors	12 a/c per hour		MR	
Fire Extinguishers				
Total numbers	20	Provided	MR	
• Types	ABC, CO ₂	Provided	MR	
IS marking	ISI marked	Provided	MR	
First-Aid Hose Reels.				
Total numbers on each floor	01	Provided	MR	
 Length of hose reel hose 	30 m	Provided	MR	
Nozzle diameter	5 mm	Provided	MR	
Type of detectors	Required (smoke/heat)	Provided	MR	
 Location of Main Panel 	Ground floor	Provided	MR	
 Location of Repeater Panel 	N/A	N/A	N/A	
 Alternate source of power 	Required	Provided	MR	
Hooters' Location	Required	Provided at each floor	MR	
MOEFA	Required	Provided	MR	
Public Address System.	N/A	N/A	N/A	
Automatic Sprinkler System.				
 Basement 	N/A	Provided		
• Upper Floor	Required	Provided	MR	
Sprinkler above false ceiling	N/A	N/A	N/A	
Internal Hydrants				
Size of riser/down-comer	100 mm	Provided	MR	
• Number of hydrants per floor	01	Provided	MR	
Hose Box	01	riovided	IVII	
	 Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers Types IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Internal Hydrants	Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers N/A N/A N/A N/A N/A Smoke Management System. Basements Upper floors Total numbers Types Signarking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming system. Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System. Basement Upper Floor Sprinkler above false ceiling N/A Internal Hydrants N/A N/A N/A N/A N/A N/A N/A N/	Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers N/A	



2	Yard Hydrants.	21/4	N/A	N/A	
	 Total number of hydrants 	N/A	N/A	N/A	
	Hose Box	N/A	IN/A	TV/A	
13	Pumping Arrangements.				
	Ground Level	-	-	-	
	Discharge of main Pump	N/A	N/A	N/A	
	Head of Main pump	N/A	N/A	N/A	
	Number of main pumps	N/A	N/A	N/A	
	> Jockey Pump out put	N/A	N/A	N/A	
	Jockey pump head	N/A	N/A	N/A	
	> Standby Pump out put	N/A	N/A	N/A	
	> Standby Pump Head	N/A	N/A	N/A	
	> Auto Starting/ Manual	N/A	N/A	N/A	
	stopping	N/A	N/A	N/A	
	> Pump House Access	N/A	N/A	N/A	
	Terrace levelDischarge of pump	900 , 180 LPM	Provided	MR	
	> Head of the pump	40 mts	Provided	MR	
	> Power Supply	Required	Provided	MR	
	> Auto Starting of pump	Required	provided	MR	
14	Captive Water Storage for fire fighting.				
	Underground tank capacity	N/A	N/A	. N/A	
	➤ Draw-off connection	N/A	N/A	N/A	
	> Fire service inlet	N/A	N/A	N/A	
	> Access to tank	N/A	N/A	N/A	
	Overhead Tank capacity	5,000 liters	Provided	MR	
15	Exit Signage.	Required	Provided	MR	
16	Provision of Lifts.				
	Pressurization of Lift Shaft	N/A	N/A	N/A	
	Pressurization of Lift lobby	N/A	N/A	N/A	
	Communication In lift Car	Required	Provided	MR	
		A .			



		1		
		Required	Provided	MR ,
	Lift Signage	Required	62.5 KVA Provided	MR
7	Standby power supply	1		
8	Refuge Area.	N/A	N/A	N/A
	> Total Area	N/A	N/A	N/A
	> Location	IN/A		
19	Fire Control Room	N/A	N/A	N/A
	Detector System Panel	N/A	N/A	N/A
	 Flow Switch Panel 		N/A	N/A
	PA System Panel	N/A N/A	N/A	N/A
×	Batter backup		N/A	N/A
20	Building Floor Plans Special Fire Protection Systems for	N/A Required	01 CO ₂ type fire extinguishers found provided	MR
	Protection of special Risks, if any:		near elect. panel	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

DFA is put up for approval & signature please.

Do (5%) - not available

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY

Designation: - Asstt. Div. Officer (M.Rd)