GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: cfohq.dlfire@nic.in, Tel:- 011-23414333

NO.F6/DFS/MS/GH/2013/52/1364

Dated: 3///2//3

FIRE SAFETY CERTIFICATE

Certified that Sage Guest House, located at No.4, Navjeevan Vihar, New Delhi comprised of basement floor (vacant), ground floor (04 guest rooms + reception + Pantry + D.Hall), first floor (09 guest rooms), second floor (09 guest rooms), & third floor (09 guest rooms) was granted NOC by this department vide letter No. F.6/DFS/MS/GH/2010/3420 dated 24.12.2010. The premises was inspected by the officer concerned of this department on 20.12.2013 in presence of Mr. Ranjit Kumar Singh, Manager of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi fire service Rules 2010 and that the building /premises is fit for occupancy class residential(Guest house) effect from 31/12 1 3 for a period of 3 (three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 3///2//3 at New Delhi by.

(Dr. G.C. MİSRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

2. The Manager, Sage Guest House, No.4, Navjeevan Vihar, New Delhi.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: M/s SAGE Guest House, No.4, Navjeevan Vihar, New

Delhi.

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/GH/2010/3420 dated 24-12-2010

5. Fire Safety directives letter No : Nil

6. Date of inspection : 20.12.2013

7. Name of the Inspecting Officers : M.K.Chattopadhyay, ADO(M. Road)

8. Name and designation of officers

from the building side : Mr. Ranjit Kumar Singh, Manager

9. Year of Construction : 2010

10. Applicant's letter No. : 63431/joint C.P/Lic(H) dated New Delhi the 15-10-2013

The Sage Guest House is comprised of basement floor (vacant), ground floor (04 guest rooms + reception+ pantry + D.Hall), first floor (09 guest rooms), second floor (09 guest room) & third floor (09

rooms)

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC/BBL Requirement	Provided at site	Remarks MR/NMR
1	Access to building			
	Road widthGate width	06 mts	provided Directly accessible	MR MR
7.5	Width of internal road	N/A	from the road N/A	N/A
2	Number, Width, Type & Arrangement of Exits			
,	a. Number of staircases			
	• Upper Floors	02	Provided	MR (being old case)
	• Basements	02	Provided	MR
	b. Width of staircases	#	Provided	
9	Upper FloorsBasements	1.25 mts	1.6 mts, 1.30 mts Provided	MR
	c. Protection of exits	1.25 mts	1.5 mts, 0.90 mts	MR
	Fire check door	n - 2	Provided	
W a	Pressurization	-		a gas = a
-	e. No. of continuous staircases to terrace	N/A	N/A	N/A
2	g. Width of Corridor	N/A	N/A	N/A
	h. Door Size	02	02	MR
	II. DOOL SIZE	N/A	N/A	N/A



		1/4	la a la	
		N/A	N/A	N/A
3	Compartmentation.	у 2 — в 3 — в	A	, An
	Fire check door	N/A	N/A	N/A
	Sealing of electrical shafts	N/A	N/A	N/A
n .	Fire Rating of shaft door	N/A	N/A	N/A
	Water Curtain	N/A	N/A	N/A
	Fire Dampers	N/A	N/A	N/A
	Smoke Management System.	4 1	2 2	
	Basements	30 a/c per hour	Provided	MR
	Upper floors	12 a/c per hour	N/A	N/A
	Fire Extinguishers	5 · · · · · · · · · · · · · · · · · · ·		3 2
	Total numbers	10	Provided	MR
	• Types	ABC, CO ₂	Provided	MR
	IS marking	ISI marked	Provided	MR
	First-Aid Hose Reels.		* * * * * * * * * * * * * * * * * * *	8 8 20 8
	Total numbers on each floor	01	Provided	MR
	 Length of hose reel hose 	30 m	Provided	MR
	Nozzle diameter	5 mm	Provided	MR
	Automatic fire detection and alarming	g system.	# 0 2	
	Type of detectors	N/A	N/A	N/A
	Location of Main Panel	N/A	N/A	N/A
	Location of Repeater Panel	N/A	N/A	N/A
*1	Alternate source of power	N/A	N/A	N/A
	Hooters' Location	N/A	N/A	N/A
3	MOEFA	Required	Provided	MR
)	Public Address System.	Required	Provided	MR
10	Automatic Sprinkler System.	»		
	• Basement	Required	Provided	MR
	Upper Floor	N/A	N/A	N/A
2 0	Sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			10 T
11	Size of riser/down-comer	100 mm	Provided	MR

		1/5			
	Number of hydrants per floor	01	Provided	MR	
	Hose Box	01	Provided	MR	
12	Yard Hydrants.		7 79		
	Total number of hydrants	N/A	N/A	N/A	
	Hose Box	N/A	N/A	N/A	
13	Pumping Arrangements.				
	Ground Level				
	Discharge of main Pump	N/A	N/A	N/A	
	➤ Head of Main pump	N/A	N/A	N/A	
	Number of main pumps	N/A	N/A	N/A	
	Jockey Pump out put	N/A	N/A	N/A	
	> Jockey pump head	N/A	N/A	N/A	
8	> Standby Pump out put	N/A	N/A	.N/A	
	Standby Pump Head	N/A	N/A	N/A	
2 (3) 2:	Auto Starting/ Manual stopping	N/A	N/A	N/A	
	Pump House Access	N/A	N/A	N/A	
	Terrace level				
	Discharge of pump	1200, 180 LPM	Provided	MR	
	Head of the pumpPower Supply	40 mts	Provided	MR	
2 79	Auto Starting of pump	Required	Provided (DG Set)	MR	
>	rate starting of pump	Required	Provided	MR	
14	Captive Water Storage for fire fighting.	# E			
2	Underground tank capacity	N/A	N/A	N/A	
2 2	> Draw-off connection	N/A	N/A	N/A	
	Fire service inlet	N/A	N/A	N/A	
	Access to tank	N/A	N/A	N/A	
8	Overhead Tank capacity	15,000 lts	15000 lts	MR	
15 .	Exit Signage.	Required	Provided	MR	
16	Provision of Lifts.				
**	Pressurization of Lift Shaft	N/A	N/A	N/A	
	Pressurization of Lift lobby	N/A	N/A	N/A	



		11/6		
	Communication In lift Car	Required	Provided	MR 🔭
	Fireman's Grounding Switch	Required	Provided	MR
2	• Lift Signage	Required	Provided	MR
17	Standby power supply	Required	Provided (DG Set 140 KVA)	MR
18 .	Refuge Area.	a v		g v
2 200,	> Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19	Fire Control Room			a ga a
	Detector System Panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel	N/A	N/A	N/A
: ::	Batter backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	One ABC type fire extinguisher found provided near elect panel	MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2010/3420 dated 24-12-2010 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

Ø7-12-13 Hal573

26/11/13

23 12 2013

Signature of the Inspecting Officer
Name M.K.CHATTOPADHYAY

Designation: - Asstt. Div. Officer (M.Rd)