GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/BNOT/2014/WZ/56

Dated: /5/0/ /2018

Fire Safety Certificate

Following fire safety directives must be adhered to:-

- 1) All the means of escape shall be kept free of all type of obstruction all the time.
- 2) All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3) All the fire fighting equipment shall be maintained in perfect working condition all the time and lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4) Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.
- 5) Basement shall be used as per NBC.
- 6) This NOC may not be treated in any case for regularizations of unauthorized construction, if any.
- 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

Santokh Singh Chief Fire Officer Delhi Fire Service

E-mail: <u>cfowzr.dlfire@nic.in</u>

Phone: 011-23414250

Copy to:

The Manager

7 Star Banquet's located at 20, Shivaji Marg (Near Moti Nagar), New Delhi

Basemont + ground + 1st floor 7 Star Banquet's located at 20, Shivaji Marg (Near Moti Nagar),

Name &address of the building

New Delhi

2. Type of Occupancy

Banquet Hall/Assembly

3. Type of Case

New

4. Details of previous NOC

N.A.

Fire Safety directives letter No. 5.

F6/MS/DFS/BP/2013/2267 dated 19.09.2013

6. Date of inspection

22.12.2013

Name of the Inspecting Officers 7.

DO (West) Sunil Chawdhary

Name and designation of officers 8.

From the building side

Mr. Tejinder Singh

9. Year of Construction

10. Applicant's letter No.

nil dated 28/11/13

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Minimum Standards on fire Prevention and fire safety U/R 33	BBL Requirement	Provided at site	Remarks MR/NMR
1.	Access to building	•		WIR/INIVIR
	Road width	18mtrs	Provided	M.R.
	Gate width	N.A.	N.A.	N.A.
2.	Width of internal road Number, Width, Type & Arrangement	N.A.	N.A.	N.A.
	a. Number of staircasesUpper Floors			
		3	3	M.R.
	Basement	2	2	M.R.
	b. Width of staircases			
	Upper Floors	2 x 2 mtr 1 x 1.5 mtr	1 x 1.5 mtr 2 x 2 mtr	M.R.

	,		D '1 1	M.R.			
	• Basement	2 x 2 mtr	Provided	W.K.			
	c. Protection of exits						
	Fire check door	Required	Provided	M.R.			
	Fire check door		27.7	ND			
	Pressurization	N.R.	N.R.	N.R.			
	d. No. of continuous staircases to terrace						
	e. Width of Corridor	Required 2 mtrs	Halls only	M.R.			
	f. Door size	Andrew M. P. Communication of the Communication of		MD			
		2 x 2 mtr	Provided	M.R.			
3.	Compartmentation.			120			
		required	Provided	M.R.			
	 Fire check door 			27.4			
	 Sealing of electrical shafts 	N.A.	N.A.	N.A.			
	Fire Rating of shaft door	N.A.	N.A.	N.A.			
	Water Curtain	N.A.	N.A.	N.A.			
	Fire Dampers	N.A.	N.A.	N.A.			
4.	Smoke Management System.						
	Basements	required	Provided	M.R.			
	Upper floors	required	Provided	M.R.			
5.	Fire Extinguishers						
	Total numbers	18	22	M.R.			
	Types	Water CO ₂	Provided Water CO ₂ -6	M.R.			
	1,1400	ABC & CO ₂ Required	DCO – 12				
	IS marking	ISI marks required	Provided provided	M.R.			
6.	First-Aid Hose Rees.	,					
	Total numbers on each floor	2	provided	M.R.			

4			W		
	Length of hose reel hose	30 m	required	Provided	M.R.
	Nozzle diameter	5 mm	required	Provided	M.R.
7.	Automatic fire detection and alar	ming s	ystem.		
	Type of detectors		N.R.	N.R.	N.R.
	Location of Main Panel		N.R.	N.R.	N.R.
	Location of Repeater Panel		N.R.	N.R 1.	N.R.
	Alternate source of power	8	N.R.	N.R.	N.R.
	Hooter's Location		N.R.	N.R.	N.R.
8.	MOEFA		Required	Provided	M.R.
9.	Public Address System.		Required	Provided	M.R.
10.	Automatic Sprinkler system		Required	Provided	M.R.
	Basement		Required	Provided	M.R.
	Upper Floor		N.R.	N.R.	N.R.
	Sprinkler above false ceiling		N.R.	N.R.	N.R.
11.	Internal Hydrants	2 2 2			Tar
	Size of riser/down-comer		100 mm	Provided	M.R.
	Number of hydrants per floor		2	Provided	M.R.
	Hose Box		2	Provided	M.R.
12.	Yard Hydrants.		•	78.03 (16.1	
					10 k 13 k 17

	Total number of hydrants	N.R.	N.R.	N.R.
	Hose Box	N.R.	N.R.	N.R.
13.	Pumping Arrangements.			
	Ground Level			7
	Discharge of main pump	NR	NR	NR
No.	➤ Head of Main pump	NR	NR	NR
	Number of main pumps	NR	NR	NR
	> Jockey Pump out put	NR	NR	NR
	> Jockey pump head	180 LPM	Provided	M.R.
	> Standby pump out put	40 mtr	Provided	M.R.
	Standby pump Head	NR	NR	NR
	Auto Starting/Manual stopping	NR	NR	NR
	> Pump Hose Access	NR	NID	ND
	Terrace level	IVIX	NR NR	NR
	> Discharge of pump	1620 LPM	Provided	MR
	> Head of the pump	40 mtr	Provided	M.R.
	> Power supply	Required	Provided	M.R.
	> Auto Starting of pump	required	Provided	M.R.
14.	Captive Water Storage for fire fighting		Provided	44.
	Underground tank capacity	25,000 ltrs	Tank provided on terrace	N.R.
	> Draw -off connection	N.R.	N.R.	N.R.

Privile

	Fire service inlet	N.R.	N.R.	N.R.
	> Access to tank	N.R.	N.R.	N.R.
	Overhead Tank Capacity	N.R.	25,000 ltrs O.H. tank provided instead of U.G tank	M.R.
15	Exit Signage.	Required	Provided	M.R.
16.	Provision of Lifts			
	Pressurization of Lift Shaft	N.A.	N.A.	N.A.
	Pressurization of Lift lobby	N.A.	N.A.	N.A.
	Communication In lift Car	N.A.	N.A.	N.A.
	Fireman's Grounding Switch	N.A.	N.A.	N.A.
	Lift Signage	N.A.	N.A.	N.A.
17.	Standby power supply	Required	Provided	M.R
18.	Refuge Area	V 8	i canalire i	
0.	Ketuge Area		the section of	
<u>j</u>	> Total Area	N.R.	N.R.	N.R.
1	> Location	N.R.	N.R.	N.R.
9.	Fire Control Room	N.R.	N.R.	N.R.
	> Detector System Panel	N.R.	N.R.	.N.R.
	> Flow Switch Panel	N.R.	N.R.	N.R.
	PA system Panel	N.R.	N.R.	N.R.
	> Batter backup	N.R.	N.R.	N.R.
	> Building Floor plans	N.R.	N.R.	N.R.
				e E
		· · · · · · · · · · · · · · · · · · ·	8 11	8

20.	Special Fire Protection Systems		N.D.		7.9
20.			N.K.	N.R.	N.R.
	for	ki .			
	Duotostiss Commist Bill 10	132			
1	Protection of special Risks, if any:		9		

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/.

Signature of the Inspection Officer

Signature of the Inspection Officer

Name Sunil Chawdhary

Name