GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/School/2014/ \$2/136

Dated: 30/1/14

FIRE SAFETY CERTIFICATE

Certified that the **Banasthali Public School** located at Plot No-16, G-Block, Vikaspuri, New Delhi-110018 comprised of ground floor plus two upper floors, having total 32 rooms (Including Class Rooms, Offices, Sci. Labs, Comp. Lab, Sports Room, Library, Hall & Store etc.) was issued NOC by this department vide letter No.F.6/DFS/MS/09/1869 dated 25.06.2009. The School building was re-inspected by the officer concerned of this department on 22.01.2014 in the presence of Smt. Shashi Mohan (Principal) and found that the school management have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class educational w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on 36/1/2014 at New Delhi.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

ole

Copy to:-

- The Principal, Banasthali Public School, Plot No-16, G-Block, Vikaspuri, New Delhi-18.
- Director of Education,
 Govt. of NCT of Delhi, Old Secretariat,
 New Delhi 110 054.

Following fire safety directives must be adhered to –

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

Ground plus two upper floors.

10/3 dd cal

(Renewal)

	INSPECTION REPORT						
	1. Name & address of the building: Parasthal Public Col of DI 1. V. C. D. A						
	2. Type of Occupancy	Educational Needland Needland					
	o. The or case	New Case/Renewal					
	4. Details of Previous NOC	Fire Safety directives letter No : Date of inspection Name of Inspecting Officer Letter No. F6 DFS MS 09 1869 Date \$5.06.2009					
	. " C souch mightings leffer No .						
STREET, CANCELL STREET, CANCEL	6. Date of inspection						
	/ Name of Inspecting Officer :						
	8. Name and designation of officers						
	From the building side	Smt Charlin	Mahan (Principal				
	9. Year of Construction : Smt Shashi Mohan (Principal)						
	10. Applicant's letter No.	235/B.P.S/0	13/25 dt 16:1	1.7m17			
S.	Minimum Standards on fire	NBC	Provided at	the second secon			
No.	prevention and fire safety U/R 33	Requirement	site	Remarks			
1.	Access to building	- requirement	site	MR/NMR			
	 Road width 	Accepible	10 - 1	11.0			
	Gate width	ACCOTION.	12 mm	MR			
	Width of internal road		4 mms	MR			
2.	Number, Width, Type & Arrangement o	of Evite	:	<u>.</u>			
	a. Number of staircases	LAILS					
	• Upper Floors						
	• Basements	Two	two Provided	MR			
	b. Width of staircases	-		No Basement			
	Upper Floor		0 145 cm (2	GI ₀ C			
	• Basements		135 cms & 145 cms (2	DOCH MR			
	c. Protection of exits			No basement			
	Fire check door						
	• pressurization	S		1			
	d. No. of continuous staircases to		· · · · · · · · · · · · · · · · · · ·				
	terrace						
	e. Width of Corridor		01				
	f. Door Size		160.4130	i —			
		Imby	106 cms	MR (Students less)			
3.	Compartmentation			than 45 in each			
	Fire check door						
	Sealing of electrical shafts						
	Fire Rating of shaft door		- Managaran de la companya de la com				
	Water Curtain		The second secon				
	• Fire Dampers		Approximation and the second				
4.							
4.	Smoke Management System						
	 Basements 	30 a/c per					
	 Upper floors 	hour		No Basement			
Name of Street, Street, or other Designation of Street, or oth		<u> </u>	National Ventilation	MR			
				-			

the regard on the case of	- No.	p/4	, e 1,	
		12 a/c per		
		hour		
5.	Fire Extinguishers			
	Total numbers	15		
	Types	ABC 4 CO,	bonded	MR
:	IS marking	ISI marked		MR
6.	First-Aid Hose Reels		-00	MR
	 Total numbers on each floor 	one	Provided	
	 Length of hose reel hose 	30 m	0	MR
	 Nozzle diameter 	5 mm	-96	MR
7.	Automatic fire detection and alarming	system	-0.6	ML
	 Type of detectors 			
	 Location of Main Panel 			
	 Location of Repeater Panel 			
	 Alternate source of power 		1	
	 Hooters' Location 			1
8.	MOEFA			
9.	Public Address System	-	Provided	MR
10.	Automatic Sprinkler System			
	 Basement 			
	 Upper Floor: 			
	 Sprinkler above false ceiling 	·	1	
11.	Internal Hydrants	- 1		
	 Size of riser/down-comer 		100 MM	
	 Number of hydrants per floor 		Poorded	
13	• Hose Box	0	Provided	
12.	Yard Hydrants		J.	
	 Total number of hydrants 		4	
13.	* Hose Box			
10,	Pumping Arrangements • Ground Level			
	I Salarana de la		*	
	Discharge of main PumpHead of Main pump			*.
	> Number of main pumps	•		·
	> Jockey Pump out put	4		
	> Jockey pump head			
	Standby Pump out put			-
	Standby Pump Head	× 11	1	
	Auto Starting/Manual		i.	
	stopping			

N/5

		-		1	
	Pump House Access	36			
	Terrace level	1.		в 8	
	Discharge of pump	450 cm & 180 cpm	fronded	MR	
	> Head of the pump	Leombe	-do	MR	
	Power Supply			IMA	
	Auto Starting of pump	<u> </u>			
14.	Captive Water Storage for fire fighting			Ī	
	 Underground tank capacity 	_ lakh ly —			
	Draw-off connection			•	
	Fire service inlet		2 way provided	MR	
	Access to tank			-	
	Overhead Tank capacity		40000 Um	MR	
			70000 004	11)	
15.	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.				
	Pressurization of Lift Shaft			1	
	 Pressurization of Lift lobby 				
	Communication In lift Car				
	• * Fireman's Grounding Switch				
	Lift Signage				
		V		-	
17.	Standby power supply				
		1	8 5	ÿ (E	
18.	Refuge Area.			T	
	> Total Area				
	> Location	1	7		
	t t				
19.	Fire Control Room				
	Detector System Panel		-		
V	Flow Switch Panel				
.00	PA System Panel		·		
	Batter backup				
	Building Floor Plans		•		
20.	Special Fire Protection System for Protection of special Risks, if any:				

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F6 | DFS | MS | 09 | 1869 dated 25.06.2009 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Note: - There are less than 45 students in each class as given in form k' (placed on C-6), by the principal of school.

Signature of Inspecting Officer

Name Sandeep Duggel
Designation ASIA Divisional Officer

Signature of Inspecting Officer

Name

Designation