GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001 Fax:- 011-23412593 Ph: 011 - 23414250

No F-6/DFS/ms/schnol/2014/MOZ/270

Dated: 26 | 02 | 14

FIRE SAFETY CERTIFICATE

Certified that the Navyug Co-Ed Sr. Sec. School & Navyug Pry. School at Tilak Marg, New Delhi comprises of ground & first floor was granted NOC by this department vide letters No. F6/DFS/MS/2014/103 dated 24-01-2014 & F6/DFS/MS/2008/389 dated 13-02-2008 two separate schools. Now the NDMC have merged the schools on dated 20.04.2011. The premises was re-inspected by the officer concerned of this department on 15-01-2014 in the presence of Sh. Sajjan Sharma Fo NDMC, have deemed complied with the fire prevention and fire safety requirements in accordance with the circular issued by the Director of Education dated 01.03.2011 & DFS order dates 18.04.2012 and that the building is fit for occupancy, class B "Educational Building" with effect from 2-6/02/14_for a period of three years, subject to conditions printed overleaf.

Issued on 2.6. 1.6.2. 1.9. at New Delhi by.

(Santokh Singh) Chief Fire Officer, Delhi Fire Service.

20 Just

Copy to:-

?

- The Principal
 Navyug Co-Ed Sr. Sec. School
 Tilak Marg, New Delhi
- 2. Anil Kumar Saha Fire Officer New Delhi Municipal Council Palika Kendra New Delhi.

-19/4-

INSPECTION REPORT

1. Name & address of the building: Navyug Co-Ed Sr. Sec. School,

Tilak Marg, New Delhi. (Navyug Pry.

School & Navyug Co-Ed Sec. School)

Amalgamated.

2. Building is comprised of

: Ground & First floor

3. Type of Occupancy

: Educational

4. Type of Case

Renewal

5. Details of Previous NOC:

F6/DFS/MS/2008/389 dated 13-2-2008

& F6/DFS/MS/2008/651 dated 04.03.2008.

6. Fire Safety directive letter No

NA

7. Date of Inspection

15.01.2014

8. Name of the Inspecting officers:

Gurmukh Singh, Div. officer.

9. Name and designation of Officer:

from the building side

: Sh. Sajjan Sharma Fo NDMC

10. Year of Construction

Old

12. Applicant's letter No 1

: Letter No. -Nil- dated 10.9.2013

| S.NO. | Minimum Standards on fire | Existing | Provided at | Remarks | |
|-------|--|-------------|---------------|------------------|--|
| | prevention and fire safety U/R33 | Requirement | Site | MR/NMR | |
| 1 | Access to building | | | | |
| 20 | Road width | 5Mtr | 5 Mtr. | MR (old case) h. | |
| 5 | Gate width | 4.5Mtr | 4.5 Mtr | MR | |
| | Width of internal road | NA | NA | NA | |
| 2 | Number, Width, Type and Arrangement of Exits | | | | |
| | a. Number of Staircases | а | 8 | | |
| | Upper Floor | 4Nos. | 4 Nos. | MR | |
| | Basement | NA | NA | NA | |
| | B. Width of Staircases | | | | |
| | Upper Floor | 1.5 Mtr. | 1.35,1.2.1.05 | MR | |
| | • | | &1.05 ramp | e e | |
| | Basement | NA | NA | NA | |
| | c. Protection of exits | NA | NA | NA | |
| | Fire check door | NA | NA | NA | |

-N/2-

| 8 | Pressurization | 1 | | | |
|------------------|---|------------------|----------------|----------|--|
| - | | NA | NA | NA | |
| | e. No. of continuous staircases to terrace | 1 No | 2 Nos. | MR | |
| | g. Width of Corridor | 1.5 Mtr. or less | 2.0 Mtr. | MR | |
| 3 | h. Door Size | 1.0Mtr. | 1.0 Mtr. | MR | |
| 5 | Compartmentation. | | | | |
| | Fire check door | NA | NA | NA | |
| | Sealing of electrical shafts | NA NA | NA | NA | |
| | Fire rating of shaft door | NA | NA | NA | |
| | Water curtain | NA | NA | NA | |
| A | Fire Dampers | NA | NA | NA | |
| 4 | Smoke Management System. | | | 107 | |
| | Basement | NA | NA | NA | |
| _ | Upper floor | NA | NA | NA | |
| 5. | Fire Extinguishers | | | IVA | |
| | Total numbers | 11 Nos. | 18Nos. | MD | |
| | • types | ABC & Co2 | ABC & Co2 | MR MR | |
| 76 | ISI marking | Required | Provided | | |
| 3 | First-aid-Hose Reels. | rtoquired | Flovided | MR | |
| | Total numbers at each floor | 1 No | 3 Nos. | MR | |
| | Length of hose reel hose | 30 Mtr. | 30 Mtr. | MR | |
| | Nozzle diameter | 5 mm | 5mm | MR | |
| Application Con- | | | | IVIIX | |
| , | Automatic fire detection and alarming system. | | | | |
| | Type of detectors | NA | NA | NIA | |
| | Location of main panel | NA | NA | NA | |
| | Location of repeater panel | NA | NA NA | NA | |
| | panol | 1.0.1 | INA | NA | |
| | Alternate source of power | NA | NA | NA | |
| | Hooter's location | NA | Provided | NIA | |
| | MOEFA | NA | Provided | NA | |
| 2 | Public address System. | NA | NA Drawidad | NA | |
|) | Automatic Sprinkler System. | NA | Provided | NA | |
| | Basement | NA | NA | NA | |
| | | 2 | NA | NA | |
| | upper floor (1st.,floor) | NA | NA | NA | |
| | sprinkler above false ceiling | NA | NA | NA | |
| 1 | Internal Hydrants | • | | | |
| | size of riser/down-comer | NA | NA | NA | |

-NB-

| | Number of hydrants per floor | NA. | NA | NA |
|----|--|------------------------|-------------------|-------|
| -0 | Hose Box | NA | NIA | N10 |
| 12 | Yard Hydrants. | INA | NA | NA |
| | Total number of hydrants | NA | NIA | N10 |
| | Hose Box | AND THE REAL PROPERTY. | NA. | NA |
| 13 | | NA | NA | NA |
| 10 | Pumping Arrangements. • Ground Level * | NIA | | |
| | | NA | NA | NA |
| | Discharge of main Pump | NA | NA | NA |
| | > Head of Main Pump | NA | NA | NA |
| | > Number of main pumps | NA | NA | NA |
| | > Jockey pump out put | NA | NA | NA |
| 2 | > Jockey pump head | NA | NA | NA |
| | > Standby pump out put | NA | NA | NA |
| | ➤ Standby pump Head | NA | NA | NA |
| | ➤ Auto Starting /Manual stopping | NA | NA | NA |
| | → Pump House Access | NA | NA | NA |
| | Terrace Level | | | |
| | Discharge of pump | 450 LPM | 450 LPM | MR |
| | Head of the Pump | 40 Mtr. | 40 Mtr. | MR |
| | ➢ Power supply | Required | Provided | MR |
| | ➤ Auto Starting of pump | Required | Provided | MR |
| 14 | Captive Water Storage for Fire Fighting. | | | |
| | Underground tank capacity | NA | NA | NA |
| | ▶ Draw-off connection | NA | NA | NA |
| * | Fire service inlet | NA | NA | NA |
| | ➤ Access to tank | NA | NA | NA |
| 5 | Overhead Tank capacity | 2500 Ltr. | 2500+3000 Ltr. | MR |
| 15 | Exit Signage. | Required | Provided | MR |
| 16 | Provision of Lifts. | - | | |
| | Pressurization of Lift Shaft | NA | NA | NA |
| | Pressurization of Lift lobby | NA | NA | NA |
| | Communication in lift car | NA | NA NA | NA |
| | Firemen's grounding switch | NA | NA | NA NA |
| | Lift Signage | NA | NA | NA |
| 17 | Standby power supply | NA | NA NA | NA |
| 18 | Refuge Area. | NA | | NA |
| | Total area | NA | NA | NA |
| | • I Utai ai Ca | IAN | NA | NA |

-11/4-

| 0 | Location | NA | NA | NA |
|----|---|----|----|----|
| 19 | Fire Control Room | | | |
| | Detector system panel | NA | NA | NA |
| | Flow switch panel | NA | NA | NA |
| | PA system panel | NA | NA | NA |
| | Battery backup | NA | NA | NA |
| | Building Floor Plans | NA | NA | NA |
| 20 | Special Fire Protection systems fire protection of special Risks, if any: | NA | NA | NA |

The fire protection systems provided in the building were tested checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no.F6/DFS/MS/2008/389 dated 13.02.2008 & F6/DFS/MS/2014/103 dated 24.01.2014 renewal under rule 35 of the Delhi Fire Service Rule 2010 is recommended.

The two Schools have been Joined fresh Now is Sulmitted.

Name Gyomnkh Singh

Designation

DO (0)