FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub – rule (1) of rule 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE

No. 66/065/005/2014/W2/290

Dated: 03/03/19

FIRE SAFETY CERTIFICATE

Certified that the NDM - II located at Plot no. D - 1, 2, 3, Netaji Subhash Pace, Pitampura, Delhi - 110034 comprised of 2 Basement + Ground + 10 Upper Floors was issued FSC vide Letter No. F6/DFS/MS/2009/64 dated 09-01-2009. The premises was re-inspected by the officer concerned of this department on 19-02-2014 in the presence of Mr. Tarun Sharma (Engineer) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Business Building" Group E with effect from $\frac{3}{\sqrt{3}}$ for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Santokh Singh) Chief Fire Officer, Delhi Fire Service Ph – 011-23414250

Copy to:-

Sh. Tarun Sharma (Engineer),
 NDM – II, D – 1, 2, 3,
 Netaji Subhash Place, Pitampura, Delhi – 110034.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner / occupier shall submit a declaration every year in the Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building: NDM - II, Plot no. D - 1, 2, 3, Netaji Subhash Place, Pitampura, Delhi – 110034.

2. Type of Occupancy

: Business (2 Basement + Ground + 10 Upper Floors)

3. Type of Case

: Renewal

4. Details of previous NOC : Letter No. F6/DFS/MS/2009/64 dated 09-01-2009

5. Fire Safety directives Letter No.: Letter No. F6/DFS/MS/BP/2006/2655 dated 19-09-2006

6. Date of inspection

: 19-02-2014

7. Name of the Inspecting Officer: DCFO (WZ), DO (West) & ADO (MN)

8. Name and designation of Officer

from the building side

: Sh. Tarun Sharma (Engineer)

9. Year of Construction

: 2008

10. Applicant's letter No.

: Nil dated 10-02-2014

S	Minimum standards on fire	BBL	Provided at	Remarks MR/NMR
No	prevention and fire safety U/R 33	Requirements	site	Δ
1.	Access of building	-		
	 Road width 	24 m	Provided	MR
	 Gate width 	6 m	Provided	MR
	 Width of internal road 	6 m	Provided	MR
2.	Number, width, Type & Arrangeme	ents of exits		,
	a. Number of staircases			
	 Upper floors 	4	Provided	MR
	 Basements 	6	Provided	MR .
	b. Width of staircases			
	 Upper floors 	Old Case	Old Case	Old Case
	 Basements 	Old Case	Old Case	Old Case
	c. Protection of exits		•	
	 Fire check door 	Required	Provided	MR
	 Pressurization 	Required	Provided	MR
	d. No of continuous staircase	2	Provided	MR
	to terrace e. Width Of Corridor	Old Case	Old Case	Old Case
	f. Door Size	Old Case	Old Case	Old Case
3.	Compartmentation			
	Fire check door	Required	Provided	MR
	 Sealing of electrical shafts 	Required	Provided	MR
	 Fire Rating of shaft door 	Required	Provided	MR
	Water Curtain	Required	Provided	NR

	 Fire Dampers 	Required	Provided	MR		
4.	Smoke managements System					
	 Basements 	30 a/c per hour	Required	MR		
	 Upper floors 	12 a/c per hour	Provided	MR		
5.	Fire Extinguishers					
	 Total numbers 	54 nos.	Provided	MR		
	Types	CO2, WCO2,	Provided	MR		
	 IS marking 	ABC	Provided	MR		
		ISI marked				
6.	First – Aid Hose Reels					
	 Total numbers on each floor 	4	Provided	MR		
	 Length of hose reel hose 	30 m	Provided	MR		
	 Nozzle diameter 	5 mm	Provided	MR		
7.	Automatic fire detection and alarming system					
	 Type of detectors 	Smoke & Heat	Provided	MR		
	 Location of Main Panel 	Required	Provided	MR		
	 Location of Repeater 	Required	Provided	MR		
	Panel					
	 Alternate source of power 	Required	Provided	MR		
	 Hooters' Location 	Required	Provided	MR		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System					
	Basements	Required	Provided	MR		
	Upper Floor	Required	Provided	MR		
	 Sprinkler above false 	Required	Provided	MR		
	ceiling					
11.	Internal Hydrants					
	Size of riser/down- comer	150 mm	Provided	MR		
	 Number of hydrants per 	4	Provided	MR .		
	floor		riorided			
	 Hose Box 	Required	Provided	MR		
12.	Yard Hydrants					
	Total number of hydrants	Required	Provided	MR .		
	 Hose Box 	Required	Provided	MR		
13.	Pumping Arrangements		. ro raca	A. 11 X		
	Ground Level					
	 Discharge of main pump 	2850 lpm	Provided	MR		
	Head of main pump	110 m	Provided	MR		
	Number of main pumps	2	Provided	MR		
	Jockey pump out put	2X180 lpm	Provided	MR		
	 Jockey pump head 	110 m	Provided	MR		
	Standby Pump out put	2850 lpm	Provided	MR		
	Standby Pump Head	110 m	Provided	MR		
	Auto Staring/Manual	Required	Provided	MR		
	stopping	1		· LAAN		
	Pump House Access	Required	Provided	MR ,		
	 Terrace level 					

	Discharge of pump	Not Required	NR	NR		
	Head of the pump	Not Required	NR	NR		
	Power supply	Not Required	NR	NR		
	Auto starting of pump	Not Required	NR	NR		
14.	Captive water Storage for fire fighting					
	Under ground tank	2,00,000 litres	Provided	MR		
	capacity	Required	Provided	MR		
	Draw of connection	Required	Provided	MR		
	Fire service inlet	Required	Provided	MR		
	Access to tank	20, 000 litres	Provided	MR		
	 Overhead Tank capacity 	9				
15	Exit Signage	Required	Provided	MR		
16.	Provision of Lifts					
	Pressurization of Lift Shaft	Required	Provided	MR		
	Pressurization of lift lobby	Required	Provided	MR		
	Communication in lift Car	Required	Provided	MR		
	Fireman's Grounding	Required	Provided	MR		
	Switch	Required	Provided	MR		
	Lift Signage					
17.	Standby power supply	Required	Provided	MR		
18.	Refuge Area					
	Total area	Required	Provided	MR		
	Location	5 th , 7 th , 9 th Floor	Provided	MR		
19.	Fire control room.					
	 Detector system panel 	Required	Provided	MR		
	Flow Switch Panel	Required	Provided	MR		
	PA System Panel	Required	Provided	MR		
	Battery backup	Required	Provided	MR		
	Building Floor Plans	Required	Provided	MR		
20.	Special Fire Protection Systems	CO2 flooding	Provided	MR		
	for Protection of special Risks, if	System for HT &		80° A B B B B		
	any;	LT panel		1 0.9		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/2009/64 dated 09-01-2009 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name

Mukesh Velme

Designation

A DO (MW)

Signature of the Inspecting Officer

Name

Designation