## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001 Fax: 23412593, Email: \_\_cheq.dlfire@nic.in, Tel:- 011-23414333

No.F6/MS/DFS/Motel/2014/ 9 2 / 3 2 8

Dated :- 19/03/19

## FIRE SAFETY CERTIFICATE

Certified that the Golden Tulip Motel.KH.NO-241,244,245,246,Min(1<sup>st</sup>),249,251,252,253,256,Village-Asola,New Delhi-110001, comprised of Basement & Ground Floor with 34 guest rooms was granted NOC by this department vide letter No. F6/DFS/MS/Motel/2011/190 Dated 01/02/2011. The premises was reinspected by the officer concerned of this department on 14/02/14 in the presence of Mr.Attiq Khan and Technical Team of Motel and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class **Group – A Residential Building (Motel)** with effect from-1-2-f-9-3-f-2-----for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010.

Issued -- 1- 9/03/1-7-- at New Delhi

(Dr.G.C. Misra) Chief Fire Officer

Copy to:-

- (1) The Joint Commissioner of Police First Floor,PS Defence Colony,New Delhi
- (2) Sh. Kanwar Singh Tanwar Golden Tulip Motel, KH.NO-241,244,245,246,Min(1<sup>st</sup>),249,251,252,253,256, Village- Asola , New Delhi-110001

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

## **INSPECTION REPORT**

- 1.Name & address of the building:- Golden Tulip Motel.KH.NO-241,244,245,246,Min(1<sup>st</sup>), 249,251,252,253,256,Village- Asola ,New Delhi-110001
- 2. Type of occupancy:- Group A, Residential Building (Motel)
- 3. Type of case:-Renewal
- 4. Details of previous NOC:- F6/DFS/MS/Motel/2011/190 Dated:01/02/2011
- 5. Fire safety directives No.- F6/DFS/MS/BP/2006/GH/2989 Dated:06/10/2006
- 6. Date of inspection: 14/02/2014
- 7. Name of the inspecting officer:-Dharampal Bhardwaj, D.O (South) & D.B.Mukherjee , ADO(BCP)
- 8. Name & designation of officer
  From the building side: Mr. Attiq Khan (Manager)
- 9. Year of construction: 2005.
- 10.Applicant's letter No:- 82384/Joint C.P./Lic (H) Dated 27/12/2013

~		Comprised of Basement	Provided at site	Old Case Remarks	
S.No.	Minimum Standards on fire	Requirement NBC/BBL	Flovided at Site	MR/NMR	
	Prevention and fire safety U/R 33	NDC/DDL		17114/171714	
	Access to Building		A1 41:	MR	
	1) Road width	Required	Abutting on more than 30 mtr wide road		
	2) Gate width	5 mtr.	Provided 03 Nos. 5.08,5.05& 5.13 mtrs	MR	
	3)Width of internal road	06 mtr	Provided	MR	
2.	Number, Width Type & Arranger	nent of Exits			
	A. Number of staircases				
	1. Upper floors	Required	02Nos.	MR	
	2. Basements	Required	04 Nos	MR	
	B. Width of staircase				
	1. Upper floors	(Old Case)	1.31m & 1.28 mtrs	MR	
	2. Basements	(Old Case)	1.09, 1.50,3.50,1.31 mtrs respectively	MR	
	C. Protection of exits				
	1. Fire check door	Required	Provided	MR	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	Required	02 Nos. Provided	MR	
	E. Width of corridor	Required	Provided	MR	
	F. Door size	1 mtr.	Provided	MR	
3.	Compartmentation				
	1) Fire check door	Required	Provided	MR	
	2) Sealing of electrical shafts	Required	Provided	MR	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 a/c per hour	Provided	MR	
	2) Upper floors	12 a/c per hour	Natural Ventilation	MR	

5.	Fire Extinguishers			
	1) Total numbers		40 Nos.	MR
	2) Types	ISI Marked	WCo <sub>2</sub> , ABC, Foam & Co <sub>2</sub>	MR
	3) ISI marking		Yes	MR
6.	First-Aid Hose Reel			
	1) Total number of each floor	02 Nos.	Provided	MR
	2) Length of hose reel hose	30 m	Yes	MR
	3) Nozzle diameter	5 mm	Yes	MR
7.	<b>Automatic Fire Detection &amp; Alarmi</b>			
	1) Type of detectors	Required	Smoke & Heat	MR
	2) Location of main panel	Required	Provided at Fire Pump House	MR
	3) Location of repeater panel	Required	Entrance Lobby	MR
	4) Alternate source of power	Required	DG Set & UPS	MR
	5) Hooter's Location	Required	In every floor	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			
	1) Basement	Required	Provided	MR
	2) Upper floors	Required	Provided	MR
	3) Sprinkler above false ceiling	N/A	N/A	N/A
11.	Internal Hydrants-		-	
	1) Size of riser/down-comer	150 mm	Provided	MR
	2) Number of hydrants per floor	02	Provided	MR
	3) Hose box	02	Provided	MR
12.	Yard Hydrants-			
	1) Total number of hydrants	Required	Provided	MR
	2) Hose box	Required	Provided	MR
13.	Pumping Arrangement			
	1) Ground level			
	a) Discharge of main pump	Required	1620 LPM	MR
	b) Head of main pump	Required	70 mtrs	MR
	c) Number of main pump	Required	01	MR
	d) Jockey pump out put	Required	180 LPM	MR
	e) Jockey pump head	Required	70 mtrs	MR
	f) Stand by pump output	Required	1620 LPM	MR
	g) Stand by pump head	Required	70 mtrs	MR
	h) Auto starting/Manual stopping	Required	Provided	MR
	2) Terrace level			
	a) Discharge of pump	Required	900 LPM	MR
	b) Head of pump	Required	70 mtrs	MR
	c) Power supply	Required	Provided From LT Panel & DG Set	MR
	d) Auto starting of pump	Required	Provided	MR
14.	Captive Water Storage for Fire Fig			
	1) Under ground tank capacity	Required	100000 Ltrs	MR
	a) Draw-off connection	Required	Provided	MR
	b) Fire service inlet	Required	Provided	MR
	c) Access to tank	Required '	Provided	MR
	d) Over head tank capacity	10,000 Ltrs	20000 Ltrs	MR
15.	Exit Signage.	Required	Provided	MR



16.	Provi	sion of Lifts.	Not Required	ð.	
	a)	Pressurization of lift shaft	N/A	N/A	N/A
	b)	Pressurization of lift lobby	N/A	N/A	N/A
	c)	Communication in lift car	Required	Provided	MR
	d)	Fireman's switch	Required	Provided	MR
	e)	Lift signage	Required	Provided	MR
17.	Stand	by Power Supply	Required	Provided	MR
18.	Refug	e Area	N/A	N/A	N/A
	Total	area location	N/A	N/A	N/A
19.	Fire (	Control Room	9		
,	a)	Detector system panel	N/A	N/A	N/A
	b)	Flow switch panel	N/A	N/A	N/A
	c)	PA system panel	N/A	N/A	N/A
	d)	Battery backup	N/A	N/A	N/A
	e)	Building floor plan	N/A	N/A	N/A
20.	Specia	al Fire Protection System for P	rotection of special	Risk, if any:	N/A

The fire protection system provided in the building were checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F6/DFS/MS/Motel/2011/190 Dated: 01/02/2011 renewal under rules 35 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly DFA is put up please.

Signature of the inspecting officer

Signature of the inspecting officer

Name: - Dharampal Bhardwaj

Name:-D.B.Mukherjee.

Designation: Divisional Officer (South)

Designation: - Assistant Divisional Officer (BCP)