FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. 1261 DPS/ ms/2014/w2/344

Dated: 21/3/14

FIRE SAFETY CERTIFICATE

Certified that the P P Trade Centre located at Plot no. P - 1, Netaji Subhash Place, Pitampura, Delhi - 110034 comprised of 2 Basement + Ground + 07 Upper Floors owned/occupied by M/s P P Buildwell Pvt. Ltd. was inspected by the officer concerned of this department on 13-03-2014 in the presence of Sh. Kawal Kumar (Owner) and found that the building have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy Class Group - F Mercantile Sub Division F - 2 + Storage (Parking) Group - H, with effect from - 1/3.114.... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 21.13./14 at New Delhi by.

Copy to:

Kawal Kumar (Owner),
 PP Buildwell Pvt. Ltd.,
 Plot No. P -- I, Netaji Subhash Place,
 Pitampura, Delhi - 110034.

Following fire safety directives must be adhered to:-

- (SANTOKH SINGH)
 Chief Fire Officer
 Delhi Fire Service
 Ph: 011-23414250
 cfowz.dlfire@nic.in
 - ed in good working
- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

Re inspection to see the compliance of shortcomings communicated vide letter no. F6/DFS/MS/2014/207 Dated 28-01-2014.

INSPECTION REPORT

1. Name & address of the building: P P Trade Centre, Plot no. P – 1, Netaji Subhash Place, Pitampura, Delhi – 110034.

2. Type of Occupancy

: Mercantile + Storage (Parking) 02 Basement + Ground

+ 07 Upper Floors

3. Type of Case

: New

4. Details of previous NOC

: Nil

5. Fire Safety directives Letter No.: Letter No. F6/DFS/MS/BP/2011/2504 dated 12-10-11

6. Date of inspection

: 13-03-2014

7. Name of the Inspecting Officer: DO (West) & ADO (MN)

8. Name and designation of Officer

from the building side

: Sh. Kawal Kumar (Owner)

9. Year of Construction

: 2014

10. Applicant's letter No.

: Nil Dated 01-02-2014

S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requirements	Provided at site	Remarks MR/NMR	
1.	Access of building				
	 Road width 	12 m	Provided	MR	
	Gate width	4.5 m	Provided 6 m	MR	
	Width of internal road	60 m	Provided	MR	
2.	Number, width, Type & Arrangen	nents of exits			
	a. Number of staircases				
	Upper floors	4	Provided	MR	
	Basements	6 + 2 ramps	Provided	MR	
	b. Width of staircases			17111	
	• Upper floors	1.5m each	Provided	MR	
	• Basements	1.5 m each	Provided	MR	
	c. Protection of exits				
	Fire check door Pressurization	Required	Provided	MR	
	Pressurizationd. No of continuous staircase to terrace	Required	Provided	MR	
		4	Provided	MR	
	e. Width Of Corridor	2.85 m & 2 m	Provided	MR	
	f. Door Size	1 m	Provided	MR	
	Compartmentation	i			
de activité de la constitue de	• Fire check door	Required	Provided	MR	
	 Sealing of electrical shafts 	Required	Found Provided		

M.	_//
1 -	1

			1-6-11				
	0	Fire Rating of shaft door	Required	Found Provided	MR .		
	Water Curtain		Required	Provided	MR		
		Fire Dampers	Required	Found Provided	MR		
4.		e managements System			·		
4.		Basements	30 a/c per hour	Provided	MR		
	8		12 a/c per hour	Provided &	MR		
	8	Upper floors	12 a/e per nour	Found			
			5 000000000000000000000000000000000000	Functional			
5.	Fire F	xtinguishers					
		Total numbers	165 nos.	Provided at all	MR		
		i Otal Hulliocis		locations			
	•	Types	ABC & CO2	Provided	MR		
	@	IS marking	ISI marked	Provided	MR		
6.		- Aid Hose Reels					
0.		Total numbers on each	5	Provided	MR		
	0	floor		and the second of the second of			
	- COM	Length of hose reel hose	30 m	Provided	MR		
	9	Nozzle diameter	5 mm	Provided	MR		
-7	Auton	natic fire detection and alarm		1 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2			
7.			Smoke & Heat	Provided	MR		
	40	Type of detectors	Required	Provided	MR		
	8	Location of Main Panel	Required	Provided	MR		
	(8)	Location of Repeater	Required	Tiovided	TATT		
	A A A STORE OF THE	Panel	Required	Provided	MR		
	•	Alternate source of power	Required	Provided	MR		
	 Hooters' Location 		A CONTROL OF THE CONT				
8.	MOE		Required	Provided	MR		
9.		Address System	Required	Provided	MR		
10.	Autor	matic Sprinkler System	0 1	D '11	MD		
	0	Basements	Required	Provided	MR		
	9	Upper Floor	Required	Provided	MR		
	0	Sprinkler above false	Required	Provided	MR		
		ceiling					
11.	Intern	al Hydrants		2.4.4			
	. 0	Size of riser/down- comer	150 mm	Provided	MR		
	8	Number of hydrants per	5	Provided	MR		
		floor			3 (7)		
	•	Hose Box	5	Provided	MR		
12.	Yard	Hydrants					
	0	Total number of hydrants	6	Provided	MR		
		Hose Box	6	Provided	MR		
13.	Pumping Arrangements						
	69	Ground Level					
	9	Discharge of main pump	2850 lpm	Provided	MR		
	-	Head of main pump	85 m	Provided	MR		
	>	The state of the s	2	Provided	MR		
	>	Paris Paris	2 X 280 lpm	Provided	MR		
and collection and the state of	1	P The P	85 m	Provided	MR		
	ada	, 1 1	2850 lpm .	Provided	MR		
	1	Standby Pump Head	85 m	Provided	MR		

M

		7.0		
	Auto Staring/Manual	D		
	stopping	Required	Provided	MR
	Pump House Access			
	• Terrace level	Required	Provided	MR
	Discharge of pump			
	Head of the pump	900 lpm	Provided	MR
	Power supply	85 m	Provided	MR
	Auto starting of pump	Required	Provided	MR
4.	Captive water Co	Required	Provided	
	- The water storage for fire fig		Trovided	MR
	 Under ground tank 	2,00,000 litres	Provided	MD
	capacity	1	/ Trovided	MR
	Draw of connection	Required	Provided	
	Fire service inlet	Required	Provided	MR
	Access to tank	Required	Provided	MR
_	• Overhead Tank capacity	20, 000 litres	The same of the sa	MR
5	Exit Signage	Required	Provided	MR
_		required	Adequately	MR
).	Provision of Lifts		Provided	
-	Pressurization of Lift	Required		
	Shaft	required	Provided &	MR
		Required	Functional	
	Pressurization of lift lobby	Required	Provided &	MR
		D	Functional	
ĺ	Communication in lift Car	Required	Provided	MR
1	Fireman's Grounding	Required	Provided	MR
	Switch			
	Lift Signage	Required	Provided	MR
	Standby power supply	The state of the s		
	Refuge Area	Required	Provided	MR
	> Total area	2506		
	Location	250Sq.m	Provided	MR
T	Fire control room	7 th Floor	Provided	MR
		Annual Control of the		WIIC
	Detector system panelFlow Switch Panel	Required	Provided	MR
	PA System Panel	Required	Provided	
	PA System Panel	Required	Provided	MR MR
	Building Floor Pl	Required	Provided	MR
-	Building Floor Plans	Required	Provided	MR (a)
0	pecial Fire Protection Systems	HT & LT Panel		MR
11	of Protection of special Risks, if	Compartmentation	Provided	MR (4)
	ny;	- Farencination		I Truck & gra

on systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/issue shortcomings as noted at serial numbers

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name MUKESH VERMA Note: - Dambers have been provided

Designation ADO (MN) DYC. fo. in the A. H.U. Designation