## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

Ph - 23414333 Fax - 23412593 Email - cfohq.dlfire@nic.in

No. F6/OFS/MS/2014/MDZ/362

Dated: 27/03/14

## FIRE SAFETY CERTIFICATE

Certified that the Banquet Hall running at ground plus two upper floors of a building which comprised of Basement, ground plus two upper floors located at G-78, Vikas Marg, Preet Vihar, Delhi-92, owned/occupied by M/S Culinary Hospitality Pvt. Ltd, have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officers concerned of this department on dated 20.02.14 in the presence of Owner and found that the building is fit for occupancy class D 'Assembly (Banquet Hall)' with effect from 2.7/.03./.04.... for a period of three years, in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, subject to conditions printed overleaf.

Issued on 27/03/19 at New Delhi by

(Dr. G.C. Misra)

Chief Fire Officer

01c /2713

To

M/S Culinary Hospitality Pvt. Ltd., G-78, Vikas Marg, Preet Vihar, Delhi-92.

Copy to-

The Dy. Health Officer,

EDMC Health Department,

Karkardooma, Shahdara, Delhi

## CONDITIONS:

- 1. All the means of escape shall be kept free of all the type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc. may be got verified from the authorities concerned.
- This Fire Safety Certificate can not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. Basement shall be used as per BBL.

1. Name & address of the building : M/S Culinary Hospitality Pvt. Ltd., G-78, Vikas Marg, Preet Vihar,

Delhi-92.

2. Building is comprised of : B+G+2 (Banquet is proposed at G+2)

3. Type of Occupancy : Assembly (Banquet Hall)

4. Type of Case : New Case

5. Details of Previous NOC : Nil

6. Fire Safety direction letter No : F6/DFS/MS/BP/2013/1573 dated 11.06.13

7. Date of Inspection : 20.02.14

8. Name of the Inspecting Officers: : Suresh Singh (ADO)

9. Name of the designation of Officer

from the building side : Owner

10. Year of Construction : 1994

11. Applicant's letter No : Nil

| S.No | Minimum Standards on fire prevention   | Requirement/NBC     | Provided at Site  | Remarks      |  |  |
|------|--|---------------------|-------------------|--------------|--|--|
|      | and fire safety U/R33  | , requirement, resc | Trovided at Site  | MR/NMR       |  |  |
| 1    | Access to building   |                     |                   | TVITTY TVITT |  |  |
|      | Road width   | 6 m                 | 20 m              | MR           |  |  |
|      | Gate width   | N.A.                | N.A.              | N.A.         |  |  |
|      | Width of internal road   | N.A.                | N.A.              | N.A.         |  |  |
| 2    | Number, Width, Type and Arrangement of Exits   |                     |                   |              |  |  |
|      | a. Number of Staircases  | 2 no.               | 02 no.            | MR           |  |  |
|      | Upper Floor  | 2 no.               | 02 no.            | MR           |  |  |
|      | Basement   | 1 no.               | 03 no.            | MR           |  |  |
|      | b. Width of Staircases   | 1.5 m               | 1.5 m each        | MR           |  |  |
| ١.,  | Upper Floor Basement c. Protection of exits Fire check door Pressurization e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size i. No. of door | 1.5 m               | 1.5 m each        | MR           |  |  |
| A;   |  | 1.5 m               | 1.5m, 1.1m, 0.90m | MR           |  |  |
|      |  |                     | 111               | 2.           |  |  |
|      |  | Required            | Provided          | MR           |  |  |
|      |  | N.A.                | N.A.              | N.A.         |  |  |
|      |  | 02 nos.             | Provided          | MR           |  |  |
|      |  | N.A.                | N.A.              | N.A.         |  |  |
|      |  | 2 m                 | 2 m each floor    | MR           |  |  |
|      |  | 2 no.               | 2 no. each floor  | MR           |  |  |
| 3    | Compartmentation.  |                     |                   |              |  |  |
| -    | Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers  | N.A.                | N.A.              | N.A.         |  |  |
|      |  | N.A.                | N.A.              | N.A.         |  |  |
| •    |  | N.A.                | N.A.              | N.A.         |  |  |
|      |  | N.A.                | N.A.              | N.A.         |  |  |
|      |  | N.A.                | N.A.              | N.A.         |  |  |
| 1    | Smoke Management System.   |                     |                   |              |  |  |
|      | Basement   | Ventilated          | Ventilated        | MR           |  |  |
|      | Upper floor  | Ventilated          | Ventilated        | MR           |  |  |

is Basement is not being used as Bannet. It is in possesson of other and used as storage.

1/2

| 5. | Fire Extinguisher                                |                       |  |       |  |  |  |
|----|--|-----------------------|--|-------|--|--|--|
|    | Total numbers                                    | 06 no.                | 13 no.   | MR    |  |  |  |
|    | types  | CO <sub>2</sub> & ABC | CO <sub>2</sub> & ABC  | MR    |  |  |  |
|    | IS marking                                       | ISI marked            | ISI marked   | MR    |  |  |  |
| 6  | First-aid-Hose Reels.                            |                       |  |       |  |  |  |
|    | Total numbers of each floor                      | 1 no.                 | 1 no.  | MR    |  |  |  |
|    | Length of hose reel hose                         | 30 m                  | 30 m   | MR    |  |  |  |
|    | Nozzle diameter                                  | 5 mm                  | 5 mm   | MR    |  |  |  |
| 7  | Automatic fire detection and alarming system.    |                       |  |       |  |  |  |
|    | Type of detectors                                | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | Location of main panel                           | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | Location of repeater panel                       | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | Alternate source of power                        | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | Hooters's location                               | N.A.                  | N.A.   | N.A.  |  |  |  |
| 8  | MOEFA  | Required              | Provided   | MR    |  |  |  |
| 9  | Public address System.                           | N.A.                  | N.A.   | N.A.  |  |  |  |
| 10 | Automatic Sprinkler System.                      |                       |  |       |  |  |  |
|    | basement   | Required              | Provided   | MR    |  |  |  |
|    | upper floor                                      | N.A.                  | Provided   | MR    |  |  |  |
|    | sprinkler above false ceiling                    | N.A.                  | N.A.   | N.A.  |  |  |  |
| 11 | Internal Hydrants                                |                       |  |       |  |  |  |
| 11 | size of riser/down-comer                         | 100 mm                | 100 mm   | MR    |  |  |  |
|    | Total no. of hydrants each floor                 | 01 no.                | 03 no.   | MR    |  |  |  |
|    | Hose Box per floor                               | 01 no.                | 01 no.   | MR    |  |  |  |
| 12 | Yard Hydrants.                                   | 01110.                | 01110.   | TVIIV |  |  |  |
| 12 | Total number of hydrants                         | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | Hose Box   | N.A.                  | N.A.   | N.A.  |  |  |  |
| 13 | Pumping Arrangements.                            | 14.7.                 | IV.A.  | 14.74 |  |  |  |
| 15 | Ground Level                                     | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | > Discharge of main Pump                         | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | ➤ Head of Main Pump                              | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | > Number of main pumps                           | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | > Jockey pump out put                            | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | <ul><li>Jockey pump head</li></ul>               | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | > Standby pump out put                           | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | > Standby pump Head                              | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | <ul><li>Auto Starting /Manual stopping</li></ul> | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | Pump House Access                                | N.A.                  | N.A.   | N.A.  |  |  |  |
|    | Terrace Level                                    | IV.A.                 | IV.A.  | IV.A. |  |  |  |
|    | Discharge of pump                                | 900 LPM               | 900 LPM  | MR    |  |  |  |
|    | ➤ Head of the Pump                               | 40 m                  | The second secon |       |  |  |  |
|    | Power supply                                     |                       | 40 m   | MR    |  |  |  |
|    | Auto Starting of pump                            | Required              | Provided   | MR    |  |  |  |
|    |  | N.A.                  | N.A.   | N.A.  |  |  |  |

## IRU/5

M/S Culinary Hospitality Pvt. Ltd., G-78, Vikas Marg, Preet Vihar, Delhi-92

| 1  |   |               | o, rect villar, De    | 1111-92 |  |  |
|----|---|---------------|-----------------------|---------|--|--|
| 14 | out the Water Storage for Fire Fighting |               |                       |         |  |  |
|    | Underground tank capacity               |               |                       |         |  |  |
|    | Draw-off connection                     | N.A.          | N.A.                  | N.A.    |  |  |
|    | Fire service inlet                      | N.A.          | N.A.                  | N.A.    |  |  |
|    | Access to tank                          | N.A.          | N.A.                  | N.A.    |  |  |
|    | Overhead Tank capacity                  | N.A.          | N.A.                  |         |  |  |
| 15 | Exit Signage.                           | 15,000 Liters | 15,000 Liters         | N.A.    |  |  |
| 16 | Provision of Lifts.                     | Required      | Provided              | 31111   |  |  |
|    |   |               | Frovided              | MR      |  |  |
|    | Pressurization of Lift Shaft            | N.A.          | N. A                  |         |  |  |
|    | Pressurization of Lift lobby            | N.A.          | N.A.                  | N.A.    |  |  |
|    | Communication in lift car               | Required      | N.A.                  | N.A.    |  |  |
|    | Firemen's grounding switch              | Required      | Provided              | MR      |  |  |
|    | Lift Signage                            |               | Provided              | MR      |  |  |
| 17 | Standby power supply                    | Required      | Provided              | MR      |  |  |
| 18 | Refuge Area.                            | Required      | Provided              | MR      |  |  |
|    | Total area                              |               |                       |         |  |  |
|    | Location                                | N.A.          | N.A.                  | N.A.    |  |  |
| 19 | Fire Control Room                       | N.A.          | N.A.                  |         |  |  |
|    | Detector system panel                   |               | 1                     | N.A.    |  |  |
|    | Flow switch panel                       | N.A.          | N.A.                  |         |  |  |
| 1  | PA system panel                         | N.A.          | N.A.                  | N.A.    |  |  |
| 1  | Batter backup                           | N.A.          |                       | N.A.    |  |  |
|    | Building Floor Plans                    | N.A.          | N.A.                  | N.A.    |  |  |
|    |   |               | N.A.                  | N.A.    |  |  |
| 0  | Special Fire Protection systems for     | N.A.          | N.A.                  | N.A.    |  |  |
|    | protection of special Risks, if any:    | Required      | CO <sub>2</sub> local | MR      |  |  |
|    |   |               | application in        |         |  |  |
|    |   |               | electrical panel      |         |  |  |
| C. | Orotection system                       |               | provided              |         |  |  |

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer

Name Suresh Singh

Designation ADO (Shah)