GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI -110001

No F6 DFS MS EH / 2014 MDZ / 504

Dated 23/04/14

FIRE SAFETY CERTIFICATE

& mezzanine floor, of building which comprises of Ground +2 Upper floors, was granted NOC by this department vide letter No.F6/MS/DFS/2011/EH/1313 dated 24-06-2011. The premises was re-inspected by the officer concerned of this department on 16-04-2014 in the presence of Mr. Rakesh Sr. Manager and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules. 2010 and that the premises is fit for occupancy of restaurant with effect from .2.3 99.1.2014 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

Issued ... 2.3 . 0.4 . 1.4 at New Delhi by.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to :-

1. Mr. Akash Kalra (Partner) M/s United Coffee House, 15-E, Connaught Place, New Delhi

2. The DEO (Restt.)
Deptt. of Excise, Entertainment and Luxury,
Govt. of NCT of Delhi.

L & N Block, Vikas Bhawan, I.P. Estate, New Delhi.

United Coffee House

es taque 1 1 23.04.14

11-10

INSPECTION REPORT

1. Name & address of the building: M/s United Coffee House, 15-E,

Connaught Place New Delhi.

2. Building is comprised of : Ground +2 Upper floors Restaurant is

at Ground & Mezzanine floor

3. Type of Occupancy : Restaurant

4. Type of Case : Renewal

5. Details of Previous NOC Letter: F6/MS/DFS/2011/ EH/1313 dated

24-06-2011

6. Fire Safety directive letter No : -Nil-

7. Date of Inspection : 16.04.2014

8. Name of the Inspecting officers: Gurmukh Singh (DO)

9. Name and designation of Officer:

from the building side : Mr. Rakesh Chander

10. Year of Construction

11. Applicant's letter No : -Nil - dated 05.04.2014

S.NO.	Minimum Standards on fire	Existing	Provided at	Remarks		
	prevention and fire safety U/R33	Requirement	Site	MR/NMR		
1	Access to building					
	Road width	9 Mtrs	9 Mtrs.	MR		
	Gate width	NA	Directly from	MR		
			road			
	 Width of internal road 	NA	NA	NA		
2	Number, Width, Type and Arrangement of Exits					
	a. Number of Staircases					
	Upper Floor	2 Nos	2 Nos.	MR		
	Basement	NA	NA .	NA		
	B. Width of Staircases					
	Upper Floor	1.2 Mtr & .70	1.2 Mtr.& .70	MR (old		
		Mtr	Mtr	case)		
	Basement	NA	NA	NA		
	c. Protection of exits					
	Fire check door	NA	NA	NA		
	 Pressurization 	NA	NA	NA		
	e. No. of continuous staircases to terrace	NA	NA	NA		

g. Width of Corridor	NA	NA	NA ×		
h. Door Size	1.0 Mtr.	1.0 Mtr.	MR		
Compartmentation.					
Fire check door	NA	NA	NA		
 Sealing of electrical shafts 	NA	NA	NA		
 Fire rating of shaft door 	NA	NA	NA		
Water curtain	NA	NA	NA		
Fire Dampers	NA	NA	NA		
Smoke Management System.					
Basement	NA	NA	NA		
Upper floor	Required	Provided	MR		
Fire Extinguishers					
Total numbers	4Nos.	8 Nos.	MR		
• types	Co2 &Wco2	Co2 &Wco2	MR		
	Required	Provided	MR		
First-aid-Hose Reels.					
Total numbers at each floor	Required	Provided	MR		
	30 Mtr.	30 Mtr.	MR .		
			MR		
Trouble diameter					
Automatic fire detection and alarming system					
		NA	NA		
			NA		
			NA		
2004.01 of repeater pariet					
Alternate source of power	NA	NA	NA		
Hooter's location	NA	NA	NA		
MOEFA	Required	Provided	MR		
	NA	NA	NA		
Automatic Sprinkler System.	Required	Provided	MR		
Basement	NA	NA	NA		
upper floor	Required	Provided	MR		
 sprinkler above false ceiling 	NA	NA	NA		
size of riser/down-comer	NA	NA	NA		
	NA	NA	NA		
Number of hydrants per floor	INA				
floor			NA		
	NA NA	NA NA	NA NA		
	h. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers Smoke Management System. Basement Upper floor Fire Extinguishers Total numbers types ISI marking First-aid-Hose Reels. Total numbers at each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarmi Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooter's location MOEFA Public address System. Automatic Sprinkler System. Basement upper floor sprinkler above false ceiling Internal Hydrants	n. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers Smoke Management System. Basement Upper floor Fire Extinguishers Total numbers Strict aid-Hose Reels. Total numbers at each floor Length of hose reel hose Nozzle diameter Type of detectors Location of main panel Location of repeater panel Alternate source of power Automatic Sprinkler System. Automatic Sprinkler System. Automatic Sprinkler System. Automatic Sprinkler above false ceiling Internal Hydrants	h. Door Size Compartmentation. Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers NA Smoke Management System. Basement Upper floor Fire Extinguishers Total numbers Sypes Show Hose reel hose Nozzle diameter Automatic fire detection and alarming system. Type of detectors Location of repeater panel Alternate source of power Automatic Sprinkler System. Hooter's location Required Required Required Provided Required Provided Provided Provided NA NA NA NA NA NA NA NA NA NA		

	Hose Box	NA	NA	NA
13	Pumping Arrangements.			
	Ground Level	NA	NA	NA
	➢ Discharge of main Pump	NA	NA	NA
	➤ Head of Main Pump	NA	NA	NA
	➤ Number of main pumps	NA	NA	NA
	> Jockey pump out put	NA	NA	NA
	➤ Jockey pump head	NA	NA	NA
	➤ Standby pump out put	NA	NA	NA
	➤ Standby pump Head	NA	NA	NA
	➤ Auto Starting /Manual stopping	NA	NA	NA
	➤ Pump House Access	NA	NA	NA
2.1.1	Terrace Level	Required	Provided	MR
	➤ Discharge of pump	180 LPM & 450 LPM	180 LPM & 450 LPM	MR
	➤ Head of the Pump	30Mtrs	30Mtrs	MD
	> Power supply			MR
	> Auto Starting of pump	Required Required	Provided	MR
	Auto Starting of pump	Required	Provided	MR
14	Captive Water Storage for Fire Fighting.	*	CERTAIN S	
	19.19.			
	 Underground tank capacity 	NA	NA	NA
	➤ Draw-off connection	NA	NA	NA
	➤ Fire service inlet	NA	NA	NA
	> Access to tank	Required	Provided	MR
	Overhead Tank capacity	5,000 Ltrs.	5,000 Ltrs.	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.	NA		
	Pressurization of Lift Shaft	NA	NA	NA
	Pressurization of Lift lobby	NA	NA	NA
	Communication in lift car	NA	NA	NA
	Firemen's grounding switch	NA	NA	NA
	Lift Signage	NA	NA	NA
17	Standby power supply	Required	Provided	MR
18	Refuge Area.	NA	NA	NA
	Total area	NA	NA	NA
	Location	NA	NA	NA
19	Fire Control Room	NA	NA	NA
10		NA	NA	NA
	Bottottoi oyotoini parioi			
	Flow switch panel	NA	NA	NA
	PA system panel	NA	NA	NA

h

	Battery backup	NA	NA		
	Building Floor Plans	NA	NA		
20	Special Fire Protection systems fire protection of special Risks, if any:		NA	NA	

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no.F6/MS/DFS/2011/EH/1313 dated 24.06.2011, renewal, under rule 35 of the Delhi Fire Service Rule 2010, is recommended.

Name - Gurmukh Singh

Designation (DO)