FORM H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI
HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6|DFs|m3|2014|w2|523

Dated: 28/04/14

FIRE SAFETY CERTIFICATE

Certified that the City Square Mall located at Plot No. 7 & 8, District Centre, Shivaji Palace, Raja Garden, New Delhi - 110027 comprised of 2 Basement + Ground + 4 Upper Floors was issued FSC vide Letter No. F6/DFS/MS/2010/2188 dated 23-07-2010. The premises was re inspected by the officers concerned of this department on 11-04-2014 in the presence of Mr. Arvind Kapur (General Manager) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule. 2010 and that the premises is fit for occupancy class "Mercantile" Group F with effect from 28 / 04 / 19 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules. 2010.

(Santokh Singh) Chief Fire Officer, Ph: 011 - 23414250

Copy to:

Sh. Arvind Kapoor (General Manager).
 City Square Mall, Plot No. 7, 8.
 Shivaji Palace, District Centre, Raja Garden. New Delhi.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on way dfs delhigovi nic in.

Re inspection to see the compliance of shortcomings communicated vide letter no. F6/DFS act 2007/MN dated 17-09-2013.

INSPECTION REPORT

1. Name & address of the building: City Square Mall, Plot No. 7, 8, Shivaji Palace, District Centre, Raja Garden, New Delhi.

2. Type of Occupancy

: Mall

3. Type of Case

: Renewal

4. Details of previous NOC

: Letter No. F6/DFS/MS/2010/2188 dated 23-07-2010

5. Fire Safety directives Letter No.: Letter No. F6/DFS/MS/BP/2004/341 dated 12-02-2004

6. Date of inspection

: 11-04-2014

7. Name of the Inspecting Officer: DO (West) & ADO (MN)

8. Name and designation of Officer

from the building side

: Sh. Arvind Kapur (General Manager)

9. Year of Construction

: 2006

10. Applicant's letter No.

: Nil Dated 08-03-2014

S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requirements	Provided at site	Remarks MR/NMR
1.	Access of building			
	 Road width 	30 m	Provided	MR
	 Gate width 	6 m	Provided	MR
	 Width of internal road 	6 m	Provided	MR
2.	Number, width, Type & Arrangem	ents of exits		
	a. Number of staircases			,
	 Upper floors 	3	Provided	MR
	 Basements 	5	Provided	MR ·
	b. Width of staircases		and the second s	7
	 Upper floors 	Old Case	Old Case	MR
	 Basements 	Old Case	Old Case	MR
	c. Protection of exits			
	 Fire check door 	Required	Provided	MR
	 Pressurization 	NR	NR	NR
	d. No of continuous staircase	Required	Provided	MR
	to terrace	Old Case	Old Case	MR
	e. Width Of Corridor f. Door Size	Old Case	Old Case	MR
3.	Compartmentation			
	Fire check door	Required	Provided (NR near lift lobby a it opens in atrium)	MR

	Sealing of electrical shafts	Required	Found Provided	MR			
	 Fire Rating of shaft door 	Required	Provided	MR			
	Water Curtain	Required	Provided	MR			
	Fire Dampers	Required	Provided at the	MR			
	·	recented	AHU				
	Smoke managements System			MAD			
	 Basements 	30 a/c per hour	Connected with	MR			
			Detection &				
		100	alarm system	MR			
	 Upper floors 	12 a/c per hour	Provided	IVIK			
	Fire Extinguishers		D : 1 - 1	MR			
	 Total numbers 	51 nos.	Provided				
	• Types	ABC, CO2 & WCO2	Provided	MR			
	 IS marking 	ISI marked	Provided	MR			
Ó.	First – Aid Hose Reels		D 111	MD			
	 Total numbers on each floor 	Required	Provided	MR			
	 Length of hose reel hose 	30 m	Provided	MR			
	 Nozzle diameter 	5 mm	Provided	MR			
7.	Automatic fire detection and alarm			2			
	Type of detectors	Smoke & Heat	Provided	MR			
	 Location of Main Panel 	Required	Provided	MR			
	· · · · · · · · · · · · · · · · · · ·	Required	Provided	MR			
	Location of Repeater Panel	Required	Provided	MR			
	 Alternate source of power 	Required	Provided	MR			
	 Hooters' Location 	recamed					
8.	MOEFA	Required	Provided	MR			
s. 9.	Public Address System	Required	Provided	MR			
9. 10.	Automatic Sprinkler System	Required	1107100				
10.	D	Required	Provided	MR			
		Required	Provided	MR			
	• Upper Floor	Required	Provided	MR			
	 Sprinkler above false ceiling 	recumed					
11.	Internal Hydrants	P-10-1					
	 Size of riser/down-comer 	150 mm	Provided	MR			
	 Number of hydrants per 	Required	Provided	MR			
	floor			1.40			
	 Hose Box 	Required	Provided	MR			
12.	Yard Hydrants						
	 Total number of hydrants 	Required	Provided	MR			
	 Hose Box 	Required	Provided	MR			
13.							
	Ground Level						
	A STATE OF THE STA	2850 lpm	Provided	MR			
	 Discharge of main pump 	2000 ipiii					
	5	60 m	Provided	MR			
	 Discharge of main pump Head of main pump Number of main pumps 	and the same of th	Provided Provided	MR MR			

,	Jockey pump head	60 m	Provided	MR		
	Standby Pump out put	2850 lpm	Provided	MR		
	Standby Pump Head	60 m	Provided	MR		
	Auto Staring/Manual stopping	Required	Provided	MR		
	Pump House Access	Required	Provided	MR		
	 Terrace level 		to the product of the part to the			
	Discharge of pump	NR	NR	NR		
	Head of the pump	NR	NR	NR		
	Power supply	NR	NR	NR		
	Auto starting of pump	NR	NR	NR		
14.	Captive water Storage for fire fighting					
	 Under ground tank capacity 	1,00,000 litres	Provided	MR		
	Draw of connection	Required	Provided	MR		
	Fire service inlet	Required	Provided	MR		
	Access to tank	Required	Provided	MR		
	 Overhead Tank capacity 	30, 000 litres	Provided	MR		
15	Exit Signage	Required	Provided	MR		
16.	Provision of Lifts					
	Pressurization of Lift Shaft	NR	NR	NR		
	Pressurization of lift lobby	NR	NR	NR		
	Communication in lift Car	Required	Provided	MR		
	Fireman's Grounding Switch	Required	Provided	MR		
	Lift Signage	Required	Provided	MR		
17.	Standby power supply	Required	Provided	MR		
18.	Refuge Area			2 10		
	Total area	Required	Provided	MR .		
	Location	Open Terrace	Provided	MR.		
19.	Fire control room					
	 Detector system panel 	Required	Provided	MR		
	Flow Switch Panel	Required	Provided	MR		
	PA System Panel	Required	Provided	MR		
	Battery backup	Required	Provided	MR		
	Building Floor Plans	Required	Provided	MR ·		
20.	Special Fire Protection Systems for Protection of special Risks, if	CO2 Flooding System for HT &	Provided	MR		
	any;	LT Panel				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/2010/2188 dated 23-07-2010 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the

Signature of the Inspecting Officer 17-4-14

Designation APO (MW)

Dy (Fo (on C)2) Designator A