GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

FIRE SAFETY CERTIFICATE

Certified that Chittaranjan Bhawan located at C-405A, Chittaranjan Park, New Delhi-110019 comprised of basement, ground & first floor was granted NOC by this department vide letter No. F.6/DFS/MS/2007/3602 dated 04-12-2007 except the area occupied by the bank. The premises was re-inspected by the officer concerned of this department on 31-03-2014 in presence of Mr. A.K Ghosh, Vice President & A.K.Chandra, Executive Secretary of the society and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class group-D(Assembly) with effect from 25/4// for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules,2010. This certificate is valid for the entire building except the area occupied by the bank.

Issued on 25/4/14 at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

2. The General Secretary, Deshbandhu Chittaranjan Memorial Society (Regd.), "Chittaranjan Bhawan", C-405A, Chittaranjan Park, New Delhi-110019.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: Chittaranjan Bhawan, C-405A, Chittaranjan Park, New

Delhi-110019.

2. Type of Occupancy

: Assembly

3. Type of Case

: Renewal

4. Details of previous NOC

: F.6/DFS/MS/2007/3602dated 04-12-2007

5. Fire Safety directives letter No

: F.6/MS/DFS/BP/92/1215 dated 39.06.1992.

6. Date of inspection

: 31.03.2014

7. Name of the Inspecting Officers

: M.K.Chattopadhyay, ADO(M. Road)

8. Name and designation of officers

from the building side

Mr. A.K Ghosh, Vice President & A.K.Chandra, Executive Secretary

9. Year of Construction

: 1991-92

10. Applicant's letter No.

: 130A/2012/part I dated 04.03.2014

S. No.	Minimum Standards on fire	NBC/BBI Requirement	2 To vided at Site	Zeman KS
1	Access to building		ų	MR/NMR
	Road width	06 mts	Provided	3.00
	Gate width	4.5 mts	Provided	MR
	Width of internal road	N/A	27/1	MR
	Number, Width, Type & Arrangement	of Emil	N/A	N/A
	a. Number of staircases	OI EXITS		
.	• Upper Floors	-	_	_
		02	Provided	MR
	Basements	02 + 01 ramp	Provided	MR
	b. Width of staircases	-	-	
	 Upper Floors 	1.20	1 22 1 20	-
	 Basements 	1.20 mts (og)		MR (old ca
C	c. Protection of exits	1.20 mts (oc	2.60, 1.22 mts + 01 ramp	MR(old c
	• Fire check door		-	
	• Pressurization	N/A	N/A	N/A
e.	. No. of continuous staircases to terrace	N/A	N/A	N/A
g	. Width of Corridor	02	02	MR
	Door Size	N/A	N/A	N/A
		N/A	N/A	N/A
	ompartmentation.			
	Fire check door	N/A	N/A	N/A

	MX6					
	• Sealing of electrical shafts	N/A	N/A			
v .	• Fire Rating of shaft door	N/A		N/A		
	Water Curtain Fire Day	N/A	N/A	N/A		
4	• Fire Dampers	N/A	N/A N/A	N/A		
7	smoke Wanagement System.		IN/A	N/A		
	BasementsUpper floors	30 a/c per l 12 a/c per l		vided MR		
5	Fire Extinguishers		N/A	N/A		
	Total numbersTypes	20	Provided	MR		
	IS marking	ABC, CO ₂ , Wo	CO ₂ Provided	MR		
6	First-Aid Hose Reels.	ISI marked	d Provided	MR		
	 Total numbers on each floor 			TAIK		
	• Length of hose reel hose	01	Provided	MR		
	Nozzle diameter	30 m	Provided			
7		5 mm	Provided	MR MR		
	me detection and alarming system.					
	Type of detectorsLocation of Main Panel	N/A	N/A	N/A		
		N/A	N/A	N/A		
	• Location of Repeater Panel	N/A	N/A			
	 Alternate source of power 	N/A	N/A	N/A		
	 Hooters' Location 	N/A		N/A		
8	MOEFA		N/A	N/A		
9 1	Public Address System.	Required	Provided	MR		
10 A	Automatic Sprinkler System.	N/A	N/A	N/A		
	• Basement					
	• Upper Floor	Required	Provided	MR		
	 Sprinkler above false ceiling 	N/A	N/A	N/A		
1 In	ternal Hydrants	N/A	N/A	N/A		
	Size of riser/down-comer	100				
	• Number of hydrants per floor	100 mm	Provided	MR		
8	• Hose Box	01	Provided	MR		
Yaı	d Hydrants.	01	Provided	MR		

hy

	Total must			N-7
	Total number of hydrantsHose Box	N/A	N/A	N/A
13	Pumping Arrangements.	N/A	N/A	N/A
	• Ground Level			
	Discharge of main Pump			
	Head of Main pump	N/A	N/A	N/A
		N/A	N/A	N/A
	rumps of main pumps	N/A	N/A	N/A
	tookey I amp out put	N/A	N/A	N/A
	vockey pump nead	N/A	N/A	N/A
	and by I ump out put	N/A	N/A	N/A
H . (1)	Standby Pump Head	N/A	N/A	N/A
	Auto Starting/ Manual stoppin	ng N/A	N/A	N/A
	Pump House Access	N/A	N/A	. N/A
	• Terrace level			
	Discharge of pump	900 LPM	Provided	MD
	Head of the pump	40 mts	Provided	MR
*	Power Supply	Required		MR
	Auto Starting of pump	Required	Provided	MR
. C	aptive Water Storage for fire fighting.	required	Provided	MR
81	 Underground tank capacity 	Not Required	40,000 lts	>T/A
	Draw-off connection	N/A		N/A
	Fire service inlet	N/A	N/A N/A	N/A
	Access to tank	Required	**	N/A
	Overhead Tank capacity	10,000 lts	Provided	MR
Ex	it Signage.		Provided	MR
	ovision of Lifts.	Required	Provided	MR
•	Pressurization of Lift Shaft	N/A	N/A	37//
•	Pressurization of Lift lobby	N/A	N/A	N/A
•	Communication In lift Car	N/A	IN/A	N/A

N/A

N/A

Communication In lift Car

Fireman's Grounding Switch

1

N/A

N/A

N/A

N/A

1.00 E	Lift Signage	N/A	N/A	N/A
17	Standby power supply	Required	Provided (D.G set 100 KVA)	MR
18	Refuge Area.	à		
	> Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19	Fire Control Room			
	Detector System Panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	· N/A
	PA System Panel	N/A	N/A	N/A
,• a	Batter backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	One ABC type fire extinguisher found provided near elect. panel	MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/2007/3602 dated 04-12-2007, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended except the area occupied by the bank,

DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Designation: - Asstt. Div. Officer (M.Rd)

114/14