## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

No. F6/DFS/as/school/2014/402/518

Dated: 25/04/19

## FIRE SAFETY CERTIFICATE

Certified that the Dashmesh Public School at C-Block, Vivek Vihar, Delhi-95, owned/occupied by Dashmesh Public School, comprising of ground plus two upper floors was granted NOC vide letter no. No.F.6/DFS/MS/2009/733 dated 17.03.2009. The school building was inspected by the officer concerned of this department on 18.04.2014 in the presence of Smt. Sarita Sexena (Principal) of the school and found that the school building have deemed complied with the fire prevention and fire safety requirements in accordance with the circular no.262-362 Dated 17.01.2005 issued by the Director of Education and found that the building is fit for occupancy class B "Educational Building" with effect from .2.5.../.29...[14...] for a period of three years, subject to conditions printed overleaf.

Issued on ..25../.a.y.../...... at New Delhi by

(Dr. G.C. Misra) CHIEF FIRE OFFICER DELHI FIRE SERVICE

<u>Tel:-</u> 011-23414333 E-Mail:- cfohq.dlfire@nic.in

61L

To,

The Principal Dashmesh Public School C-Block, Vivek Vihar, Delhi-95,

Copy to:-

The Director of Education GNCT of Delhi, Old secretariat <sup>6</sup> Delhi -54.

## - Conditions -

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in good working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 5. This Fire Safety certificate can not be treated in any case for regularizations of unauthorized construction if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

viday(cro col)

1. Name & address of the building: Dashmesh Public School at C-Block, Vivek Vihar, Delhi -95.

2. Building is comprised of

: Ground +2, upper floors.

3. Type of Occupancy

: Educational

4. Type of Case

Renewal

5. Details of Previous NOC letter: F.6/DFS/MS/2009/733 dated 17.03.2009

6. Fire Safety direction letter No : Circular No.262-362 Dated 17.01.2005 Director of

Education

7. Date of Inspection

: 26.03.2014 & 18.04.14

8. Name of the Inspecting officers: DO Virendra Singh

9. Name and designation of Officer:

from the building side

: Smt.Sarita Sexena (Principal)

10. Year of Construction

- :1980

11. Applicant's letter No

: DPS/No.64/514 dated 29.01.2014

0.	Minimum Standards on fire prevention	Old Circular Requirement	Provided at Site	Remarks			
	and fire safety U/R33	Requirement	Cito				
	Access to building	06 Mtrs.	15 Mtrs.	MR			
	Road width	N/A	N/A	N/A			
	Gate width     All the of internal road		N/A	N/A			
	Width of internal road	N/A	TWI				
)	Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases	02 Nos	02 Nos.	MR			
	<ul> <li>Upper Floor</li> </ul>	N/A	N/A	N/A			
	<ul> <li>Basement</li> </ul>	IN/A	147.				
	B. Width of Staircases	1.5 M	1.5 M & 1.15 N	MR			
	<ul> <li>Upper Floor</li> </ul>	N/A	N/A	N/A			
	Basement	14//3					
	c. Protection of exits  • Fire check door	N/A	N/A	N/A			
	Pressurization	N/A	N/A	N/A			
	e. No. of continuous staircases to	2 nos.	2 Nos.	MR			
	terrace	1.5 M	1.8 M	MR			
	g. Width of Corridor		1.0 Mtrs	MR			
	h. Door Size	1.0 Mtrs	1.0 10103				
3	Compartmentation.						
9			NI/A	N/A			
	Fire check door	N/A	N/A	N/A			
	<ul> <li>Sealing of electrical shafts</li> </ul>	N/A	N/A	N/A			
	Fire rating of shaft door	N/A	N/A	N/A			
	Water curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	14//			
4	Smoke Management System.		N.//A	NI/A			
	Basement	N/A	N/A	N/A			
	Upper floor	N/A	N/A	N/A			
5.	Fire Extinguishers 12 Nos MR						
-	Total numbers	12 Nos.	14 Nos.				
	• Types	ABC & Co2					
	IS marking	ISI marked	ISI marked	MR			
6	First-aid-Hose Reels.						
	Total numbers of each floor	1 no.	1 no.	MR			
	<ul> <li>Length of hose reel hose</li> </ul>	30 M	30 M	MR			
	Nozzle diameter	5 mm	5 mm	MR			

7	Automatic fire detection and alarming syst	em.		
	Type of detectors	N/A	N/A	N/A
	<ul> <li>Location of main panel</li> </ul>	N/A	N/A	N/A
	<ul> <li>Location of repeater panel</li> </ul>	N/A	N/A	N/A
	<ul> <li>Alternate source of power</li> </ul>	N/A	N/A	N/A
	Hooter's location	N/A	N/A	N/A
8	MOEFA	N/A	N/A	N/A
9	Public address System.	N/A	N/A	N/A
10	Automatic Sprinkler System.			-
	Basement	N/A	N/A	N/A
	upper floor	N/A	N/A	N/A
	sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants	Required	Provided	MR
11	size of riser/down-comer	100 MM	100 MM	MR
		1 No.	1 No.	MR
	Number of hydrants per floor	1 No.	1 No.	MR
	Hose Box	T NO.	T NO.	IVII
12	Yard Hydrants.			
	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
13	Pumping Arrangements.			
	Ground Level	N/A	N/A	N/A
	Discharge of main Pump	N/A	N/A	N/A
	> Head of Main Pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	> Jockey pump out put	N/A	N/A	N/A
	<ul> <li>Jockey pump head</li> </ul>	N/A	N/A	N/A
	<ul> <li>Standby pump out put</li> </ul>	N/A	N/A	N/A
	<ul><li>Standby pump Head</li></ul>	N/A	N/A	N/A
	<ul> <li>Auto Starting /Manual stopping</li> </ul>	N/A	N/A	N/A
7.1.1.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.	> Pump House Access	N/A	N/A	N/A
	Terrace Level	Required	Provided	MR
	> Discharge of pump	450 LPM	450 LPM	MR
	Head of the Pump	40 M	40 M	MR
	> Power supply	Required	Provided	MR
	, constagely	, toquii ou		3 8 6.
	Auto Starting of pump	Required	Provided	MR
14	Captive Water Storage for Fire Fighting.			
	<ul> <li>Underground tank capacity</li> </ul>	N/A	N/A	N/A
	Draw-off connection	N/A	N/A	N/A
	Fire service inlet	N/A	N/A	N/A
	Access to tank	N/A	N/A	N/A
	<ul> <li>Overhead Tank capacity</li> </ul>	5000 Ltrs.	5000 Ltrs.	MR
15	Exit Signage.	N/A	N/A	N/A
16	Provision of Lifts.			11
	<ul> <li>Pressurization of Lift Shaft</li> </ul>	N/A	N/A	N/A
	<ul> <li>Pressurization of Lift lobby</li> </ul>	N/A	N/A	N/A
	Communication in lift car	N/A	N/A	N/A
17.	Standby power supply	N/A	N/A	N/A
18	Refuge Area.	N/A	N/A	N/A
	Total area	N/A	N/A	N/A
	• Location	N/A	N/A	N/A
19	Fire Control Room	N/A	N/A	N/A
	Detector system panel	N/A	N/A	N/A
	Flow switch panel	N/A	N/A	N/A
	PA system panel	N/A	N/A	N/A
	<ul> <li>Battery backup</li> </ul>	N/A	N/A	N/A
5 (A) (A) (B) (S) (B) (B)	Building Floor Plans	N/A	N/A	N/A

NIU

20	Special Fire Protection systems for N/A N/A N/A						
	protection of special Risks, if any:	N/A	N/A	N/A			
				1	- 1		

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules. The renewal of NOC issued vide letter no. F.6/DFS/MS/2009/733 Dated 17.03.2009 is recommended.

Signature of the inspecting Office

Name:-Virendra Singh

Designation:-DO(ED)

Dy CFOCNDS