GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI- 110001

NO.F6/DFS/MS/EH/2014/SZ/ 593

DATED: 09/05/14

FIRE SAFETY CERTIFICATE

Certified that the M/s Swagat Restaurant at Plot No. C-8, Malviya Nagar, New Delhi 110017 is running at the ground floor of a building comprised of basement, ground plus three upper floors was granted NOC by this department vide letter No. F6/DFS/MS/EH/2011/22 dated 06.01.2011. The premises was re-inspected by the officer concerned of Delhi Fire Service on 23.4.2014 in the presence of Sh. Annappa (Manager) of the restaurant and observed that fire safety norms as required under Rule 33 of Delhi Fire Service Rules, 2010 have deemed complied and that the building / premises is fit for occupancy class-D "Assembly building Restaurant" with effect from 69/65/19 for a period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rule 2010...

Issued on ...o. §../.o.s.././y...... at New Delhi by

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service (011-23414333)

- Copy To:
 1. The DHO (South Zone), Office of Deputy Health Officer, M.C.D. Public Health Department, Green Park, New Delhi
- 2. The Manager, M/s Swagat Restaurant at Plot No. C-8, Malviya Nagar, New Delhi 110017

Conditions for the validity of fire safety certificate

- 1. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- 2. Building Sanctioning authority may verify any deviation with regard to construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- 3. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- 4. The basement shall be used strictly as per the provisions of Building Bye laws.
- 5. The owner/occupier shall submit a declaration every year in form 'K' provided in the first Fire Service Rules-2010. The form is schedule of Delhi www.dfs.delhiqovt.nic.in

me & address of the building pe of Occupancy pe of case stails of previous NOC re safety directives letter No ate of inspection ame of the inspecting Officers ame and designation of officers om the building side	M/s Swa Delhi110 Assemb Renewa F6/DFS Nil 23.04.2 D.O. (§	bly Building "D" val S/MS/EH/2011/2 2014 (South) D.P. Bha	Restauant 22 Dated 06.01		r, New		
pe of Occupancy pe of case stails of previous NOC re safety directives letter No rate of inspection rame of the inspecting Officers rame and designation of officers rame the building side	Pelhi110 Assemb Renewa F6/DFS Nil 23.04.2 D.O. (S	bly Building "D" val S/MS/EH/2011/2 2014 (South) D.P. Bha	Restauant 22 Dated 06.01	1.2011			
pe of Occupancy pe of case stails of previous NOC re safety directives letter No rate of inspection rame of the inspecting Officers rame and designation of officers rame the building side	Renewa F6/DFS Nil 23.04.2 D.O. (S	2014 (South) D.P. Bha	22 Dated 06.01				
pe of case stails of previous NOC re safety directives letter No ate of inspection ame of the inspecting Officers ame and designation of officers om the building side	F6/DFS Nil 23.04.2 D.O. (\$	S/MS/EH/2011/2 2014 (South) D.P. Bha					
etails of previous NOC re safety directives letter No rate of inspection reme of the inspecting Officers reme and designation of officers reme the building side	Nil 23.04.2 D.O. (S	2014 (South) D.P. Bha					
re safety directives letter No rate of inspection rame of the inspecting Officers rame and designation of officers re safety directives letter No re safety	Nil 23.04.2 D.O. (S	2014 (South) D.P. Bha					
ate of inspection ame of the inspecting Officers: ame and designation of officers om the building side	23.04.2 D.O. (\$	(South) D.P. Bha	ardwaj , ADO [1	
ame of the inspecting Officers : ame and designation of officers om the building side	D.O. (S	(South) D.P. Bha	ardwaj, ADO L	the same of the sa	20 04 2014		
ame and designation of officers om the building side	7			D.O. (South) D.P. Bhardwaj , ADO D.B. Mukherjee			
ame and designation of officers om the building side	Sh. Aı	() ()					
om the building side	1	nnapa (Manage	er),	17			
				4			
(notruction				(Resturant ru	nning at	ground	
ear of construction	Nil		01.02.2014	floor)			
Applicant's letter No.	NRC	Requirement	Provid	ded at site	Rema		
Minimum Standards on fire prevention at	Va INDO	Nogan			INIT	TAIL.	
fire safety U/R 33	-				IMB		
Access to building	Reg	uired		ed			
	N/A		N/A				
2) Gate width	N/A		N/A				
3) Width of International	exits		T				
Number, width Type & a			NI/A		N/A		
a. Number of Standard	N/A	A .	IN// X		NI/E		
1. Upper floors	N//	Δ	N/A		IN/F	<u> </u>	
2. basements	15/-	1.				Λ	
	N/	/A	N/A			-	
1. Upper floors			N/A				
2. basements					- N/	A	
	N	,/ <u>A</u>			N/	/A	
a Prescurization							
2. Pressurization			N/A	V 10 10 10 10 10 10 10 10 10 10 10 10 10			
	-		1.04, 0.68	Mtrs Provided	M	IR	
		OW EXIL	- 1				
		NIIA	N/A			1/A	
1 Fire check door	F		N/A			N/A	
2. Sealing of electrical shafts	-		N/A			N/A N/A	
3. Fire Rating of shaft door	-		N/A			N/A N/A	
4. water curtain	-	N/A	N/A		1.	N// N	
5. Fire dampers		9	1.1/4		n 191	N/A	
		30 a/c per hour			7		
basement		12 a/c per noui	Provided	1		MR	
and floors					24	1	
	-		6 Nos			MR	
	2.5	- V		/ater Co2	* .	MR	
	12	-	Yes			MR	
		ISI				MI	
6 First-Aid Hose Reels.		One		Provided		M	
total numbers on each floor			q	Provided	1 1	M	
Length of Hose reel hose				Provided		14.	
N. F. A. S.	Access to building 1) Road width 2) Gate width 3) Width of internal road Number, width Type & arrangement of e a. Number of staircases 1. Upper floors 2. basements b. Width of staircase 1. Upper floors 2. basements c. Protection of exits 1. Fire check door 2. Pressurization d. No. of continuous staircase to e. Width of corridor f. Door size Compartmentation. 1. Fire check door 2. Sealing of electrical shafts 3. Fire Rating of shaft door 4. water curtain 5. Fire dampers Smoke Management system. basement upper floors Fire Extinguishers total numbers Types ISI marking First-Aid Hose Reels.	Minimum Standards on the prevention designer safety U/R 33 Access to building 1) Road width 2) Gate width 3) Width of internal road N/A Number, width Type & arrangement of exits a. Number of staircases 1. Upper floors 2. basements b. Width of staircase 1. Upper floors 2. basements c. Protection of exits 1. Fire check door 2. Pressurization d. No. of continuous staircase to e. Width of corridor f. Door size Compartmentation. 1. Fire check door 2. Sealing of electrical shafts 3. Fire Rating of shaft door 4. water curtain 5. Fire dampers Smoke Management system. basement upper floors Fire Extinguishers total numbers Types ISI marking 6 First-Aid Hose Reels. total numbers on each floor Length of Hose reel hose	Minimum Standards on the prevention and fire safety U/R 33 Access to building 1) Road width A) Gate width A) Width of internal road Number, width Type & arrangement of exits a. Number of staircases 1. Upper floors 2. basements b. Width of staircase 1. Upper floors 2. basements c. Protection of exits 1. Fire check door 2. Pressurization d. No. of continuous staircase to e. Width of corridor f. Door size Compartmentation. 1. Fire check door 2. Sealing of electrical shafts 3. Fire Rating of shaft door 4. water curtain 5. Fire dampers Smoke Management system. basement upper floors Fire Extinguishers total numbers Types ISI marking first-Aid Hose Reels. total numbers on each floor Length of Hose reel hose Nozzle Diameter SMM	Minimum Standards on fire prevention and fire safety U/R 33 Access to building 1) Road width 2) Gate width 3) Width of internal road N/A Number, width Type & arrangement of exits a. Number of staircases 1. Upper floors 2. basements b. Width of staircase 1. Upper floors 2. basements c. Protection of exits 1. Fire check door 2. Pressurization d. No. of continuous staircase to e. Width of corridor f. Door size Compartmentation. 1. Fire check door 2. Sealing of electrical shafts 3. Fire Rating of shaft door 4. water curtain 5. Fire dampers Smoke Management system. basement upper floors Fire Extinguishers total numbers Types ISI marking First-Aid Hose Reels. total numbers on each floor Length of Hose reel hose N/A N/A N/A N/A N/A N/A N/A N/A N/A N/	Minimum Standards on tire prevention. If re safety U/R 33 Access to building 1) Road width 2) Gate width 3) Width of internal road Number, width Type & arrangement of exits a. Number of staircases 1. Upper floors 2. basements b. Width of staircase 1. Upper floors 2. basements c. Protection of exits 1. Fire check door 2. Pressurization d. No. of continuous staircase to e. Width of corridor f. Door size Compartmentation. 1. Fire check door 2. Sealing of electrical shafts 3. Fire Rating of shaft door 4. water curtain 5. Fire dampers Smoke Management system. basement Upper floors Fire Extinguishers total numbers Itotal numbers on each floor Length of Hose reel hose Nozzle Diameter N/A N/A N/A N/A N/A N/A N/A N/A N/A N/	MR / MR	

	Automatic fire detection and alarming syster	n:-		T
	Type of detectors	N/A	N/A	1
	ocation of Main Panel	N/A	N/A	N/A
	ocation of Repeater panel	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
1	hooter's location	N/A	N/A	N/A
	MOEFA	Required	Provided	MR
	Public Address System.	N/A	N/A	N/A
	Automatic Sprinkler System.		•	1 1/0
	basement	N/A	N/A	N/A
	upper floors	Required	Provided (Ground)	MR
	sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			1 115
	Size of riser/down-corner	100 MM	Provided	MR
	Number of Hydrants per floor	One	Provided	MR
	hose Box	One	Provided	MR
12	Yard Hydrants.			
	total number of hydrants	N/A	N/A	N/A
	hose box	N/A	N/A	N/A
13	Pumping arrangements			1
	1. Ground level			
	a. Discharge of main Pump	N/A	N/A	N/A
	b.Head of main pump	N/A	N/A	N/A
	c.Number of main pumps	N/A	N/A	N/A
	d.jockey pump out put	N/A	N/A	N/A
	e.jockey pump head	N/A	N/A	N/A
	f. Standby Pump output	N/A	N/A	N/A
	g.Stanby Pump head	N/A	N/A	N/A
	h.Auto Starting/Manual stopping	N/A	N/A	N/A
	pump house access	N/A	N/A	N/A
	2.Terrace level	**		
	a. Discharge of pump	450 & 180 LPM	Provided	MR
	b. head of the pump	35 Mtr	Provided	MR
	c. Power supply	Required	Provided	MR
		Required	Provided	MR
4.4	d. Auto starting of pump			
14	Captive water storage for fire fighting 1. Underground tank capacity	N/A	N/A	N/A
	a. Draw-off connection	N/A	N/A	N/A
	The state of the s	N/A	N/A	N/A
	b. fire service inlet	N/A	N/A	N/A
	c.Access to tank	5000 Ltrs	Provided	MR
	Over head tank Capacity	Required	Provided	MR
15	Exit Signage.	1,09202		
16	Provision of lifts.	N/A	N/A	N/A
	a. Pressurization of lift shaft	N/A	N/A	N/A
	b. pressurization of lift lobby	N/A	N/A	N/A
	c. communication in lift car	N/A	N/A	N/A
	d. Fireman's grounding switch	N/A	N/A	N/A

	Standby power supply	Required	Provided	MR				
18	Refuge Area.							
	total area	N/A	N/A	N/A				
	location	N/A	N/A	N/A				
19	Fire control room							
	a. detector system Panel	N/A	N/A	N/A				
	b. Flow switch Panel	N/A	N/A	N/A				
	c. PA system Panel	N/A	N/A	N/A				
	d. Batter backup	N/A	N/A	N/A				
	e. Building floor plans	N/A	N/A	N/A				
20	Special Fire Protection systems for protection of special risks, if any: N/A							

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules of NOC issued vide letter no. **F6/DFS/MS/EH/2011/22 Dated 06.01.2011** renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Accordingly DFA is put up for your approval and signature please.

Signature of the Inspecting Officer
Name D.P. BHARDWAJ

Designation:- D.O. (South)

Signature of the Inspecting Officer

Name

D.B. Mukherjee

Designation:- A.D.O. (BCP)