GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. F6/OFS/015/2014/ w2/567

Dated: 07 / 55 /2014

FIRE SAFETY CERTIFICATE

Certified that M/s Sidhi Cosmetics, D-259, Sector-3, DSIDC Bawana, Delhi-110039 comprised of G.F of premises Basement + Ground + One upper floor owned/occupied by M/s Sidhi Cosmetics have complied with the fire prevention and fire safety requirement in accordance with rule 33 of the Delhi Fire Service Rules, 2010, and verified by the officer concerned of Fire Service on 24/04/2014 in the presence of Sh. Kashish Madaan and that the building /premises is fit for occupancy Industrial G-2 (ii) building with effect from 57/55/2014 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

- 1. Means of escape shall not be kept locked or bolted from outside and shall be easily open able by guests in an event of emergency.
- 2. All employees shall be acquainted with the use and maintenance of all the fire fighting installation/equipments.
- 3. The fire suppression / protection arrangements provided in the guest house are to minimize losses, if maintained in good working condition. These systems cannot give any guarantee that there will be no fire or losses in the event of one.
- 4. Any loss of life and property due to non-functional of fire safety arrangements and other installations shall be the responsibility of the licensee.
- 5. This report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.Delhigovt.nic.in

Issued on ... o. 7./o.5././y ... at New Delhi.

(SANTOKH SINGH) Chief Fire Officer Delhi Fire Service Ph: 011-23414250 cfowz.dlfire@nic.in

Copy to:-

1. M/s Sidhi Cosmetics, D-259, Sector-3, DSIDC Bawana, Delhi-110039.

2. The Assistant Drugs Controller & Licensing Authority, Govt. of NCT of Delhi, F-17, Karkardooma, New Delhi-110032

B+ Sr. + one + two rooms.

	. INSPECTION	JN REPORT			
 3. 4. 6. 7. 8. 	Type of Case : New Ca Details of previous NOC :	se/Renewal () NIL NBG Past 24.4.14 ADD (BW) Kashesh	Esctor Gr. H	rop.	
۸	let Area-150m2 CA-4	20 haz			
٧.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR	
1	Access to building				
1	Road width	Auesseble	Accessable	MR	
	Gate width	Here of the second			
	Width of internal road				
2	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases		f. for Gr. floor	only)	
		(1-)0 10-			
	Upper Floors Personners		1.	-	
	Basements Width of staircases				
	Upper Floors	_	1.12 mts	/	
	Basements		1-12 mtr	- /	
	c. Protection of exits				
91	Fire check door				
	Pressurization		- 888 <u>- 13 1</u>		
	e. No. of continuous staircases to terrace			-	
	g. Width of Corridor				
	h. Door Size	2 exit	1.12 Mtz +	mr.	
3	Compartmentation.	2.21			
-	Fire check door				

	0.11			
	Sealing of electrical shafts			
	Fire Rating of shaft door			
	Water Curtain		HIA	
	Fire Dampers			
4	Smoke Management System.		1	
	Basements	30 a/c per hour		
	Upper floors	12 a/c per hour	Alla	
٠			Aldiu to at-	
5	Fire Extinguishers			
	Total numbers	7 ABC	12	MR
	• Types	ISI marked	ABC	WR,
	IS marking		Yes	me -
6	First-Aid Hose Reels.		1 / 2	ME
	Total numbers on each floor	one	P.	MR,
	Length of hose reel hose	30 m	P	MR.
	Nozzle diameter	5 mm	0	7
7	Automatic fire detection and alarming s	The property of the property of the		MR
	Type of detectors	J.		
	 Location of Main Panel 		• •	
	Location of Repeater Panel			
		GRANCE SOLD SERVICE		
	Alternate source of power		771	State Co.
0	Hooters' Location			
8	MOEFA			
9	Public Address System.			
10	Automatic Sprinkler System.			
	Basement	R	I P	MR.
	Upper Floor	R	· P .	MR -
	Sprinkler above false ceiling			
1.1	Internal Hydrants			
	Size of riser/down-comer			
	Number of hydrants per floor			
10	Hose Box		MA	
12	Yard Hydrants.		· LaKinest	
	Total number of hydrants			- 2 8
	Hose Box		930 8	

3	Pumping Arrangements.			
\dashv	Ground Level			
	Discharge of main Pump	n 2		
	> Head of Main pump			
	> Number of main pumps		/.	
	> Jockey Pump out put			
	> Jockey pump head		.18	
	> Standby Pump out put		131	
	> Standby Pump Head			•
	 Auto Starting/ Manual stopping Pump House Access 			
	Terrace level			41.00
	> Discharge of pump	900 Cd M	<i>Y</i> .	MR
	➤ Head of the pump	40 M	<i>P</i> ·	- K
	> Power Supply			44.0
	> Auto Starting of pum	R	Ρ,	MR
14 .	Captive Water Storage for fire fighting.			
	Underground tank capacity	2		
	> Draw-off connection		114	
	> Fire service inlet		1	
	> Access to tank			
	Overhead Tank capacity	10,000 lts	P	MR
15	Exit Signage.	. R	P	MR -
16	Provision of Lifts.			
	Pressurization of Lift Shaft			/.
	Pressurization of Lift lobby		*	
	Communication In lift Car			
	Fireman's Grounding Switch			
	Lift Signage			
17	Standby power supply		1/4	
18.	Refuge Area.			
	> Total Area		1	
į.	> Location	. /	,	
19	Fire Control Room			
	Detector System Panel			

	Flow Switch Panel		•	
	PA System Panel	.:		
	Batter backup		Alk	
	Building Floor Plans			
20	Special Fire Protection Systems for Protection of special Risks, if any:			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer

Name

Designation

Do Wol

Signature of the Inspecting Officer

Name

Designation

ADO BW