GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DF5/MS/EH/2014/W2/628 Dated: 22/05/2014

FIRE SAFETY CERTIFICATE

Certified that the Punjabi By Nature at Premises No. 39, NWA, Ground Floor, Club Road, Punjabi Bagh, New Delhi is comprised of ground floor + 2 upper floors owned/occupied by AR Fisheries Pvt. Ltd. have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Fire Service on 07.05.2014 in the presence of Mr. Tarak and that the building/premises is fit for occupancy class "Assembly" with effect from .2.2.../........../2014 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Following fire safety directives must be adhered to:-

- 1) All the means of escape shall be kept free of all type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3) All the fire fighting equipment shall be maintained in perfect working condition all the time and lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4) Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.
- 5) Basement shall be used as per NBC.
- 6) This NOC may not be treated in any case for regularizations of unauthorized construction, if any.
- 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs. delhigovt. nic.in

Santokh Singh Chief Fire Officer Delhi Fire Service

E-mail: cfowz.dlfire@nic.in Phone: 011-23414250

Ola

Copy to:

- 1. Mr. Tarak, Punjabi By Nature at Premises No. 39, NWA, Ground Floor, Club Road, Punjabi Bagh, New Delhi-11--26
- 2. Dy. Health Officer, South Municipal Corporation, Public Health Department, West Zone Vishal Enclave, New Delhi-110015

Ground = Restaurant

two upper floor = Residential

1. Name &address of the building : Punjabi By Nature, Premises No. 39, NWA, Ground Floor, Club

Road, Punjabi Bagh, New Delhi (Building = G+2 upper floors)

Type of Occupancy : Class-D Assembly

3. Type of Case : New

4. Details of previous NOC : Nil

5. Fire Safety directives letter No. : Nil

6. Date of inspection : 07.05.2014

7. Name of the Inspecting Officers : Divisional Officer Sunil Chawdhary

8. Name and designation of officers

From the building side : Mr. Tarak

9. Year of Construction

10. Applicant's letter No. : 688/DHO/WZ/2014 dated 25/04/2014

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

| S. | Minimum Standards on fire | BBL | Provided at site | Remarks MR/NMR | |
|-----|--|-------------------|------------------|-------------------|--|
| No. | Prevention and fire safety U/R 33 | Requirement | | IVINITALIA | |
| 1. | Access to building | | | | |
| | Road width | 09mtrs | 12 mtr | M.R. | |
| | Gate width | N.R. | N.R. | N.R. | |
| | Width of internal road | N.R. | N.R. | N.R. | |
| 2. | Number, Width, Type & Arrangement of Exits | | | | |
| | Ground floor only | | | | |
| | a. Number of staircases | | | | |
| | Upper Floors | N.R. | N.R. | N.R. | |
| | | N.R. | N.R. | N.R. | |
| | Basement | | | | |
| | b. Width of staircases | | | | |
| | Upper Floors | N.R. | N.R. | N.R. | |
| | Basement | N.R. | N.R. | N.R. | |
| | c. Protection of exits | Ground floor only | | | |
| | Electrical deser | N.R. | N.R. | N.R. | |
| | Fire check doorPressurization | N.R. | N.R. | N.R. | |

| | d. No. of continuous staircases | N.R. | N.R. | N.R. | | |
|----|--|----------------------------|----------|------|--|--|
| | to terrace | N.R. | N.R. | N.R. | | |
| | e. Width of Corridor | 2 doors of 2 mtr width | | | | |
| | f. Door size | each | Provided | M.R. | | |
| 1 | Compartmentation. Ground floor only | | | | | |
| - | | N.R. | N.R. | N.R. | | |
| | Fire check door | N.R. | N.R. | N.R. | | |
| | Sealing of electrical shafts | N.R. | N.R. | N.R. | | |
| | Fire Rating of shaft door | N.R. | N.R. | N.R. | | |
| | Water Curtain | N.R. | N.R. | N.R. | | |
| | Fire Dampers | | | | | |
| | Smoke Management System. | | | | | |
| | Basements | N.A | N.A | N.A | | |
| | Upper floors | required | Provided | M.R. | | |
| 5. | Fire Extinguishers | | - 15 | | | |
| | Total numbers | 04 | 08 | M.R. | | |
| | • Types | ABC & CO ₂ type | Provided | M.R. | | |
| 2 | IS marking | ISI marks required | provided | M.R. | | |
| 5. | First-Aid Hose Reels. | | | | | |
| | Total numbers on each floor | 1 | Provided | M.R. | | |
| | Length of hose reel hose | required | Provided | M.R. | | |
| | Nozzle diameter | required | Provided | M.R. | | |
| 7. | Automatic fire detection and alarming system. | | | | | |
| | Type of detectors | N.R. | N.R. | N.R. | | |
| | Location of Main Panel | N.R. | N.R. | N.R. | | |
| | | N.R. | N.R. | N.R. | | |
| | Location of Repeater Panel | N.R. | N.R. | N.R. | | |
| | Alternate source of power | N.R. | N.R. | N.R. | | |
| | Hooter's Location | | | 1 | | |

| 8. | MOEFA | Required | Provided | M.R. | |
|-----|-------------------------------|------------|----------|------|--|
| 9. | Public Address System. | N.R. | N.R. | N.R. | |
| 10. | Automatic Sprinkler system | | | | |
| | Basement | N.R. | N.R. | N.R. | |
| | Upper Floor | N.R. | N.R. | N.R. | |
| | Sprinkler above false ceiling | N.R. | N.R. | N.R. | |
| 11. | Internal Hydrants | × . | | | |
| | Size of riser/down-comer | Down-comer | Provided | M.R. | |
| | Number of hydrants per floor | 1 | Provided | M.R. | |
| | Hose Box | 1 | Provided | M.R. | |
| 12. | Yard Hydrants. | | | | |
| | Total number of hydrants | N.R. | N.R. | N.R. | |
| | Hose Box | N.R. | N.R. | N.R. | |
| 13. | Pumping Arrangements. | | | | |
| | Ground Level | | | | |
| | > Discharge of main pump | N.R. | N.R. | N.R. | |
| | ➤ Head of Main pump | N.R. | N.R. | N.R. | |
| | > Number of main pumps | N.R. | N.R. | N.R. | |
| | > Jockey Pump out put | N.R. | N.R. | N.R. | |
| | > Jockey pump head | N.R. | N.R. | N.R. | |
| | > Standby pump out put | N.R. | N.R. | N.R. | |
| | > Standby pump Head | N.R. | N.R. | N.R. | |

| Auto Starting/Manual stopping | N.R. | N.R. | N.R. |
|--------------------------------------|---|---|---|
| | N.R. | N.R. | N.R. |
| Terrace level | | | |
| Discharge of pump | 450 LPM | Provided | M.R. |
| > Head of the pump | 40 mtr | Provided | M.R. |
| > Power supply | Required | Provided | M.R. |
| > Auto Starting of pump | required | Provided | M.R. |
| Captive Water Storage for fire fight | ing. | | and the desired of the service of the control of the control of the control of the service desired and and addition where the control of the |
| Underground tank capacity | N.R. | N.R. | N.R. |
| > Draw -off connection | N.R. | N.R. | N.R. |
| ➤ Fire service inlet | N.R. | N.R. | N.R. |
| > Access to tank | N.R. | N.R. | N.R. |
| > Overhead Tank Capacity | 10 000 ltrs | 10 000 ltrs | M.R. |
| Exit Signage. | Required | Provided | M.R. |
| Provision of Lifts | | | |
| Pressurization of Lift Shaft | N.A. | N.A. | N.A. |
| Pressurization of Lift lobby | N.A. | N.A. | N.A. |
| Communication In lift Car | N.A. | N.A. | N.A. |
| Fireman's Grounding Switch | N.A. | N.A. | N.A. |
| Lift Signage | N.A. | N.A. | N.A. |
| Standby power supply | Required | Provided | M.R |
| Refuge Area | | | |
| > Total Area | N.R. | N.R. | N.R. |
| | N.R. | N.R. | N.R. |
| | Pump Hose Access Terrace level Discharge of pump Head of the pump Power supply Auto Starting of pump Captive Water Storage for fire fight Underground tank capacity Draw -off connection Fire service inlet Access to tank Overhead Tank Capacity Exit Signage. Provision of Lifts Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area | stopping Pump Hose Access Terrace level Discharge of pump Head of the pump Head of the pump Auto Starting of pump Captive Water Storage for fire fighting. Underground tank capacity Draw -off connection Fire service inlet Access to tank Overhead Tank Capacity Exit Signage. Provision of Lifts Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Required N.R. N.R. N.R. N.A. N.A. N.A. N.A. N.A. N.A. N.A. N.A. N.A. Required Required | stopping Pump Hose Access Terrace level Discharge of pump Head of the pump Mutr Provided Captive Water Storage for fire fighting. Underground tank capacity N.R. N.R. Praces to tank N.R. N.R. N.R. N.R. Poverhead Tank Capacity Exit Signage. Provision of Lift Shaft Pressurization of Lift Shaft N.A. Provided Refuge Area |

| 19. | Fire Control Room | | | |
|-----|--|------|------|------|
| | > Detector System Panel | N.R. | N.R. | N.R. |
| | > Flow Switch Panel | N.R. | N.R. | N.R. |
| | > PA system Panel | N.R. | N.R. | N.R. |
| | ➤ Batter backup | N.R. | N.R. | N.R. |
| | Building Floor plans | N.R. | N.R. | N.R. |
| 20. | Special Fire Protection Systems for Protection of special Risks, if any: | N.R. | N.R. | N.R. |

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/.

Signature of the Inspection Officer

Signature of the Inspection Officer

Name Sunil Chawdhary

Designation

Name

Designation D.O. (M.N.)

22-5-14.