GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. F6/DFS/MS/2014/WZ/ 665

Dated:30 / 05 /2014

FIRE SAFETY CERTIFICATE

Certified that North Gate Orbit Plaza, Gujranwala town, Delhi-110009 comprised of 02 Basement + Ground + Three Upper Floors owned/occupied by M. N Securities Pvt. Ltd. was issued fire safety certificate by this department vide letter no. F.6/DFS/MS/2010/2488 Dated 27/08/2010 The premises was re-inspected by the officer concerned of this department on 01/05/2014 in the presence of Sh. Mukesh Arora and found that the building have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010, and premise is fit for class Group 'F' Mercantile Building (Shopping Mall) with effect from 30 /05/2014 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rule, 2010.

1. Means of escape shall not be kept locked or bolted from outside and shall be easily open able by guests in an event of emergency.

2. All employees shall be acquainted with the use and maintenance of all the fire fighting

installation/equipments.

3. The fire suppression / protection arrangements provided in the guest house are to minimize losses, if maintained in good working condition. These systems cannot give any guarantee that there will be no fire or losses in the event of one.

4. Any loss of life and property due to non-functional of fire safety arrangements and other

installations shall be the responsibility of the licensee.

5. This report may not in any way be treated as regularization of unauthorized construction,

6. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on WWW.dfs.Delhigovt.nic.in

Issued on 30 55/14 at New Delhi.

ntokh Singh Chief Fire Officer

Delhi Fire Service

E-mail: cfowz.dlfire@nic.in Phone: 011-23414250

Copy to:-

1. Sh. Mukesh Arora, Authorized signatory, M. N. Securities Pvt. Ltd, Statesman House, 8th Floor, Barakhamba Road, New Delhi 110001

INSPECTION REPORT

02 Basement + G + Three upper floors

1. Name & address of the building : North Gate Mall, Gujranwala Town - II, Delhi-

2. Type of Occupancy : Shopping Mall, Mercantile (Group- F)

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/2010/2488 Dated 27/08/2010

5. Fire Safety directives letter No : F.6/DFS/MS//BP/2006/3738 Dated 21/02/2006

6. Date of inspection : 01/05/2014

7. Name of the Inspecting Officers : DCFO (WZ) & DO (NW)

8. Name and designation of officers

from the building side : Mukesh Arora

9. Year of Construction :

10. Applicant's letter No. : L.No- Nil dated 21/04/2014

S. No	Minimum Standards on fire prevention and fire safety U/R 33	BBL & NBC Requirement	Provided at site	Remarks MR/NMR
1	Access to building			
	 Road width 	24 m	P	M.R.
	Gate width	06 m	Р	M.R.
	Width of internal road	06 m	P	M.R.
2	Number, Width, Type & Arrangement	of Exits		2 "
	a. Number of staircases			H C
	Upper Floors	06	P	M.R.
	• Basements	06 + 02 ramp	Р	M.R.
	`b. Width of staircases			7
	• Upper Floors	Old case	Old case	Old case
	• Basements	Old case	Old case	Old case
	c. Protection of exits			
	Fire check door	R	Р	M.R.
	 Pressurization 	N.A	Stairs open to sky	N.A
	d. No. of continuous staircases to terrace			
	e. Width of Corridor	1.5 mtr	P	M.R.
	f. Door Size	Old case	Old case	Old case



N) 15

Compartmentation	*				
Compartmentation.					
Fire check door	R	P	M.R.		
Sealing of electrical shafts	R	P	M.R.		
Fire Rating of shaft door	R	P	M.R.		
> Water Curtain	R	P	M.R.		
Fire Dampers	R	P	M.R.		
Smoke Management System.					
> Basements	30 a/c per hour	P	M.R.		
> Upper floors	12 a/c per hour	P	M.R.		
Fire Extinguishers					
	64	W co ₂ DCP type	M.R.		
32. 850006	One @ 300 m ²	P	M.R.		
	ISI marked				
		yes	M.R.		
First-Aid Hose Reels.					
Total numbers on each floor	06 at each floor	P	M.R.		
 Length of hose reel hose 	30mm	P	M.R.		
Nozzle diameter	5mm	P	M.R.		
Automatic fire detection and alarming system.					
> Type of detectors	Smoke & heat	P	M.R.		
Location of Main Panel	GF	P	M.R.		
Location of Repeater Panel	Each floor	P	M.R.		
➤ Alternate source of power	R	P	M.R.		
➤ Hooters' Location	Comman areas	9			
MOEFA	R	P	M.R.		
Public Address System	D				
	K.	P	M.R		
Automatic Sprinkler System.					
Basement	R	р	MD		
Upper Floor	R	P	M.R M.R		
F 1			**1*1/		
	 Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System. Basements Upper floors Fire Extinguishers Total numbers Types IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System. Automatic Sprinkler System. Basement 	Fire check door R Sealing of electrical shafts R Fire Rating of shaft door R Water Curtain R Fire Dampers R Smoke Management System. Basements 30 a/c per hour Upper floors 12 a/c per hour Fire Extinguishers Total numbers 64 Yppes ISI marked ISI marked First-Aid Hose Reels. Total numbers on each floor 06 at each floor Length of hose reel hose 30mm Nozzle diameter 30mm Automatic fire detection and alarming system. Type of detectors Smoke & heat Location of Main Panel GF Location of Repeater Panel Each floor Alternate source of power R Hooters' Location Comman areas MOEFA R Public Address System. R Automatic Sprinkler System. R	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers R P Smoke Management System. Basements Upper floors Total numbers Types IS marking First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming system. Type of detectors Location of Repeater Panel Alternate source of power Hooters' Location MOEFA R P R P R P W co2 DCP type W co2 DCP type W co2 DCP type One @ 300 m² P ISI marked Yes W co2 DCP type One @ 300 m² P Of at each floor Of at each floor Of at each floor Each floor P Smm P Comman areas P Comman areas P Automatic System. R P Automatic System. R P Automatic System. R P Automatic Syrinkler System.		



11	Internal Hydrants				
	> Size of riser/down-comer	100 mm	P	M.R	-
	Number of hydrants per floor	06	P	M.R	1
	Hose Box	06	P	M.R	1
12	Yard Hydrants.				
	Total number of hydrants	10	Р	M.R.	
	➤ Hose Box	R.	P	M.R.	
13	Pumping Arrangements.			¥	
	Ground Level				
	Discharge of main Pump	2280 LPM	P	M.R.	
	➤ Head of Main pump	60 M	P	M.R.	
	> Number of main pumps	02	P	M.R.	
	> Jockey Pump out put	180 LPM	P	M.R.	
	Jockey pump head	60 M	P	M.R.	
	Standby Pump out put	2280 LPM	P	M.R.	-
	Standby Pump Head	60 M	P	M.R.	/
	> Auto Starting/ Manual stopping	R	P	M.R	-
	> Pump House Access	R	Р	M.R	1
	Terrace level				
	Discharge of pump				
	Head of the pump		_		
8	> Power Supply				
a u	> Auto Starting of pump	_	_		
14	Captive Water Storage for fire fighting.				
	Underground tank capacity	3,00,000 ltr	P	M.R	-
	> Draw-off connection	R	P	M.R	
	> Fire service inlet	R	Р	M.R	
55	> Access to tank	R	Р	M.R	7
	Overhead Tank capacity	30,000 Ltr	P	MR	_
15	Exit Signage.	R	P	MR	/
16	6 Provision of Lifts.				

•		J17		
•	Pressurization of Lift Shaft Pressurization of Lift lobby	R	P & F	DA W
•	Communication In lift Car			M.R
	Fireman's Grounding Switch Lift Signage	R	P	M.R
17 Standby p	ower supply	R	P	M.R
18 Refuge Ar		R	P	M.R M.R
> Totale > Locale 19 Fire Control		N.A N.A	N.A N.A	N.A N.A
	etor System Panel Switch Panel	R	P	MD
1	stem Panel	R R	P	M.R M.R
	backup	R	P	M.R
Special Fire I	Protection Systems for	R	P	M.R M.R
Protection of	special Risks, if any:		No special risk seen at time of inspection	MAR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of the fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/2010/2488 Dated 27/08/2010 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Name

Designation

Signature of the Inspecting Officer

Name

Designation

